

# Resene Paint Prep and Housewash

liquid concentrate

Resene Paint Prep and Housewash is a quick and easy way to clean surfaces ready for painting or use annually to give homes and buildings a fresh look by washing away dirt and contaminants that may be present.

## exterior/interior

### Typical uses

- Painted surfaces

<b>Vehicle type</b>	Blend of anionic and nonionic surfactants
<b>Form</b>	Concentrated solution
<b>Solvent</b>	Water
<b>Viscosity of solution</b>	Water thin
<b>Colour</b>	Pale yellow
<b>Mixing ratio</b>	1 part Resene Paint Prep and Housewash to 3 parts water
<b>Number of applications</b>	1
<b>Usage (diluted mix)</b>	10-20 sq. metres per litre
<b>VOC</b>	c. 105 grams per litre (see <a href="#">Resene VOC Summary</a> )

### Physical properties

### Performance and limitations

- Performance**
1. Provides an immediately cleaner surface.
  2. Helps maintain the longevity of the paint finish.

- Limitations**
1. Do not add Resene Paint Prep and Housewash to paint.
  2. Mild steel and aluminium are attacked by Resene Paint Prep and Housewash and are unsuitable materials for either storage or application equipment.
  3. Ensure product is well rinsed off glass surfaces. Concentrated product left on glass surfaces may etch the surface.

# Paint Prep and Housewash liquid concentrate

## Application

Wear adequate protection. Use overalls, gloves, eye protection and suitable footwear.

Mix with water and apply by brush, knapsack, garden or conventional spray. Scrub vigorously using a nylon bristle broom or short, hard bristle scrubbing brush to remove all dirt, grease, mould and any loose flaking paint. Rinse with clean water.

Use more concentrated mixes to clean more heavily soiled surfaces.

## Precautions

Do not allow the product to come into contact with plants, stormwater outlets, streams or animals. May kill aquatic life if allowed to enter the stormwater system. Divert all roof runoff to a sewer or alternative catchment system.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.  
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

**In Australia**  
PO Box 785, Ashmore City, Queensland 4214  
Call 1800 738 383, visit [www.resene.com.au](http://www.resene.com.au)  
or email [advice@resene.com.au](mailto:advice@resene.com.au)

**Resene**  
the paint the professionals use

**In New Zealand**  
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Call 0800 RESENE (737 363), visit [www.resene.co.nz](http://www.resene.co.nz)  
or email [advice@resene.co.nz](mailto:advice@resene.co.nz)