



Te Awahou Nieuwe Stroom, photo by Jason Mann

Pinetech Cladding

Plytech Pinetech Cladding is a bandsawn exterior plywood panel for use in residential and commercial construction. Pinetech Cladding is a cost effective cladding solution that offers a natural timber finish and allows for staining to enhance the look and performance. Pinetech Cladding is envelope treated H3.1 LOSP or H3.2 CCA for exterior use.

OPTIONS

- Pinetech 1000/100: grooves at 100mm centres
- Pinetech 1000/150: grooves at 150mm centres
- Pinetech 3000: no grooves.

DIMENSIONS

2440 x 1216mm x 12.0mm

FINISHING

We recommend that both faces and all edges of the uncoated plywood are coated.

TECHNICAL SPECIFICATIONS

Standard – AS/NZS 2271

Wood Raw Material – Pinus Radiata

Density – average 500kg/m³

Class – Softwood, non-durable

Glue Bond – A Bond Exterior

Glue Formaldehyde Emissions – E0 < 0.3mg/L, (AS/NZS 2098.11).

COLOUR CONSISTENCY

It is not possible to guarantee an absolute consistency in colour of plywood between sheets. A slight variation between sheets cannot be considered a defect. Check sheets before commencing your project.

EXPOSURE TO WATER AND SUNLIGHT

Direct or indirect light will have an effect on plywood products. A change in colour and appearance over time is a natural characteristic, and not considered a defect.

HANDLING AND STORAGE

Plywood is a natural product that can be affected by changes in weather, causing previously flat sheets to bow or twist. All

precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. Avoid leaning sheets against walls. Store where construction traffic and activity will not damage sheets. Keep the surface free of contaminants such as dust, oil and adhesives.

The storage area should be protected from sun, rain and wind to minimise rapid changes in temperature and humidity. Treat sheets as a finished product and avoid dragging sheets across other surfaces.



Pinetech Cladding



PLYTECH SHOWROOM

26 Business Parade North, PO Box 204-070, Highbrook, Auckland 2161, New Zealand. Phone: 09 573 5016, Fax: 09 573 5035

sales@plytech.co.nz

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade.

plytech