



+Hollow masonry

STANDARD PRODUCT RANGE 2017



10 SERIES

10.01 Standard Whole (also supplied as two core in some areas)

H10.01 Standard Whole Half High (also supplied as two core in some areas)

10.02 Half

10.03 Corner

25 SERIES

H25.04 Half High

25.05 Open End and Plain End

25.09 (North Island only) Rebate Whole

25.11 (North Island only) Rebate Half

25.12 Lintel and Half-End Closer

25.14 Knock-in Bond Beam

25.15 Left Hand Corner Bond Beam (right hand also available)

25.16 Open End Bond Beam Depressed Web

15 SERIES

H15.04 Plain End Half High

15.08 Sill (projecting)

15.09 Rebate Whole

15.04 Plain End Standard

15.11 Rebate Lintel

15.14 Knock-in Bond Beam

15.15 Right Hand Corner Bond Beam (left hand also available)

15.16 Open End Bond Beam Depressed Web

15.12 Lintel and Half-End-Closer

HOTBLOC® 25 SERIES

H20.08HB Thermal Sill

HOTH25.04 Thermal Half High (Only suitable for a single course in a wall)

2xH20.08HB+1xHOTH25.04 Sill Option to achieve 190 height

HOT25.09 Thermal Rebate Whole

HOT25.11 Thermal Rebate Half

HOTSTD25 Thermal Whole, Knock-in Bond Beam

HOT25.12 Thermal Lintel and Half-End Closer

HOT25.15 Left hand corner bond beam (Right-hand also available)

20 SERIES

20.02 Half

H20.04 Plain End Half High

H20.14 Half High Bond Beam (Available in Auckland only)

20.05 Open End

20.08 Sill (projecting 50mm)

H20.08 Sill (flush available in Auckland only)

20.09 Rebate Whole

20.11 Rebate Lintel

20.12 Lintel and Half-End-Closer

20.14 Knock-In Bond Beam (Universal)

20.15 Corner Bond Beam

20.16 Open End Bond Beam Depressed Web

20.19 Three Quarter

20.30 Standard Column

20.33 Flier (available North island only)

20.34 Plaster 'C' Type

20.44 Knock-In Half Bond Beam (available North island only)

20.45 Header

05.17 Capping

USEFUL ESTIMATING DATA FOR HOLLOW MASONRY

BLOCKFILL VOLUME				UNITS PER SQUARE METRE			
15 SERIES	20 SERIES	25 SERIES	HotBloc® 25 SERIES	10 SERIES	15 SERIES	20 SERIES	25 SERIES
165 BLOCKS/M3	125 BLOCKS/M3	85 BLOCKS/M3	125 BLOCKS/M3 (40MM POLY)	12.5 UNITS	10 SERIES	15 SERIES	20 SERIES
					25 UNITS		

FIRTH RECOMMENDS DRICON® TRADE MORTAR®

- 30kg bag size for ease of use
- Approximately 23 blocks laid per bag
- Trade Mortar is formulated to meet NZS4210:2001 Masonry Construction: Materials and Workmanship of 12.5MPa after 28 days (under standard curing conditions)
- Contains a dry plasticiser accepted and endorsed by key trade users
- Minimises site waste
- Has consistent material calculations from bag to bag



AM Blocks available as Architectural Masonry [AM]. AM is recommended for honed and polished finishes. Sealing is recommended for all AM. Not all AM is available as stock product - check for availability and lead times in your area.



VISIT FIRTH.CO.NZ OR CALL 0800 800 576 FOR MORE INFO