

CMP-A, CMP-ADJ, CMPH & CMP-S

Product Ordering Key and Suggested Specifications

CMP	-	A	-	1	-	41	-	450x450	-	600x600	-	OBD	-	TRV	-	SRA 300 DIA CH 300 DIA	-	FINISH	
⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮	
Ceiling Multi Pattern		Aluminium		Frame Style		Core Pattern		Duct Size		Module Size		Opposed Blade Damper Attached		Throw Reducing Vanes		Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat	

Ceiling Multi Pattern Louver Face diffusers shall be type CMP-A and be all Aluminium construction with removable core, to give the air distribution pattern shown on the drawings. They shall be available with a range of frame styles and purpose made accessories for both throw adjustment and volume control.

All shall be as manufactured by Holyoake.

CMP-ADJ	-	2	-	41	-	225x225	-	600x600	-	OBD	-	TRV	-	SRA 150 DIA CH 150 DIA	-	FINISH	
⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮	
Ceiling Multi Pattern - Adjustable		Frame Style		Core Pattern		Duct Size		Module Size		Opposed Blade Damper Attached		Throw Reducing Vanes		Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat	

Ceiling Multi Pattern - Adjustable Louver Face diffusers shall be type CMP-ADJ. They shall be of all Aluminium construction, with removable cores. CMP-ADJ are fitted with vanes which can easily be adjusted to enable vertical, or horizontal throw.

All shall be as manufactured by Holyoake.

CMPH	-	2	-	41	-	300x300	-	600x600	-	OBD	-	TRV	-	SRA 150 DIA CH 150 DIA	-	FINISH	
⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮	
Ceiling Multi Pattern Horizontal		Frame Style		Core Pattern		Duct Size		Module Size		Opposed Blade Damper Attached		Throw Reducing Vanes		Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat	

Ceiling Multi Pattern Horizontal Louver Face diffusers shall be type CMPH and be all Aluminium construction with additional horizontal blades. Complete with removable core to give multiple air distribution patterns. They shall be available with a range of frame styles and accessories for both throw adjustment and volume control.

All shall be as manufactured by Holyoake.

CMP	-	S	-	2	-	41	-	450x450	-	600x600	-	OBD	-	TRV	-	SRA 300 DIA CH 300 DIA	-	FINISH	
⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮		⋮	
Ceiling Multi Pattern		Steel		Frame Style		Core Pattern		Duct Size		Module Size		Opposed Blade Damper Attached		Throw Reducing Vanes		Square to Round Adaptor or Cushion Head		Holyoake White Powder Coat	

Ceiling Multi Pattern Louver Face diffusers shall be type CMP-S and be of Steel construction with removable core, to give the air distribution pattern shown on the drawings. They shall be available with a range of frame styles and purpose made accessories for both throw adjustment and volume control.

All shall be as manufactured by Holyoake.

Note: All ceiling diffusers, seismic restraints required, but not supplied.

CMPP, CMP - T & CMP - TL

Product Ordering Key and Suggested Specifications

CMPP	–	1	–	300x300	–	450 x 450	–	OBD	–	SRA 300 DIA CH 300 DIA	–	FINISH
⋮		⋮		⋮		⋮		⋮		⋮		⋮
Ceiling Multi Pattern Plaque		Frame Style		Duct Size		Module Size		Opposed Blade Damper Attached		Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat

Ceiling Multi Pattern - Plaque Louver Face diffusers shall be type CMPP. They shall be of all Aluminium construction, with removeable plaque core. CMPP have a range of frame styles and accessories for installation and volume control.

All shall be as manufactured by Holyoake.

CMP-T	–	1	–		–	450x450	–		–	SRA 300 DIA CH 300 DIA	–	FINISH
⋮		⋮				⋮				⋮		⋮
Ceiling Multi Pattern - Thermal		Frame Style				Neck Size				Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat

Ceiling Multi Pattern - Thermal Louver Face diffusers shall be type CMP-T. They shall be of Aluminium construction, with removeable cores. CMP-T central cores, are complete with a vertical supply section controlled by a thermally actuated damper. Supply air is diffused horizontally below temperatures of 24°C and vertically above temperatures of 28°C.

All shall be as manufactured by Holyoake.

CMP-TL	–	1	–		–	450x450	–		–	SRA 300 DIA CH 300 DIA	–	FINISH
⋮		⋮				⋮				⋮		⋮
Ceiling Multi Pattern - Thermal Low Cost		Frame Style				Neck Size				Square to Round Adaptor, or Cushion Head		Holyoake White Mill Aluminium Powder Coat

Ceiling Multi Pattern - Thermal Low Cost Louver Face diffusers shall be type CMP-TL. They shall be of Aluminium construction, with removeable cores. CMP-TL central cores, are complete with a vertical supply section controlled by a thermally actuated damper. Supply air is diffused horizontally below temperatures of 24°C and vertically with temperatures above 30°C.

All shall be as manufactured by Holyoake.

Note: All ceiling diffusers, seismic restraints required, but not supplied.