




Merchant Price List

GLASS FIXINGS - BUTTON HEADS

Button Head Fixings	Code	Description 304 Stainless Steel Buttons	Price
 <p>"X" equals tightened thread length between button heads.</p>	DB19-X	Replace "X" in code with required length of thread between buttons when tightened. Double Button Heads 19mm diameter	
	DB25-X	Double Button Heads 25mm diameter	
	DB32-X	Double Button Heads 32mm diameter	
	DB38-X	Double Button Heads 38mm diameter	
	DB50-X	Double Button Heads 50mm diameter	
			All double button heads are supplied with two nylon washers and sleeve.
 <p>"X" equals length of rod.</p>	BT19-X	Replace "X" in Code with required length of threaded rod. Stock length 18mm. Button Head 19mm diameter	
	BT25-X	Button Head 25mm diameter	
	BT32-X	Button Head 32mm diameter	
	BT38-X	Button Head 38mm diameter	
	BT50-X	Button Head 50mm diameter	
			All single button heads are supplied with two nylon washers and sleeve.
 <p>"X" equals length of Lag Screw. Minimum length 25mm Maximum length 55mm. Note: 50mm diameter minimum length 50mm</p>	BL19-X	Replace "X" in Code with required length of Lag Screw. Stock length 18mm. Button Head 19mm diameter with Lag Screw	
	BL25-X	Button Head 25mm diameter with Lag Screw	
	BL32-X	Button Head 32mm diameter with Lag Screw	
	BL38-X	Button Head 38mm diameter with Lag Screw	
	BL50-X	Button Head 50mm diameter with Lag Screw	
			All single button heads are supplied with two nylon washers and sleeve.
		Note: Lag Screw and Rod sizes 19mm Button - M6 } Minimum Lag Screw length 25mm 25mm Button - M6 } 32mm Button - M8 } Minimum Lag Screw length 30mm 38mm Button - M8 } 50mm Button - M10 - Minimum Lag Screw length 50mm	