

WOVON

The Polyflor Wovon interwoven vinyl flooring a collection of diverse weave designs offering a varied yet unmistakable textile feeling. With the advantages of its heavy commercial vinyl construction the Wovon collection is a hard wearing, low maintenance option for commercial and residential locations. Such areas include Office, Retail and Hotels.



PRODUCT SPECIFICATION



- The flooring shall be Polyflor Wovon interwoven vinyl flooring, as supplied by Polyflor Ltd. of Manchester, England.
- The flooring shall be flexible PVC tile flooring in 3.1mm thickness.



- The flooring material shall fully conform with the European Norm for EN 1307 TEXTILE FLOOR COVERINGS
- In respect of flamespread, the flooring shall be certified as Class Bfl-S1 according to EN 13501-1.
- This product does not accumulate static charges above 2kV and is classified as 'antistatic' when tested to EN 1815. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.
- The product's weight should not be more than 3750g/m².
- The flooring is suitable for Use Area Classification 23/33, as defined in EN 1307
- In respect of light fastness, the flooring shall have been fully tested to ISO 105-B02 Method 3 and obtain ≥ 6 .



- The manufacturer should provide a facility to take back and recycle waste vinyl flooring material through the Recofloor scheme.
- Polyflor Wovon interwoven vinyl flooring achieves a very low VOC emissions result when tested to AgBB standards.



- The manufacturer of the floorcovering must be in possession of a valid quality systems certificate, showing compliance with BS EN ISO 9001.
- The manufacturer of the floorcovering must be in possession of a valid environmental certificate, showing compliance with ISO 14001.



- A moisture test must be carried out, to ensure that the subfloor has dried out to a level consistent with the application of vinyl flooring. The test should be carried out using a hygrometer, in accordance with the instructions in BS 8203. The result should not exceed 75%RH, once equilibrium has been achieved.
- The adhesive used must be approved by Polyflor, to ensure full product compatibility.
- Products must be fully conditioned to the environment in which they are to be installed. See Polyflor installation instructions for details.
- Installation must be carried out in accordance with BS 8203 and the instructions of Polyflor.
- Suitable for use with underfloor heating up to 27°C. See Polyflor installation instructions for details.
NOTE: Recommended fit – Serene tile: Tessellate and Broadloom. Optics & Structure: Tessellate only



- We recommend that adequate UV protection be taken against products being installed in direct sunlight as fading may occur.
- For further information and advice on specific applications, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com.



- At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.

