

CARE AND MAINTENANCE GUIDE JULY 2021

Created from Orientated Strand Board (OSB) IBS EUROFloor is an edge sealed, tongue and groove profiled, flooring substrate. It is for internal use with timber or steel framing.

IBS EUROFloor is a 2 man lift and is a strong, dimensionally stable panel that resists warping and delamination. IBS EUROFloor is not intended to be left in its raw state and will need to be sealed or covered for its in situ life.

Finishing the Floor

IBS EUROFloor is required to be sealed or overlaid with an appropriate protective floor covering (tile, carpet etc) or a paint (not water based) or a membrane system compatible with a composite timber.

Where the panels are used in areas prone to water splash, a waterproof membrane or impervious floor covering must be used.

Maintenance

Under normal conditions IBS EUROFloor requires no maintenance providing that the protective covering has been maintained. If water damage occurs to an area where IBS EUROFloor has been used, ensure the area is allowed to dry before replacing any covering or coating. The moisture content is to be approximately between 12% and 14% before resealing.



NOTE:

Maximum exposure to weather must not exceed 90 days. IBS EUROFloor may need mechanical sanding on the joins if being covered or a full sand if being clear finished.

Scan the QR code to view all IBS EUROFloor documents.



NZBN 9429000097253

IBS EUROFloor Product Details

L x W x Thickness (mm)	Weight (kg)	IBS Product Code	GTIN
2400 x 1200 x 20	36.7	OSBF202412	09421028769877
3600 x 1200 x 20	55.1	OSBF203612	09421028769877