

UM mesh 140 x 30

Technical data

		Substance
Material		3D separation layer
Attribute	Regulation	Value
Thickness		9 mm
Reaction to fire	EN 13501-1	E
Exposure time		3 months
Tensile strength MD/LD	EN 12311-1	70 ±15 N/5 cm / 40 ±15 N/5 cm
Temperature resistance		-20 °C to +80 °C

Area of application

9 mm SEPARATION MESH is suitable for ventilated or unventilated structures in combination with all SOLITEX® roof and wall underlays and with any type of roofing or facade materials such as titanium zinc, aluminium, stainless steel, galvanised steel, copper etc.

Forms of delivery

Art. no.	GTIN	Length	Width	Contents	Weight	Sales unit	Container
1AR01832	4026639218322	30 m	1.4 m	42 m ²	12.8 kg	1	9

Advantages

- ✓ 3D separation layer provides increased acoustic insulation and ventilation between roof underlay on solid substrate and the metal cladding
- ✓ very high thermal stability

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

MOLL