



# SPECIFICATION SHEET

## DEVAN 15000L - STANDARD DUTY - SOUTH ISLAND

<b>Code</b>	TT15S
<b>Empty weight</b>	275kg
<b>Specific gravity - max</b>	1.0
<b>Max working temperature</b>	30°C
<b>Raw material type</b>	Medium density polyethylene
<b>Raw material standards</b>	AS/NZS 2070 - Food contact requirements AS/NZS4020:2005 - Potable drinking water AS/NZS4766 Polyethylene storage tanks for water
<b>Complying water tank standard</b>	AS/NZS4766 Polyethylene storage tanks for water
<b>Manhole opening size</b>	435mm (located at 6 o'clock)
<b>Diameter</b>	2.95m
<b>Overall height</b>	2.6m
<b>Overflow height</b>	2.2m
<b>Overflow panels</b>	4 off (1, 5, 7 & 11 o'clock)
<b>Height to dome part line</b>	2.1m
<b>Outlet size</b>	50mm BSP
<b>Outlet - base to centre line</b>	120mm
<b>Maximum no. of moulded in outlets</b>	4
<b>Outlet location(s) - standard</b>	1 & 7 o'clock
<b>Other available locations - non standard</b>	5 & 11 o'clock
<b>Lifting eyes</b>	4 (1, 5, 7 & 11 o'clock)

