




Contents

- 1. Introduction
- 2. Strength and Versatility
- 3. Design Initiative
- 4. Our Board Profiles





Designed for New Zealand Weather Conditions



Strength and Versatility

- Don't spend your weekends or budget on house maintenance. Install ULLTRACLAD,[®] the low maintenance cladding system, designed in New Zealand by Ullrich Aluminium for New Zealand weather conditions.
- With a massive 25 year warranty, ULLTRACLAD[®] has been design tested to withstand all weather variables including; high temperatures, extra high wind speed (NZS3604:2011), sea spray zones and of course to keep moisture out.
- ULLTRACLAD[®] is equally suited to classic or modern home styles, giving architects and designers the ability to design something unique using a product that will stand the test of time.
- With its quick installation and prefinished coating you can enclose your building quickly and safely.
- ULLTRACLAD® has been seismically tested by BRANZ. The following conclusion was included in their report: "In an earthquake, the ULLTRACLAD® wall system tested is expected to 'ride out' the expected displacements of the light timber frame to which it is attached with no observable damage up to racking displacements of +48mm. Damage at the completion of racking displacements of +65mm is expected to be slight with no components failing or falling."





The Permanent Cladding Solution for Today's Market



Our Board Profiles

- ULLTRACLAD[®] is available in six profiles, allowing it to be specified for both domestic and commercial applications.
- The boards are extruded from premium grade aluminium as a weatherboard profile
 with either a smooth or textured surface. When installed, ULLTRACLAD[®] is
 effectively 15mm thick and ranges from 140mm to 205mm in depth. It is extruded
 in both 5m and 6m lengths.



Overview

Material Type Aluminium (T5 6060)

BRANZ Approved Yes

Mass 'Lightweight' (NZS:3604.2011)

Wind Zones Up to and including 'Extra High Wind Speed' (NZS:3604.2011)


Direct FixUp to Risk Matrix of 12 (refer NZBC/E2)Cavity FixUp to Risk Matrix of 20 (refer NZBC/E2)

Warranty 25 Years

Fixing Type Aluminium Bracket with Stainless Steel Screw (hidden fixings)

Finish Type Dulux Powder Coating range

Seismic Testing Yes (BRANZ ST0871)







Representative and franchised operations throughout the South Pacific

ULLRICH ALUMINIUM PTY LTD
PO Box 246 Carole Park Queensland 4300
20 Ron Boyle Crescent Carole Park Queensland Australia
Tel +61 7 3718 1400 Fax +61 7 3271 1230
ullrich@ullrich.com.au www.ullrich.com.au

ULLRICH ALUMINIUM CO LTD
PO Box 98 843 Manukau City
Auckland 2241 New Zealand
Tel +64 9 262 6262 Fax +64 9 262 6265
alkalum@uacl.co.nz www.ullrich.co.nz

SALES & DISTRIBUTIONEXTRUSION PLANT