

## WIRING

## ATTENTION -

## Ensure link wires provided are fitted between all Neutral and Earth busbars, where appropriate.

No link between the Neutral and Earth Busbars is required on busbars dedicated to RCD protected circuits

## SPECIFICATIONS

Complies with	AS/NZS 3439.3	Rated Insulated Voltage Rated Current of Board	
		Rated Operational Voltage Short Circuit Withstand Strength For Indoor or Outdoor use	. 415V à.c.
		Suitable for connection of copper wire Degree of Protection	. IP66

Description	Weight (with enclosure)	Board Size (with enclosure)	Hole Size
56CB4 Cover	1.1kg	102W x 110D x 198H	1 x 25mm, 1 x 32mm
56CB13 Cover	1.8kg	295W x 123D x 198H	6 x 25mm, 2 x 32mm

The above products have a 12 month warranty from the date of purchase providing the unit is installed according to these instructions, local wiring regulations and Codes of Practice. This warranty is void on any unit which has been tampered with, damaged by accident improper operation or incorrect installation. This guarantee is in addition to, and does not in any way affect the rights under the Consumer Guarantees Act 1993, if the ACT applies to the supply of this product and you are not acquiring the product for a business use. If the ACT applies and any term is inconsistentwith the terms or requirements of the ACT that term shall be invalid without affecting the remaining terms of the warranty. Note: Under the CGA 1993, Schneider Electric advises that this product does not contain user serviceable components thus spare parts and repair facilities are not available. In the event of a warranty claim, the proof of purchase.





New Zealand Head Office: PO Box 15 355, Auckland, New Zealand Telephone +64-9-829 0490, Fax +64-9-829 0491 www.schneider-electric.co.nz Australia Head Office: Locked Bag 5500, Baulkham Hills Business Centre,

NSW 2153, Australia Telephone +61-2-9851 2800, Fax +61-2-9629 8340 www.schneider-electric.com.au

