



IBS HARDCORE FORMPLY

PURPOSE

IBS supplies Hardcore Formply for use as part of a structural formwork system for use with in-situ concrete.

EXPLANATION

IBS Hardcore Formply:

- > is an 11-ply hardwood plywood
- > is supplied as 2400 x 1220 x 17 mm sheetsthird-party certified to AS 6669:2016
- > is available in two stress grades: F14 and F17
- > has a class 2 finish
- > is Super E0
- > has climate-resistant A grade Water Boil Proof (WBP) Phenolic glue lines
- > has anti-abrasive, wrinkle-resistant 130 160 gm/m² Stora-Enso protective paper overlay
- > is painted with a water-resistant paint on all edges.

SCOPE AND LIMITATIONS OF USE



For further assistance			
please contact:			
0	0800 367 759		
0	info@ibs.co.nz		
	www.ihs.co.nz		



Scope	Limitations
Building	
Where the maximum construction requirements for the concrete structure is designed in accordance with NZS 3101:2006.	
Where the formply is specified in accordance with AS 3610.1 <i>Formwork for concrete.</i>	> A sheet can be reused 5 to 8 times each side, provided it is used, stored and maintained as instructed.
	> Release agents must not come into contact with

- Release agents must not come into contact with reinforcement, embedded items, or hardened concrete against which fresh concrete is to be placed.
- > Diesel, petrol, or other oil-based products are not recommended as release agents.
- > Any cut edges must be sealed with paint or sealant.

USEFUL INFORMATION

For information on the design, installation and maintenance of Hardcore Formply and for our warranty refer to ibs.co.nz

OTHER CERTIFICATIONS AND APPROVALS HELD SHANDONG ROGGE WOOD INDUSTRY CO. LTD

> SAI Global FSC Standard for Chain of Custody Certification, certificate no: FCOC40436, exp. 3 May 2021.





PERFORMANCE CLAIMS

If designed, installed, and maintained in accordance with all the IBS requirements, IBS Hardcore Formply will meet the following performance claims:

NZ Building Code clauses	BASIS OF COMPLIANCE		
	Compliance statement ¹	Demonstrated by	
B1 Structure B1.3.1	ALTERNATIVE SOLUTION AS 6669:2016.	Third party certified by bsi Benchmark Product Certification BMP 650464 [23 Jul 2018].	
B1.3.2	10 0000.2010.	> bsi is JASANZ accredited.	
B1.3.3 (a, b, c, j & p)			
B2 Durability	ALTERNATIVE SOLUTION	> Third party certified by bsi Benchmark Product	
B2.3.1(c)	AS 6669:2016.	Certification BMP 650464 [23 Jul 2018].	
		> bsi is JASANZ accredited.	
F2 Hazardous	ALTERNATIVE SOLUTION	> No release of formaldehyde.	
Building Materials	ISO 12460-5:2015.		
F2.3.1			

1. The Compliance Statement is the pass holder's statement that they have met their obligations under s14G(2) of the Building Act 2004.

SOURCES OF INFORMATION

The following information was relied upon to prepare this pass.

- > bsi [2018]. AS 6669:2016. *Plywood formwork*. Benchmark Product Certificate 650464.
- > AS/NZS 2754.1:2016. Adhesives for timber and timber products.
- > NZS 3101:2006. Concrete structures standard.



VERSION:

DATE:

Signed on behalf of IBS Building Products:

Note: Uncontrolled in printed format.

NAME:	Jason Bardell
	Managing Director

By signing this pass[™] the signatory confirms that, in respect of the subject of this pass[™], the company has met their s14G obligations under the Building Act 2004.



IBS Building Products, 1/7 Fraser Road, Panmure, Auckland > info@ibs.co.nz > 0800 367 759 > www.ibs.co.nz

This Product Assurance Supplier Statement (pass™) has been prepared by TBB in accordance with MBIE PTS guidelines and the recommendations of \$9.2, <u>Determination No. 2019-011 (issued 12</u> April 2019). TBB is ISO9001:2016 certified. Copyright © 2017, The Building Business Limited (TBB). All rights reserved.