



MASONS
Designed Smart, Built Tough.

BrickTies

Heavy Duty Earthquake



Complies to AS/NZS2699.1.2000.

Applications

- Used to tie any masonry veneer to a structural frame
- Suitable for Dry and Wet Bed applications

Physical Properties

- Heavy Duty (EH) Earthquake
- Tie sizes: 90mm, 110mm, 135mm
- Hot dipped galvanised and 316 stainless steel

The following is to be used as a guide only

Horizontal	Vertical
400mm	500mm
450mm	450mm
600mm	400mm

Approx. 5 brick ties per m² per 100 ties per 1000 bricks

Product Code	Description	Building Zone	Qty
TIE90HD250	90mm Hot Dipped Galvanised.	Normal	250
TIE90HD250SD	90mm Hot Dipped Galv. Self Drilling Screws for Steel Frames	Normal	250
TIE90SS250	90mm Stainless Steel	Sea Spray	250
TIE90SS250SD	90mm Stainless Steel. Self Drilling Screws for Steel Frames	Sea Spray	250
TIE110HD250	110mm Long Hot Dipped Galvanised	Normal	250
TIE110HD250SD	110mm Long Hot Dipped Galv. Self Drilling Screws for Steel Frames	Normal	250
TIE110SS250	110mm Long Stainless Steel	Sea Spray	250
TIE110SS250SD	110mm Long Stainless Steel. Self Drilling Screws for Steel Frames	Sea Spray	250
TIE135HD250	135mm Hot Dipped Galvanised	Normal	250
TIE135SS250	135mm Stainless Steel	Sea Spray	250