


**Thermakraft™**  
**THERMAKRAFT**  
**215**



**Thermakraft™**

# THERMAKRAFT 215

## Self-supporting bituminous wall and roof underlay

Commonly referred to as 'Building Paper' Kingspan Thermakraft 215 is a self-supporting, kraft paper based, bituminous building underlay that is suitable for use on roofs and walls in residential buildings. It is vapour permeable, meaning that liquid water from the outside is prevented from penetrating but water vapour from the inside can pass through and escape the building envelope. Thermakraft 215 is easy to install.

**Thermakraft 215 comes in two roll sizes:**

1250mm wide	20m long	25m <sup>2</sup> coverage*
1250mm wide	40m long	50m <sup>2</sup> coverage*

\* **Note:** m<sup>2</sup> is the roll size for actual coverage, allow for laps and joins.



# Thermakraft 215

## Self-supporting bituminous wall and roof underlay



### Scope of Use (Roof Application)

- Suitable with masonry tile, metal tile and profiled metal roof cladding.
- Can be used on roofs up to and including NZS 3604 'Extra High' wind zones.
- Refer to installation guide regarding underlay support requirements.
- Will provide temporary weather protection during construction (maximum 7 days), same day coverage recommended.

### Scope of Use (Wall Application)

- Suitable for use with both timber and steel framing, either direct fix or in conjunction with an 18mm minimum drained cavity.
- Can be used with absorbent wall claddings (e.g. timber, brick or fibre cement) or non-absorbent wall claddings (e.g. metal or plastic).
- Can be used with masonry veneer in accordance with NZS 3604.
- Suitable for buildings situated in NZS3604 Building Wind Zones up to and including 'Very High'.
- Thermakraft 215 can be used as an air barrier to reduce wind entry and is highly water resistant.
- Will provide temporary weather protection during construction (maximum 7 day exposure), same day coverage recommended.

### General

Unaffected by LOSP or other solvent based treated timber. However, LOSP or other solvent based treated timber must have sufficient time for the solvent chemical to flash off in well ventilated area. Recommended minimum 7 days.

### Property Performance

The following data represents the minimum pass rates required by the NZBC. This product tests well beyond the minimum standards. If you require actual performance results, please contact your local Kingspan Insulation representative.

### Limitations

- In roof and wall applications must NOT be exposed to the weather or UV for more than 7 days.
- Must NOT be used under translucent sheeting.
- Is not fire retardant.
- Not suitable for School Property, please refer to Ministry of Education: Weathertightness Design Requirements for New School Buildings.

### Compliance

Thermakraft 215 meets the requirements of NZBC Acceptable Solutions E2/AS1, Table 23 and NZS 2295:2006 for both wall & roof underlay.

### Durability

Meets the Performance Requirements of NZBC Clause B2, Durability B2.3.1 (a) 50 years and B2.3.1 (b) 15 years, E2 External Moisture providing:

- It is installed in accordance to Installation Guide.
- Run length is no greater than 10 meters.
- Is not exposed to weather or UV for more than 7 days.
- Is installed by or under guidance of Licensed Building Practitioners.
- Is installed in accordance with the NZ Metal Roof and Wall Cladding Code of Practice.
- Is compatible with the cladding system used.\*

\* **Note:** roof cladding system compatibility testing must be done first before installation.

NZBC E2/AS1 Roof Underlay Requirements					
NZBC E2/AS1 Table 23 (NZS2295) Roof Underlay Properties	Absorbency	Vapour Resistance	pH of Extract	Shrinkage	Water Resistance
Property Performance Requirement	≥ 150gsm	≤ 7 MN.s/g	≥ 5.5 and ≤ 8	≤ 0.5%	100mm for 24 hrs
Property Performance	Pass	Pass	Pass	Pass	Pass

# Thermakraft 215

## Self-supporting bituminous wall and roof underlay



### NZS2295:2006 Classification

NZBC E2/AS1 Table 23 (NZS2295) Roof Underlay Properties	Flammability Index	Wind Zone	NZS2295:2006
Property Performance Requirement	F1 ≤ 5	R2	R2
Property Performance	Non-Fire Retardant	Up to Extra High	Self - Support

### Control of Condensation

In climatic regions where condensation risks are high, such as cold or high humidity areas, care needs to be taken in specifying the correct design and installation method to prevent moisture build-up in the roof cavities.

Factors which adversely affect the condensation risk in roofing systems include:

- Humid, and/or cold climatic regions.
- Warm/Skillion roof construction.
- Low roof cavity air volume and restricted air movement.
- Omitting Vapour Control Layers.
- Occupancy activities which have high moisture loading on conditioned spaces.
- Ceiling penetrations and entry of warm air into roof cavities.
- Low pitched roof.
- Bulk insulation.
- Building structure's ability to naturally dry construction moisture.

Skillion and Warm Roof Construction are particularly sensitive to moisture accumulation and the design and installation of roof construction needs to take into account the higher condensation risks. Refer to NZ Metal Roof and Wall Cladding Code of Practice for details.

For passive ventilation of the roof space, it is recommended that all roof underlays are terminated at the ridge, and if not it should be slit or slotted to allow for passive ventilation. (For further information refer to the NZ Metal Roof and Wall Cladding Code of Practice).

### Product Warranty

Standard Kingspan Insulation Warranty applies. Refer to Kingspan Insulation Warranty statement for further details. This is available online at [thermakraft.co.nz](http://thermakraft.co.nz) or call **0800 806 595**.



**0800 806 595**  
**[www.thermakraft.co.nz](http://www.thermakraft.co.nz)**

Thermakraft and Ausmesh products are brought to you by Kingspan Insulation NZ Limited.

