

Roof Access Hatch

CLEAR DOUBLE GLAZED

A high quality roof hatch, our double glazed roof access is a fully engineered prefabricated unit, manufactured with the best available materials, that allows the introduction of natural light into your access space making it safer for users. Great for either commercial or residential use.

Each hatch is fitted with a internal handle and pneumatic stays for a safe, effortless manual opening up to 80°, offering easy access to the roof. Upstand mounted for a simple and smooth install process with an internal fixing system.


Providing safe & easy roof access from inside the building.

Available in 7 standard sizes and also customizable.

OPTIONS:

- Obscure Glazing
- > Tinted Glazing





Technical Specification

) Compliance	Complies with E2 acceptable solution
Body Construction	Powder Coated Galvanised Steel Outer – .55mm sheet Structural – .75 and 1mm sheet Base - powdercoated Aluminium
> Weather Seal	Continuous all 4 sides Closed cell foam
>Pneumatic Stays	Fully calibrated Effortless self lifting lid Balanced closing
External Fixings	Stainless steel
Glazing	Clear toughened double glazed
Internal Handle	Strong zinc die-cast construction Push button cylinder lock
> Hinges	Stainless steel plate Stainless steel pin Nylon bushes
) Mounting flange	Continuous on all sides
> Mounting style	To kerb/upstand Timber, concrete or aluminium Secured to building structure
Roof pitch range	5 to 60°
Fixings	Min. 2of screws per side Factory punched fixing holes
>Flashings	Upstand to be flashed as per E2 for applicable roofing



Standard Sizes

Model N°	Opening Size
HD66DGpn	660 x 660mm
HD77DGpn	725 x 725mm
HD88DGpn	800 x 800mm
HD107DGpn	1000 x 725mm
HD108DGpn	1000 x 800mm
HD117DGpn	1100 x 725mm
HD118DGpn	1100 x 800mm

Adlux Industries Limited

36 Olive Rd, Penrose Auckland 1061, New Zealand P.O. Box 13-866, Auckland 1643 New Zealand



sales@adlux.co.nz www.adlux.co.nz

