

## **Product Data Sheet**

# WHITE GENERAL PURPOSE TAPE

## General purpose polypropylene tape

Thermakraft White General Purpose Tape has an acrylic adhesive giving it superior bonding in a wide range of environments. It is commonly used on synthetic underlays, or damp-proof membranes such as Thermathene. The tape is also ideal for sealing edges of vapour control layers.

GP Tape is easy to apply and covers multiple underlay joining purposes. It features a high performing acrylic adhesive for extreme environments.

Smarter products. Better buildings. **thermakraft.co.nz** 



# **White General Purpose Tape**

## General purpose polypropylene tape

### Scope of Use

White General Purpose Tape can be used to join the laps of wall and roof underlays, damp proof membranes (i.e. commonly refer to as concrete underlays) and other vapour control products such as foil underlays. Installer or designer must check the compatibility of the tape with the substrate manufacturer.

#### General

- Operating temperature from -10°C to 80°C.
- Roll Size 60mm wide x 66m long.
- Rolls are individually packaged.

#### Limitations

 Thermakraft White General Purpose Tape is NOT a window flashing tape and must NOT be used as a window flashing tape.

## **Product Warranty**

Standard Thermakraft warranty applies. Refer to Thermakraft Warranty Statement for further details. This is available online at **thermakraft.co.nz** or call **0800 806 595.** 

Thermakraft Limited / 0800 806 595

Smarter products. Better buildings.

thermakraft.co.nz

