

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS

Recommended use of the chemical

and restrictions on use:

Surface coating. Applied by brush, roller or spray.

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd

ABN 55 133 404 118

Co. 2355191

Street Address: 150 Hutt Park Road

Lower Hutt, New Zealand

Telephone Number: +64 4 576 6400 **Facsimile:** +64 4 576 6496

Emergency Telephone: 0 800 734 607 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Pigments	-	30-60%	-
Synthetic polymer(s)	-	30-60%	-
Water	7732-18-5	30-60%	-
Propylene glycol	57-55-6	1-<10%	-
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS Issued: 03/02/2014

Substance No: 000000010096



Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the substance or mixture:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

Conditions for safe storage, including any incompatibilities: Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority. However, Workplace Exposure Standard(s) for constituent(s):

Propane-1,2-diol (propylene glycol) (vapour & particulates): WES-TWA 150 ppm, 474 mg/m³; (particulates only): WES-TWA 10 mg/m³.

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS Issued: 03/02/2014

Substance No: 000000010096



As published by the New Zealand Workplace Health & Safety Authority.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.







MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: If there is a risk of eye contact and repeated or prolonged skin contact wear gloves and safety glasses. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous liquid Colour: Coloured Bland

Miscible with water. Solubility: **Specific Gravity:** 1.0-1.7 @20°C Not available Relative Vapour Density (air=1): Vapour Pressure (20 °C): Not available Flash Point (°C): Not applicable Not applicable Flammability Limits (%): **Autoignition Temperature (°C):** Not applicable % Volatile by Weight: Not available Solubility in water (g/L): Miscible Melting Point/Range (°C): Not applicable Boiling Point/Range (°C): 100 (water) Decomposition Point (°C): Not available

pH: 8-10

Viscosity:Not availableEvaporation Rate:Not available

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS

Substance No: 000000010096

Issued: 03/02/2014 Version: 6



10. STABILITY AND REACTIVITY

Reactivity: No information available.

Chemical stability: Stable under normal conditions of use.

Possibility of hazardous reactions: Hazardous polymerisation will not occur.

Conditions to avoid: Avoid contact with foodstuffs. Avoid exposure to frost.

Incompatible materials: Incompatible with oxidising agents.

Hazardous decomposition

products:

Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:No adverse effects expected, however, large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin may result in irritation. May cause skin sensitisation in sensitive

individuals. Repeated or prolonged skin contact may lead to allergic contact

dermatitis.

Inhalation: Where this material is used in a poorly ventilated area, at elevated temperatures or in

confined spaces, vapour may cause irritation to mucous membranes of the respiratory

tract, headache and nausea.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Substance No: 000000010096

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS Issued: 03/02/2014



Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

16. OTHER INFORMATION

Reason(s) for Issue:

Revised Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.

Product Name: 535-LINE DULUX AQUANAMEL SEMI-GLOSS Issued: 03/02/2014 Substance No: 000000010096