ARDEX WPM 155

FAST-DRYING UNDERTILE POLYURETHANE MEMBRANE



ARDEX WPM 155 Rapid is a water-based, modified polyurethaneacrylic liquid membrane developed for high performance under-tile waterproofing. ARDEX WPM 155 Rapid's fast-drying formula allows areas to be tiled in 4 hours and provides extended coverage for minimal cost.

Benefits

- · Tough, flexible film
- Tile in 4 hours
- · Long shelf life
- Excellent adhesion with ARDEX Tile Adhesives
- Environmentally friendly solvent free
- Meets Green Building Council of Australia Greenstar requirements IEQ-13 & IEQ-11
- Class III Membrane as per AS/NZS4858 Wet Area Membranes
- Use with ARDEX STB and STA tapes

Location

- Commercial or Residential
- Internal or External
- Wet areas, balconies, decks, bathrooms
- Under tiling

Coverage

Floors: 0.6m²/litre
Walls: 1.1m²/litre

Drying Times

- Recoat time: 1-2 hours
- Ready to tile: 4-6 hours
- Full cure: 3 days

Substrates

- Concrete
- Render and Screeds
- Fibre-Cement Sheets (wet area grade)
- Plywood
- Plasterboard

Packaging	Code
4L	19728
15L	1972













