

Cabot's Deck & Exterior Stain Oil Based

NZDW0819

Part A	826-Line
---------------	----------

Description

CABOT'S Deck & Exterior Stain is a durable decking stain which rejuvenates and transforms the colour of all exterior timber, decks and garden furniture, delivering a long lasting, beautiful result. It is ideal to enhance the look of timbers such as treated pine and rejuvenate worn timbers. The oil enriched formula protects timber from the most damaging environmental factors. It highlights the natural beauty and extends the life of your exterior timber, decks and garden furniture.

- Features**
- UV protection
 - Water repellent
 - Oil enriched
 - Easy to use
 - Dirt & Mould resistant




- Benefits**
- Blocks out harmful UV rays preventing them from penetrating and damaging the surface while resisting colour fading
 - Forms a water repellent barrier aiding protection against mould and minimises cracking and splitting
 - Penetrates the timber to nourish and protect the timber fibres below the surface.
 - Use a Cabot's Decking Applicator for quick and easy application.
 - Contains powerful ingredients to resist the growth of wood staining mould while providing excellent dirt and stain resistance

Uses

Exterior timber projects including decks, pergolas, fences, gates, weatherboard and garden furniture

Performance Guide

Weather	Excellent	Salt	Good
Heat Resistance	Up to 120C. Prolonged exposure to this temperature will cause yellowing	Water	Excellent
Abrasion	Good		

Typical Properties																											
Gloss Level	Matt - Low Sheen	Thinner	Not required																								
Colour	5 packaged colours, plus tinted colours	Components	1																								
Number Of Coats	1 or 2	Toxicity	Lead free																								
V.O.C. Level	< 625g/L	Touch Dry	1-2 Hours																								
Clean Up	 Thinner																										
Clean Up Description	Mineral Turpentine																										
Application Method	  Brush Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">25</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">25</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">18 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">10</td> </tr> </table>			Solids By Volume	25				Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			25	Recoat Time (min)	18 Hours	Indefinite		Theoretical Spread Rate (m²/L)			10
Solids By Volume	25																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			25																								
Recoat Time (min)	18 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)			10																								
Typical Properties Notes	FINISH Semi transparent (1 coat) to opaque matt finish (2 coats or more). DRYING AND RECOAT TIME All timings quoted at 25 degrees Celsius and 50% humidity. Cooler or humid conditions may require longer																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> ▪ Note: Fill holes and imperfections with a suitable timber putty if required. <p>BARE TIMBER Allow timber to weather for 4-6 weeks. For exterior surfaces, clean with Cabot's Deck Clean following label instructions.</p> <p>PREVIOUSLY PAINTED OR VARNISHED TIMBER Remove back to bare timber using a paint stripper, or sanding. For exterior surfaces, clean with Cabot's Deck Clean following label instructions.</p> <p>PREVIOUSLY STAINED OR OILED TIMBER For exterior surfaces, clean with Cabot's Deck Clean following label instructions. Test if the surface is ready for coating by sprinkling water on the timber. If the water beads on the surface, repeat the application of Cabot's Deck Clean. If water is absorbed into timber, it is ready for coating. For a more transparent look, sand timber back to bare then clean with Cabot's Deck Clean before coating.</p> <p>WEATHERED AND GREY TIMBER For best results, sand timber back to fresh substrate. Clean with Cabot's Deck Clean following label instructions.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> ▪ APPLICATION Stir thoroughly with a broad flat paddle before and during use. Apply liberally along the length of the board including exposed edges and end grain by brush or pad applicator. For an opaque finish apply two coats allowing 18 hours between coats. <p>MAINTENANCE Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions. To achieve a deeper colour or more opaque finish, further coats can be applied</p>

Health And Safety			
MSDS Number	14182301	Using Safety Precautions	Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors, keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any source of ignition. Do not smoke.
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-000014182301.pdf		
Health Effects	14182301 For advice contact a Doctor or Poisons Information Centre AUST 131 126, NZ 0800 764 766. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice. EYE: Irrigate with copious quantities of water. Seek medical assistance if effects persist. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. For further information or a copy of the Product Safety Data Sheet, telephone Cabot's Customer Service Department on AUST 1800 011 006, NZ 0800 222 687. For emergencies phone AUST 1800 033 111, NZ 0800 734 607.	Flammability	Flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Store and use away from sources of heat and ignition. Keep out of reach of children
Disposal	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.	Other	RISK: Flammable. Irritating to skin. May cause sensitisation by skin contact. Harmful: May cause lung damage if swallowed
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
Do not apply this product in temperatures below 10 degrees Celsius or above 35 degrees Celsius, or when rain or heavy dew is expected during the drying period. In hot temperatures do not apply in direct sunlight, cool the timber by lightly dampening with water and coat in the shade. Can be walked on 16 hours after final coat.

Transport And Storage			
Pack A	826-Line	Shipment Name	PAINT
Size	1L 5L 10L	Weight	1.1kg 5.1kg 9.8kg
Flash Point	46	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118

Version 8.0 of Woodcare datasheet NZDW0819 approved on Friday, 26 October 2012 3:20:28 AM (UTC)

