

Blacktex Collection

Range 1 Data Information

Width: 4m

Wear Layer: 0.40mm

Warranty: 10 Years

Slip Resistance: R10



Valley Oak 939L




Columbian Oak 973M



Columbian Oak 939L



Venice Wood 969D



Venice Wood 196L




Zinc 976M



Zinc 996D



White Oak 979L



Safira 996M




White Oak 997D



Venice Wood 196L

BLACKTEX



Product Information

Usage classification	EN ISO 10874 EN 685		23 - 32 - 41
Wear layer	EN ISO 24340 EN 429		0,40 mm
Total thickness	EN ISO 24346 EN 428		2,80 mm
Total weight	EN ISO 23997 EN 430		1950 g/m ²
Standard widths	EN ISO 24341 EN 426		4m
Standard length	EN ISO 24341 EN 426		30 m

Technical Information

Light stability	EN ISO 105 B02		≥ 6
Dimensional Stability	EN ISO 23999 EN 434		≤ 0,40 %
Underfloor heating	EN 12667		Suitable
Residual Indentation	EN ISO 24343-2 EN 433		≤ 0,20 mm
Impact sound	EN ISO 717/2		Δ Lw 15 dB
Castor chair	EN ISO 4918 EN 425		Suitable
Reaction to fire	EN 13501-1		Bfl/S1
Slip resistance	DIN 51130		R10
Dynamic coefficient of friction	EN 13893		> 0,6