



Top Bolt

Bottom Bolt

Meets ANSI A156.3 Type 25.  
UL Listed 90 Minute Fire Doors 8'0" x 8'0"

**FB41P Top and Bottom Bolts (Pair)**

- Fully Automatic—inactive door is latched, bolts are extended when active door closes, door is unlatched bolts retract when active door is opened.
- Low Actuation Forces—Top Bolt Has No Spring Tension.
- Non-handed.
- Bolt throw is 3/4" with a 7/8" vertical adjustment.
- Bolt backset is 3/4"

*DP1 or DP2 optional dust proof strike available, see page C11.*

**FB41T Top Bolt Only**  
**FB41B Bottom Bolt Only**

**FB42 Top Bolt with Auxiliary Fire Latch**

- FB42 Model with Auxiliary Fire Latch eliminates the bottom bolt and is UL Listed for Fire Doors.



Top Bolt

Auxiliary Fire Latch

Meets ANSI A156.3 Type 25.  
UL Listed 20 Minute Fire Doors 8'0" x 8'0"

**Dimensions**

Body Size: 1" Wide x 8-1/2" Long x 2" Deep

Guide Size: 1" Wide x 6" Long x 1/8" Thick

Strike Size: 15/16" Wide x 2-1/4" Long x 1/16" Thick

Rub Plate Size: 1-1/4" Wide x 1-11/16" Long x 3/64" Thick

Auxiliary Fire Latch Size: 1" Wide x 1-3/4" Long x 3-1/4" Deep

**Finishes**

Ives Number	US3	US4	US10	US10B	US32	US32D
BHMA	605	606	612	613	629	630

Hinges & Pivots  
**A**

Pulls & Plates  
**B**

Flush Bolts & Coordinators  
**C3**

Latches, Catches & Bolts  
**D**

Stops  
**E**

Exterior Hardware  
**F**

Miscellaneous Hardware  
**G**