SAFETY DATA SHEET

SECTION 1.	IDENTIFICATION OF THE MATERIAL AND SUPPLIER				
Product Name:	BRUSHABLE CRACK FILLER				
Other Names:					
Recommended Use:	Waterborne flexible coating				
Company Name:	Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND P O Box 38242, Wellington Mail Centre				
Phone:	(04) 577 0500 Fax: (04) 577 0600				
	Resene Paints Limited Australia Address 7 Production Avenue, Molendinar, Queensland 4214 P O Box 785, Ashmore City, Queensland 4214				
Phone	1800 738 383 AUSTRALIA				
Emergency Telephone:					
New Zealand	ealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm				
	New Zealand Poisons Centre: 0800 764 766				
Australia	1800 738 383				
	Australian Poisons Centre: 131 126				
SECTION 2.	HAZARDS IDENTIFICATION				
Hazard Classificat	on HAZARDOUS according to NZ HSNO Regulations				
	Not Regulated under NZS5433 for land transportation				
Risk Phrases					
Safety Phrases					
Substance Classifi					
Hazard Statements					
SECTION 3.	COMPOSITION / INFORMATION ON INGREDIENTS				
Ingredients	% CAS No TWA				
Acrylic Resin	10-30 Not known None Establish				
Water Proprietary ingredie	30-60 7732-18-5 None Establish				
SECTION 4.	FIRST AID MEASURES				
•	h eyes immediately with plenty of water for at least 15 minutes.				
	be harmful if swallowed.				
Dom	h affected area thoroughly with soap and water. hove to fresh air and keep at rest in a position comfortable for breathing.				
Innaica	al conditions caused by exposure				
Aggravatou mouro					
Chronic Health Effe	ects				
Advice to Doctor					
SECTION 5.	FIRE FIGHTING MEASURES				
Extinguisher	Foam, Carbon Dioxide, Dry Chemical				
Hazards from					
combustion products					
Special protective precautions and equipment for firefighters Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit					
-					
	Flash Point n/a n/a n/a				
n/a	Flash Point n/a n/a n/a n/a				

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways. Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Wear protective clothing and breathing apparatus.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water. Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C

Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for mixture Component		No exposure standards has been established for this product					
			athing Zone ppm	Bre	eathing Zone n	ng/m³	
Personal Pro	otection						
Eye:	Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.						
Hands/Feet	Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.						
Other	Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.						
		Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of leated materials. Wash hands thoroughly before handling food.					
Respirator				-			
SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES							
Appearance viscous liquid							
Odour	рН \	/apour Pressure	Vapour Density	Boiling Point	Melt Freeze	Solubility	Volatile by Weig
Ammonia	7-10	n/a	n/a	100°C	0°C	Soluble	35
SECTION 10. STABILITY AND ACTIVITY							

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Material

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

BRUSHABLE CRACK FILLER

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product Refer to individual raw materials

Component

Oral: LD50 mg/kg Dermal: LD50 mg/kg

Inhale: LC50 ppm

SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component

Fish: LC50 mg/Lt

BCF: <100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

UN Number

UN Proper

shipping

Subsidiary risk

Poison Schedule

Packing Group:

HAZCHEM Code n/a

Special precautions for user

SECTION 15. REGULATORY INFORMATION

Class

Group Standard HSR002670 Surface Coatings & Colourants (Subsidiary Hazard)

Approved Handler Not required

SECTION 16. OTHER INFORMATION

Date of Preparation	9/06/2009
Literature references	MSDS's for individual raw material
Abbreviations:	
NOHSC	National Occupational Health and Safety Commission
TWA	Time weighted average
STEL	Short term exposure limit
CAS Numbe	Chemical Abstract Service registry number
	Threshold limit value
Marine Pollutant	Marine Pollutant

Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.