1200 m3/hr



HC60DCXB3

# Wall Chimney Rangehood, 60cm, Box

This Fisher & Paykel 60cm Wall Chimney Box Rangehood quietly and efficiently removes steam and cooking odours.

**Brushed Stainless Steel with black glass** 

## **Dimensions**

Depth	500mm
Height	595 - 1035mm
Width	598mm

### **Features & Benefits**

#### Effective and quiet

This rangehood features three fan speeds, plus a boost function, providing powerful extraction to quickly remove odours and steam. The timer keeps the rangehood working for up to 15 minutes before automatically turning off.

#### Easy to use

This Fisher & Paykel rangehood features a sleek and easy to use touch-control panel. Low energy, dimmable LED lights provide superb illumination over the entire cooking surface.

#### Easy cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe. The stainless steel mesh cover just needs a quick wipe to keep clean. An alert reminds you when to clean the filter to ensure you get the best performance out of your rangehood.

#### Designed to match

This wall chimney box rangehood features sleek black glass and stainless steel styling which will complement any contemporary kitchen and is designed to match the rest of Fisher & Paykel's kitchen appliance family.

## **Specifications**

Maximum motor performance

Cleaning	
Dishwasher safe filters	
Filter cleaning alert	
Stainless steel filter cover	
Controls	

Control type	Capacitive touch
Dimmable lights	•
Light type	2x LED Spot
Timer function	•
For vetions	
Fan ratings	
Maximum decibel rating	65 dBA

020 m³/h#	Maximum pressured air movement
820 m³/hr	EN61591 at boost
65	Maximum sound rating at boost
400 m <sup>3</sup> /hr	Speed 1 Pressured air movement EN61591
554 m³/hr	Speed 2 Pressured air movement EN61591
780 m³/hr	Speed 3 Pressured air movement EN61591

Installation	
Air outlet	150

Ducted	Top extraction
Internal Blower Included	•

Recirculation	Optional - top extraction

Two-Piece Height Adjustable Flue



Parts & Accessories	
Chimney extension	792492
Eave ducting kit	PD-RHK150E
Light bulb	792556
Recirculation carbon filter(s)	792481
Recirculation diverter	792560
Roof ducting kit	PD-RHK150T
Side wall ducting kit	PD-RHK150W
Performance	
Airflow balancing plate	•
Extraction type	Surface
Filter type	Mesh
Number of filters	2
Speeds	3 Plus Boost
Power requirement	
Supply voltage	220-240V
Total Power	248 W
Warranty	
Warranty	Two year manufacturer's
	warranty
sku	50120

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com

fisherpaykel.com