

## Safety Data Sheet

### PRIMER MF comp. A

Safety Data Sheet dated 8/8/2016, version 2

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: PRIMER MF comp. A

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Epoxy resins.

Uses advised against:

==

1.3. Details of the supplier of the safety data sheet

Supplier:

Mapei New Zealand Ltd  
30 Fisher Crescent  
Mt Wellington  
Auckland  
New Zealand

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

New Zealand

Ph: +64 9 921 1994 (Mon-Fri 9am-5pm)

Fax: +64 9 921 1993

www.mapei.co.nz

enquiries@mapei.co.nz

New Zealand Poisons Centre:

Ph: 0800 764 766

---

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
- ⚠ Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

## Safety Data Sheet PRIMER MF comp. A



### Warning

#### Hazard Statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

#### Precautionary Statements:

- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P391 Collect spillage.
- P501 Dispose of contents/container in accordance with applicable regulations.

#### Special Provisions:

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### Contents:

- oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
- reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700): May produce an allergic reaction.
- bisphenol F - epoxy resin: May produce an allergic reaction.

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

#### Other Hazards:

No other hazards

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:  
 >= 50% - < 75% reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

REACH No.: 01-2119456619-26-xxxx, Index number: 603-074-00-8, CAS: 25068-38-6, EC: 500-033-5

- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
- ⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 20% - < 25% oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

REACH No.: 01-2119485289-22-XXXX, Index number: 603-103-00-4, CAS: 68609-97-2, EC: 271-846-8

- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.2/1 Skin Sens. 1 H317

>= 10% - < 20% bisphenol F - epoxy resin

## Safety Data Sheet

### PRIMER MF comp. A

REACH No.: 01-2119454392-40-0006, CAS: 9003-36-5, EC: 500-006-8

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 10% - < 20% bis(isopropyl)naphthalene

REACH No.: 01-2119565150-48-xxxx, CAS: 38640-62-9, EC: 254-052-6

⚠ 3.10/1 Asp. Tox. 1 H304

4.1/C4 Aquatic Chronic 4 H413

---

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

###### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

Wash immediately with water for at least 10 minutes.

###### In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

A suspension of activated charcoal in water, or petroleum jelly may be administered.

###### In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the eyes, the product causes irritation that may last for over 24 hours, and if brought into contact with the skin it causes significant inflammation with erythema, scabs, and oedema.

If brought into contact with the skin, the product may cause sensitisation of the skin.

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

None in particular.

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

##### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the

## Safety Data Sheet

### PRIMER MF comp. A

combustion fumes.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Limit leakages with earth or sand.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

After the product has been recovered, rinse the area and materials involved with water.

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

#### 7.3. Specific end use(s)

None in particular

---

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No occupational exposure limit available

#### DNEL Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

Worker Industry: 8.3 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

## Safety Data Sheet

### PRIMER MF comp. A

Worker Industry: 12.25 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 8.3 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 12.25 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.571 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 3.571 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

bisphenol F - epoxy resin - CAS: 9003-36-5

Worker Professional: 0.0083 mg/cm<sup>2</sup> - Exposure: Human Dermal - Frequency: Short Term, local effects

Worker Professional: 104.15 mg/kg - Consumer: 62.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 29.39 mg/m<sup>3</sup> - Consumer: 8.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 6.25 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

bis(isopropyl)naphthalene - CAS: 38640-62-9

Consumer: 2.1 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated)

Consumer: 2.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Worker Industry: 4.3 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Consumer: 7.4 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

Worker Industry: 30 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

#### PNEC Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

Target: Fresh Water - Value: 0.006 mg/l

Target: Marine water - Value: 0.0006 mg/l

Target: Freshwater sediments - Value: 0.0627 mg/kg

Target: Marine water sediments - Value: 0.00627 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. - CAS: 68609-97-2

Target: Marine water - Value: 0.00072 mg/l

Target: Fresh Water - Value: 0.0072 mg/l

Target: Freshwater sediments - Value: 66.77 mg/kg

Target: Marine water sediments - Value: 6.677 mg/kg

Target: Soil (agricultural) - Value: 80.12 mg/kg

Target: Microorganisms in sewage treatments - Value: 10 mg/l

bisphenol F - epoxy resin - CAS: 9003-36-5

Target: Fresh Water - Value: 0.003 mg/l

Target: Marine water - Value: 0.0003 mg/l

Target: MAP2 - Value: 0.0254 mg/l

Target: Freshwater sediments - Value: 0.294 mg/kg

Target: Marine water sediments - Value: 0.0294 mg/kg

Target: Soil (agricultural) - Value: 0.237 mg/kg

bis(isopropyl)naphthalene - CAS: 38640-62-9

Target: MAP1 - Value: 15 mg/kg

Target: Freshwater sediments - Value: 0.94 mg/kg

Target: Marine water sediments - Value: 0.094 mg/kg

Target: Soil (agricultural) - Value: 0.19 mg/kg

#### 8.2. Exposure controls

## Safety Data Sheet

### PRIMER MF comp. A

#### Eye protection:

Safety goggles.  
Use close fitting safety goggles, don't use eye lens.

#### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.  
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

#### Respiratory protection:

Not needed for normal use.  
In case of insufficient ventilation use mask with A filters (EN 14387).).

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

#### Thermal Hazards:

None

#### Environmental exposure controls:

None

#### Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	transparent
Odour:	typical
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.17 g/cm <sup>3</sup> (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	insoluble
Solubility in oil:	soluble
Viscosity:	350 mPa.s (23°C)
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

### 9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

## Safety Data Sheet

### PRIMER MF comp. A

#### SECTION 10: Stability and reactivity

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
It may catch fire on contact with powerful oxidising agents.
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

---

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

Route(s) of entry:

Ingestion:	Yes
Inhalation:	Yes
Contact:	Yes

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ) - CAS: 25068-38-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 15000 mg/kg - Notes: riferito a prodotto di reazione:bisfenolo-A-epicloridrina;resine epossidiche

Test: LD50 - Route: Skin - Species: Rabbit > 23000 mg/kg - Notes: riferito a prodotto di reazione:bisfenolo-A-epicloridrina;resine epossidiche

i) STOT-repeated exposure:

Test: map1 - Route: Oral - Species: Rat = 50 mg/kg

Test: map1 - Route: Skin - Species: Rat = 100 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. - CAS: 68609-97-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 4500 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 17100 mg/kg

bisphenol F - epoxy resin - CAS: 9003-36-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

bis(isopropyl)naphthalene - CAS: 38640-62-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 4000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5.6 mg/l

c) serious eye damage/irritation:

Test: Eye Irritant - Species: Rabbit : Negative - Source: OECD 405

j) aspiration hazard:

Test: Respiratory Tract Irritant - Species: Rabbit : Negative - Source: OECD 404

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.



## Safety Data Sheet

### PRIMER MF comp. A

Eye:

The product can cause irritation by contact

Sensitizing Properties:

Frequent contact may cause sensitization.

Carcinogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) - CAS: 25068-38-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 1.8 mg/l - Duration h: 48

Endpoint: LC50 - Species: Algae > 11 mg/l - Duration h: 72

Endpoint: LC50 - Species: Daphnia = 1.3 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.3 mg/l

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. - CAS: 68609-97-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 5000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 7.2 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 844 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish > 1800 mg/l - Duration h: 96

bis(isopropyl)naphthalene - CAS: 38640-62-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.15 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 0.5 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 2.3 mg/l - Duration h: 24

### 12.2. Persistence and degradability

N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil



## Safety Data Sheet

### PRIMER MF comp. A

- N.A.
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None  
Not available data on the mixture

---

#### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover if possible. In so doing, comply with the local and national regulations currently in force.  
Dispose of this material and its container to hazardous or special waste collection point.  
Avoid release to the environment. Refer to special instructions/Safety data sheets.  
91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.  
Disposal of hardened product (EC waste code) : 08 04 10  
Disposal of not hardened product (EC waste code) : 08 04 09  
The suggested European waste code is just based on the composition of the product.  
According to the specific process or application field a different waste code may be necessary.

---

#### SECTION 14: Transport information

- 14.1. UN number  
UN Number: 3082
- 14.2. UN proper shipping name  
ADR-Shipping Name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID N.O.S
- 14.3. Transport hazard class(es)  
Rail/Road(RID/ADR): 9, III  
ADR-Upper number: NA  
Air (ICAO/IATA): 9, III  
Sea (IMO/IMDG): 9, III
- 14.4. Packing group
- 14.5. Environmental hazards  
Marine pollutant: No
- 14.6. Special precautions for user
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
No

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
Restrictions related to the product:  
Restriction 3  
Restrictions related to the substances contained:  
No restriction.  
Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I -

## Safety Data Sheet

### PRIMER MF comp. A

Protection against chemical agents"

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions.  
(Environmental regulations)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement – IMDG Code – IATA Regulation

VOC (2004/42/EC) : 45 (A+B) g/l

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

15.2. Chemical safety assessment

No

---

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 14: Transport information

SECTION 15: Regulatory information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

## Safety Data Sheet

### PRIMER MF comp. A

GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	Substance with a Union workplace exposure limit.
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List