

Safety Data Sheet

SILWOOD

Safety Data Sheet dated 16/5/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SILWOOD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Acrylic sealant in water dispersion.

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI S.p.A. -Via Cafiero 22 - Milan -ITALY

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:

None

Hazard Statements:

None

Precautionary Statements:

None

Special Provisions:

EUH210 Safety data sheet available on request.

Contents:

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1): May produce an allergic reaction.

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

Safety Data Sheet

SILWOOD

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:
>= 5% - < 10% oxydipropyl-dibenzoate

REACH No.: 01-2119529241-49-0000, CAS: 27138-31-4, EC: 248-258-5

4.1/C3 Aquatic Chronic 3 H412

2 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Index number: 613-167-00-5, CAS: 55965-84-9

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C1 Aquatic Chronic 1 H410

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wash immediately with water for at least 10 minutes.

In case of Ingestion:

A suspension of activated charcoal in water, or petroleum jelly may be administered.

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

No specific hazards are encountered under normal product use.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

None in particular.

Extinguishing media which must not be used for safety reasons:

None in particular.

Safety Data Sheet

SILWOOD

- 5.2. Special hazards arising from the substance or mixture
The product does not present a fire hazard
Do not inhale explosion and combustion gases.
The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Limit leakages with earth or sand.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.
Retain contaminated washing water and dispose it.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.
Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
Store above 5°C.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
No occupational exposure limit available
DNEL Exposure Limit Values
oxydipropyl-dibenzoate
- CAS: 27138-31-4
Worker Industry: 170 mg/kg - Worker Professional: 170 mg/kg - Consumer: 8.7 mg/m³ -

Safety Data Sheet

SILWOOD

Exposure: Human Dermal - Frequency: Short Term, systemic effects
 Worker Industry: 35.08 mg/m³ - Worker Professional: 35.08 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 8.8 mg/m³ - Worker Professional: 8.8 mg/m³ - Consumer: 8.69 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 0.22 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 80 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Consumer: 0.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1.4 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 0.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

oxydipropyl-dibenzoate

- CAS: 27138-31-4

Target: Fresh Water - Value: 0.0037 mg/l

Target: Marine water - Value: 0.00037 mg/l

Target: Freshwater sediments - Value: 1.49 mg/kg

Target: Marine water sediments - Value: 0.149 mg/kg

Target: MAP2 - Value: 0.037 mg/l

Target: Soil (agricultural) - Value: 1 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

In case of insufficient ventilation use mask with B type filters (EN 14387).

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	paste
Colour:	various
Odour:	typical
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	== °C
Initial boiling point and boiling range:	100 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.

Safety Data Sheet

SILWOOD

Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1,7-1,8 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	dispersible
Solubility in oil:	insoluble
Viscosity:	600000 mPa.s (23°C)
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion:	Yes
Inhalation:	No
Contact:	No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

oxydipropyl-dibenzoate

- CAS: 27138-31-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3914 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 200 mg/l - Duration: 4h

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

Safety Data Sheet

SILWOOD

-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 53 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat 330 mg/m³ - Duration: 4h

Test: LC50 - Route: Inhalation - Species: Rat 2.36 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 660 mg/kg

Corrosive/Irritating Properties:

Eye:

The product can cause a temporary irritation by contact.

Sensitizing Properties:

No effects are known.

Carcerogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

a) acute toxicity

b) skin corrosion/irritation

c) serious eye damage/irritation

d) respiratory or skin sensitisation

e) germ cell mutagenicity

f) carcinogenicity

g) reproductive toxicity

h) STOT-single exposure

i) STOT-repeated exposure

j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Aquatic toxicity: the preparation is not to be considered toxic to the aquatic environment based on components.

LC50>100mg/l - aquatic species (calculated data following 1999/45/EC Directive).

Biodegradability: not readily biodegradable

Biodegradability: no data available on the preparation.

oxydipropyl-dibenzoate

- CAS: 27138-31-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 3 mg/l - Duration h: 96

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 0.16 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.19 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

Safety Data Sheet

SILWOOD

12.5. Results of PBT and vPvB assessment

List of substances dangerous for the environment and corresponding classification:

>= 5% - < 10% oxydipropyl-dibenzoate

CAS: 27138-31-4

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

48 ppm 1,2-benzisothiazol-3(2H)-one

CAS: 2634-33-5

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 3.7 mg/l (48 hr)

EC50 (Algae): 0.37 mg/l (72 hr)

24 ppm 2-metil-2H-isotiazol-3-one (MIT)

CAS: 2682-20-4

R50 Very toxic to aquatic organisms.

6 ppm bronopol (INN); 2-bromo-2-nitropropane-1,3-diol

CAS: 52-51-7

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 1.1 mg/l (48 hr)

LC50 (Fish): 8.6 mg/l (96 hr)

EC50 (Daphnia) 48h - 1,4 mg/l

EC50 (Algae) 72h - 0,4 mg/l

LC50 (Fish) 96h - 41,2 mg/l

6 ppm octhilonone (ISO); 2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.32 mg/l (48 hr)

EC50 (Algae): 0.031 mg/l (72 hr)

LC50 (Fish): 0.047 mg/l (96 hr)

5 ppm 2-methyl-2H-isothiazol-3-one (MIT)

CAS: 2682-20-4

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 1.6 mg/l (48 hr)

EC50 (Algae): 0.157 mg/l (72 hr)

LC50 (Fish): 6 mg/l (96 hr)

2 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

CAS: 55965-84-9

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.16 mg/l (48 hr)

LC50 (Fish): 0.19 mg/l (96 hr)

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 08 04 10

Disposal of not hardened product (EC waste code) : 08 04 14

Safety Data Sheet

SILWOOD

The suggested European waste code is just based on the composition of the product.
According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

- 14.1. UN number
UN Number: ==
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
Rail/Road(RID/ADR): no dangerous good
ADR-Upper number: NA
Air (ICAO/IATA): no dangerous good
Sea (IMO/IMDG): no dangerous good
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
Marine pollutant: No
N.A.
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
N.A.
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Dir. 2006/8/EC
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 453/2010 (Annex I)
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product:
No restriction.
Restrictions related to the substances contained:
Restriction 46
- Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"
Directive 2000/39/CE and s.m.i. (Professional threshold limit)
Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)
Directive 105/2003/CE (Seveso III): N.A.
ADR Agreement – IMDG Code – IATA Regulation
VOC (2004/42/EC) : N.A. g/l

Safety Data Sheet

SILWOOD

15.2. Chemical safety assessment
No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H412 Harmful to aquatic life with long lasting effects.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

Safety Data Sheet

SILWOOD

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List