



V1.0 January 2022

## 1. GENERAL

- |  |  |
|--|--|
| <b>1.1 GENERAL</b>                       | This specification relates to the installation of Masons UNI® PRO Flexible Air Barrier.  |
| <b>1.2 RELATED WORK</b>                  | The installation of UNI® PRO relies on the installation of a timber or steel primary structure that: <ul style="list-style-type: none"><li>› complies with the NZ Building Code and is designed in accordance with NZS 3604:2011 or NASH Standard Parts 1 and 2: 2019, or</li><li>› is specifically designed to NZS 3603:1993 or AS/NZS 1170:2002, or</li><li>› where existing is suitable for the intended building work.</li></ul> |
| <b>1.3 DOCUMENTS</b>                     | Refer to the following manufacturer's documents: <ul style="list-style-type: none"><li>› Masons UNI® PRO Design and Installation guide</li><li>› Masons UNI® PRO warranty.</li></ul> Refer to the following related documents: <ul style="list-style-type: none"><li>› NZS 3604:2011 Timber-framed buildings</li><li>› NASH Standard Parts 1 and 2: 2019</li><li>› NZS 3603:1993</li><li>› NZS 1170:2002 (set).</li></ul>            |
| <b>1.4 GENERAL DESIGN CONSIDERATIONS</b> | The system must be specified in accordance with the Mason's UNI® PRO Design and Installation guide.  |

## 2. PRODUCTS

- |                                |  |
|--------------------------------|--|
| <b>2.1 PRODUCT DESCRIPTION</b> | UNI® PRO is a nonwoven, absorbent, water-resistant 180 GSM, synthetic wall underlay. It comprises three polypropylene layers: two outer layers of nonwoven polypropylene with a middle layer of a functional-technical film. It is manufactured to meet the European standard EN 13859-2:2014 as well as the absorbency performance requirement as per NZS 2295:2006. It is supplied coloured blue with a black underside unless an alternative colour is requested. |
|--------------------------------|--|



## 2.2 ASSEMBLY COMPONENTS

The following assembly components are supplied by Masons:

UNI® PRO

- Masons UNI® PRO 2.74 x 50 m

Fixings

- Masons UNI® Fasteners 32 mm
- Masons UNI® Cap Nails

Ancillary components

- Masons 40 Below™ (Platinum or Flex) flashing tape 150 mm x 20 mm
- Masons 40 Below™ (Platinum or Flex) flashing tape 75 mm x 20 mm
- Masons Penetration Seal 1-75 mm
- Masons Penetration Seal 80-170 mm
- Masons UNI® FAB Seam and Repair Tape
- Masons Corner Guards
- Masons PEF Backing Rod
- Masons Brick Ties.

## 2.3 SUBSTITUTIONS

Substitutions are not permitted to any of the specified components listed in this section.

# 3. EXECUTION

## 3.1 QUALIFICATIONS

The installation of the UNI® PRO must be carried out by a competent and experienced builder.

## 3.2 RESTRICTED BUILDING WORK

Where Restricted Building Work applies, the installer shall be a Licensed Building Practitioner (LBP) or be supervised by an LBP with the relevant license class.

## 3.3 CHECK RELATED WORK

Confirm the primary structure:

- complies with the NZ Building Code and is designed in accordance with NZS 3604:2011 or NASH Standard Parts 1 and 2: 2019, or
- is specifically designed to NZS 3603:1993 or AS/NZS 1170:2002, or
- where existing is suitable for the intended building work, and
- meets the fixing requirements as per Table 1 in the UNI® PRO Design and Installation Guide.



## 4. APPLICATION

---

### 4.1 GENERAL

The installation of the UNI® PRO must be completed in accordance with the instructions in the Masons UNI® PRO Design and Installation guide and the building consent documentation. All conditions contained in the building consent documentation must be met.

### 4.2 RECEIPT OF PRODUCT

Ensure that all product supplied by Masons is:

- free of defects at the time of delivery and
- handled and stored in accordance with all Masons' requirements.

## 5. COMPLETION

---

### 5.1 QUALITY CHECK

Check the installation to ensure all components have been installed in accordance with all Masons' requirements.

### 5.2 WARRANTIES

A manufacturer's warranty is available for the UNI® PRO. Refer to [www.mpb.co.nz](http://www.mpb.co.nz).

### 5.3 INFORMATION FOR CARE AND MAINTENANCE

The UNI® PRO requires minimal care and maintenance to maintain the performance of the underlay. Refer to [www.mpb.co.nz](http://www.mpb.co.nz).

---



## 6. PROJECT-SPECIFIC SELECTIONS

### PROJECT DETAILS

Project address

Lot/DP number

Date of plans

Purpose of plans

Description of building work and reference to drawing numbers

### DOCUMENTS SUPPLIED (CHECK WHICH APPLIES)

Masons UNI® PRO Codemark

Masons UNI® PRO Design and Installation Guide

Masons UNI® PRO Warranty

### DESIGNER CONFIRMATION (CHECK WHICH APPLIES)

#### Location

##### Wind zone or design pressure (ULS)

Low

Medium

High

Very high

Extra high

Design pressure (ULS) up to 4.6 kPa

##### Exposure zone as per NZS 3604:2011

A

B

C

D

##### Distance to boundary

Less than 1 m

Greater than 1 m

#### Building

##### Framing

Timber

Lightweight steel

Existing building assessed at equivalent stiffness to NZS 3604:2011



## ASSEMBLY COMPONENT SELECTIONS

### UNI® PRO

- Masons UNI® PRO 2.74 x 50 m

### Fixings

- Masons UNI® Cap Nails for use with timber framing
- Masons UNI® Self Drilling Screws with washers for use with lightweight steel frames

### Ancillary components

- Masons 40 Below™ flashing tape (Flex) 150 mm x 20 mm
- Masons 40 Below™ flashing tape (Flex) 75 mm x 20 mm
- Masons 40 Below™ flashing tape (Platinum) 150 mm x 20 mm
- Masons 40 Below™ flashing tape (Platinum) 75 mm x 20 mm
- Masons Penetration Seal 1-75 mm
- Masons Penetration Seal 80-170 mm
- Masons UNI® FAB Seam and Repair Tape
- Masons Corner Guards
- Masons PEF Backing Rod
- Masons Brick Ties
- Masons Wrap Strap.