## MASONS FLOOR GUARD/FOAM GUARD/EASY-FORM

# **MATERIAL SAFETY DATA SHEET**



V1.0 October 2022

Company	Masons Plastabrick Ltd
Contact Details	0800 522 533   info@mpb.co.nz   www.mpb.co.nz
Emergency	National Poison Centre 03 474 7000
Name	Softlon® product from Sekisui Australia
Description	Softlon® is based on physically crosslinked polyolefin foam produced in a continuous web process. Softlon® is based on PE homo and copolymers and foamed with an organic foaming agent by chemical decomposition. The two following gases are
	mainly produced: - Nitrogen (N²)
	- Carbon dioxide (CO²)
	Both are known as non-depleting substances to the ozone layer

## **SECTION 2: HAZARDS IDENTIFICATION**

Polyolefin foam will burn when provided with an adequate amount of heat and oxygen, therefore do not expose the material to any flame or other source of ignition or heat. Subject to reasonable care and cleanliness there are no obvious problems associated with the handling of polyolefin foams.

SECTION 3: FIRST AID MEASURES		
After contact with skin	No special measures with usage at normal temperatures.	
After contact with eyes	Flush thoroughly with flowing water.	
After inhalation	No special measures with usage at normal temperatures.	
After swallowing	If ingested, induce vomiting by drinking a large volume of water or salt water. Seek medical attention.	
In case of fire	If smoke gases are inhaled, which contain mainly carbon dioxide (CO <sup>2</sup> ) and carbon monoxide (CO), fresh air and possible artificial respiration (seek medical attention immediately) are the recommended measures. If body skin is burned through contact with molten material, cool burned parts with water but do not remove from the skin. If skin burn degree 2 or 3 is reached, seek medical attention immediately.	

V1.0 October 2022



#### **SECTION 4: FIRE FIGHTING MEASURES**

Fire extinguishing mediums are • Dry chemical

- Water spray
- Extinguishing foam
- CO<sup>2</sup> extinguisher

Use respirator/oxygen masks in enclosed areas. Avoid dense smoke and do not inhale the smoke gases from combustion. Use safety glasses and protect skin/body with protective clothing.

## **SECTION 5: ACCIDENTAL RELEASE MEASURES** Not applicable.

## **SECTION 6: HANDLING AND STORAGE**

Handling Procedures	Practice reasonable care as a normal safety precaution. The working environment should be kept clean and free of
	dust. Fabrication areas should be well ventilated to carry away fumes, vapours and dust, especially in processes, e.g. lamination (heat and coating), welding, vacuum forming, hot press moulding; operators should be assured of a supply of fresh air.
Storage Procedures	Practice reasonable care and cleanliness; provide adequate distance between stacks as a safety precaution. Store inside with adequate ventilation and keep dry, away from direct sunlight. Keep in original packing until required. Do not expose to any source of flame, ignition or heat.

#### SECTION 7: EXPOSURE CONTROLS/PERSONAL PROTECTION

7.1 NON-FABRICATION	
APPLICATIONS	

APPLICATIONS	
Breathing protection	No special requirements.
Hand protection	Use safety gloves when cutting product with a knife.
Eye protection	No special requirements.
Body protection	No special requirements.
7.2 FABRICATION APPLICATION	S
Breathing protection	In special fabrication areas that are not well ventilated, use special personal breathing respirator/mask or filter in order to protect from fumes, vapours and dust.
Hand protection	When working in fabrication areas utilising heat processes,

thermal injury from molten foam.

wear gloves (cotton wool or leather) to prevent possible

When working in fabrication areas utilising heat processes,

wear safety glasses or goggles to prevent possible thermal



Eye protection



injury from molten foam.





Body protection	When working in fabrication areas utilising heat processes, minimise skin exposure by wearing long sleeved clothing, long leggings and shoes to prevent possible thermal injury from molten foam.
SECTION 8: PHYSICAL AND CH	IEMICAL PROPERTIES
Appearance	Semi rigid closed cell, physically crosslinked polyolefin foam.
Odour	Odourless
Softening range	≥100 - 130°C
Autoflammability	≥300°C
Thermal decomposition	≥160-180°C
Explosive properties	None
Solubility in water	Insoluble
Solubility in organic solvents	Insoluble, partly soluble, swelling; depending on solvent type
Electrical surface resistance	≥1018 <b>Ω</b> cm
SECTION 9: STABILITY AND RE	EACTIVITY
Avoid	Any temperature (over period >10 minutes). >160 - 180°C
Aviod	Any contact with strong oxidising chemicals
SECTION 10: TOXICOLOGICAL I	NFORMATION
Toxicologically harmless	Physically crosslinked polyolefin foams are among the most inert polymer foams and constitute no hazard in terms of normal handling and skin contact.
SECTION 11: ECOLOGICAL INFO	DRMATION
Environmentally harmless	<ul> <li>Insoluble in water.</li> <li>Insoluble in most solvents.</li> <li>Free of heavy metals and plasticisers.</li> <li>Degradable only by prolonged UV exposure.</li> </ul>
Ozone layer depleting substances	Softlon® does not contain and is not produced with any of the substances mentioned in the "Montreal Protocol" of ozone depleting substances and in the corresponding EC Regulation 2009/1005:  • Chlorofluorocarbons (CFCs)  • Hydrochlorofluorocarbons (HCFCs)  • Carbon Tetrachloride  • 1,1,1-Trichloroethane  • Methyl Bromide



SECTION 12: RECYCLING & DISPOSAL CONSIDERATIONS	
Re-use	Remnant material may be reused directly, e.g: Cushion packaging material
Recycling	Ask our Sales Engineers about product specific recycling possibilities.
Disposal	When disposing of any waste, observe all applicable national and local regulations. Softlon® may be disposed of by:  Landfill  Physically crosslinked polyolefin foam is inert and does not degrade, it forms a permanent soil base and releases no gases or chemicals known to pollute water resources.
	Incineration Incinerate using properly controlled municipal or industrial incineration systems. Plastic materials, such as physically crosslinked polyolefin foam, have high heat values and should only be incinerated in units designed to handle high combustion heat.

### SECTION 13: TRANSPORT INFORMATION

No restrictions and non-hazardous material in relation to transportation regulations.

#### **SECTION 14: REGULATORY INFORMATION**

No regulations apply in relation to classification, packaging and identification, also applicable to health and environmental care.

#### **SECTION 15: OTHER INFORMATION**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe the product from the point of view of safety requirements, and is not intended to guarantee any particular properties.

This information on Sekisui Foam International products is presented to the best of our knowledge. All product data is based on average values and is for guidance only. As these products are subject to constant research and development, we reserve the right to update the contents without notice.

Recommendations as to methods of post fabrication, application and use of Sekisui Foam International products are based on our experience and knowledge of the characteristics of our products and are given in good faith. As producer of the material we have no control over the application of Sekisui Foam International products and no legal responsibility is accepted for such recommendations. In particular, no responsibility is accepted by us for any system in which Sekisui Foam International products are utilised or for any application.

Softlon and Thermobreak - Registered trademarks of Sekisui Chemical Co. Ltd or its subsidiaries. © Sekisui Pilon Pty Ltd. Date of Publication: 4 January 2016



This document is uncontrolled in printed form. See www.mpb.co.nz for current version. Copyright © 2021 Masons.