### **Safety Data Sheet**

### **ULTRALITE S1 FLEX (N) GREY**

Safety Data Sheet dated: 14/12/2021 - version 1



### Section 1. Identification of the substance and supplier

#### **Product identifier**

Mixture identification:

Trade name: ULTRALITE S1 FLEX (N) GREY

Trade code: 9024299

Recommended use of the chemical and restrictions on use

Recommended use: N.A. Uses advised against: N.A.

Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road - Mount Wellington - 1060 - Auckland - New Zealand

Phone: +64 9 921 1994 (Mon-Fri 9am-5pm) - Fax: +64 9 921 1993

enquiries@MBPLtd.co.nz - www.MBPLtd.co.nz

**Emergency phone number** 

New Zealand Poisons Centre: Ph: 0800 764 766

#### Section 2. Hazards identification

#### **HSNO** hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

### **HSNO** classification:

6.3A H315 - Causes skin irritation.

8.3A H318 - Causes serious eye damage.

6.5B H317 - May cause an allergic skin reaction.

6.1E (respiratory tract

irritant)

H335 - May cause respiratory irritation.

#### **Hazard information**

# **Pictograms and Signal Words**



#### **Hazard statements:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

## **Precautionary statements:**

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with applicable regulations.

#### Other hazards which do not result in a classification

No other hazards

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 1 of 6

## Section 3. Composition/information on ingredients

#### **Substances**

N.A.

#### **Mixtures**

Mixture identification: ULTRALITE S1 FLEX (N) GREY

#### Hazardous components within the meaning of HSNO Act and related classification

Concentration (% w/w)	Name	Ident. Numb.	Classification
≥50 - <75 %	Portland cement, Cr(VI) < 2 ppm	CAS:65997-15-1 EC:266-043-4	6.3A, H315; 6.5B, H317; 8.3A, H318; 6.1E (respiratory tract irritant), H335
≥1 - <2.5 %	Calcium diformate	CAS:544-17-2 EC:208-863-7	8.3A, H318

#### Section 4. First aid measures

### Description of necessary first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

### Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

### Section 5. Fire-fighting measures

# Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

# Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 2 of 6

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

#### **Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

### Methods and materials for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

#### Section 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

# Section 8. Exposure controls/personal protection

## **Workplace Exposure Standards**

## List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour Note
Portland cement, Cr(VI) < 2 ppm	< NZL	NEW ZEALAND		10.000				
	NZL	NEW ZEALAND		3				
	NZL	NEW ZEALAND		1				

#### **Engineering Controls**

N.A.

### Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

# Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

A dust mask (P2) should be worn if above exposure limits (EN 149)

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

N.A.

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 3 of 6

#### Section 9. Physical and chemical properties

Physical state: Solid

Appearance and colour: powder Grey

Odour: cement like Odour threshold: N.A.

pH: N.A.

pH (water dispersion, 10%): 12.00 Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: N.A.

Flammability (Solid, Gas): N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: N.A. Vapour density: N.A. Relative density: N.A. Solubility in water: N.A. Solubility in oil: insoluble

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Kinematic viscosity: N.A.

Particle characteristics: No data available

## Section 10. Stability and reactivity

### Reactivity

Stable under normal conditions

#### **Chemical stability**

Data not available.

### Possibility of hazardous reactions

None.

### **Conditions to avoid**

Stable under normal conditions.

# **Incompatible materials**

None in particular.

#### **Hazardous decomposition products**

None.

#### Section 11. Toxicological information

## Information on toxicological effects

# Toxicological information on main components of the mixture:

Calcium diformate a) acute toxicity LD50 Oral Rat = 2650 mg/kg

# Section 12. Ecological information

### **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

# List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

Calcium diformate CAS: 544-17-2 - a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio >= 1000 mg/L 96h

EINECS: 208-863-7 IUCLID

#### Persistence and degradability

N.A.

# **Bioaccumulative potential**

N.A.

### Mobility in soil

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 4 of 6

#### Other adverse effects

NΔ

### Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

## Special precautions to be taken during disposal

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

# **Section 14. Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### **UN** number

N.A.

#### **UN proper shipping name**

N.A

### Transport hazard class(es)

N.A.

### Packing group, if applicable

N.A.

### **Environmental hazards**

N.A.

No

### Special precautions for user

NZS-Subsidiary risks: N.A.

NZS-Special Dispositions: N.A.

Road and Rail ( ADR-RID ):

N.A.

Air ( IATA ):

N.A.

Sea ( IMDG ):

N.A.

### Section 15. Regulatory information

#### **HSNO Approval**

HSNO approval number and group standard title:

HSR002544 - Construction Products (Subsidiary Hazard) Group Standard 2006

### **HSNO** Controls

#### **Approved Handler**

No data available

#### New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

#### Regulatory references

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Hazardous Substances (Classification) Regulations 2001.

Labelling of Hazardous Substances: Hazard and Precautionary Information (January 2012 EPA0094).

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 5 of 6

#### Section 16. Other information

Safety Data Sheet dated: 14/12/2021 - version 1

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

#### Description of the HSNO Classification codes used in section 2 or 3:

### Code Description

6.1E (respiratory Respiratory tract irritant.

tract irritant)

6.3A Substances that are irritating to the skin.
6.5B Substances that are contact sensitisers.
8.3A Substances that are corrosive to ocular tissue.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

 $\hbox{\tt EINECS: European Inventory of Existing Commercial Chemical Substances}.$ 

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

HSNO: Hazardous Substances and New Organisms Act 1996.

Date 14/12/2021 Production Name ULTRALITE S1 FLEX (N) GREY Page n. 6 of 6