SUPERGRASSE.

ProBounce PE

www.aptasiapacific.com.au 1800 652 548

Finished Product Details

Product Code Application Pile Height (mm) Colours Available Total Product Weight g/m²

Supply

Available Width Standard Roll Length Approx. Shipping Weight Line Systems

Infill Materials

Stabilising Infill Performance Infill

Product Warranty

Warranty

5008 Tennis 16 mm Green/ Blue/ Rust 2,040 g/m²

3.71m As required for kit courts 7.6 kg/lm As requested

N/A Washed and dried fine silica sand (19 kg/m2)

Seven (7) year limited warranty as per manufacturer's standard warranty terms

Configuration

Machine Gauge Stitch Rate Yarn Weight No. of Tufts (m²) Perforated

4.76mm 20 per 100 mm 1,100 g/m² 42,016 On request

Twisted PE Tape

Yarn Properties

Yarn Construction Linear Density Environment

UV Stability

740 Tex APTA manufactures with heavy metal free yarns which may be used anywhere without restriction APTA yarns are protected against UV degradation and light fastness meets the highest standards

Primary Backing

Construction Primary Layers

Woven PP Single

Secondary Coating

Compound Base Tuft Anchorage Antioxidising Agent Hybrid Emulsion 40 Newtons (minimum) Present

APT



