Saniflo **©SFA**

Sanimulti®

Sanimulti[®] is a versatile macerator with two different pan connection options making it ideal for all types of applications. The Sanimulti can be used in domestic or commercial projects.



WHY CHOOSE THIS PRODUCT?

Ideal for commercial applications with optional "plug & play" alarm interlock connectivity for water and power isolation

Robust stainless steel macerator blade for intensive use


Factory pre-mounted non return valve (supplied)

Macerator needs minimum 4.5 L of unrestricted flush for optimal function

Can be equipped with Sanialarm Interlock (sold separately)


VERTICAL/HORIZONTAL PERFORMANCE


Increase size of horizontal run by one pipe size after 5m. All horizontal pipework requires a minimum of 1:100 fall.




TECHNICAL CHARACTERISTICS

Discharge Pipework	25 mm
Motor Power	560 Watts
Voltages	220-240 V/50 Hz
Working Waste Water Temp	40°C
Product Weight	9.5 kg
Overall Measurements	505 x 361 x 205 mm
Inlet Pipework	100-40 mm
IP Rating	IP44





FLOW RATE PERFORMANCE CHART



OUTPUT (litres/min)

APPLICATIONS






WALL HUNG SHOWER TOILET

WMTS 106:2019 Certificate No. 23048 Manufacturer: SFA Brand: Saniflo

PRODUCT REFERENCE: SA222



Removable motor cassette for ease of service



Robust blade suitable for heavy usage



Shaking up water

Made in Germany to the highest standards, needs to be installed by a licensed plumber