

PRODUCT OVERVIEW

Classique Ply is a high-grade interior ply with excellent edge detail, with a Euro Poplar *Populus spp.* core and the option of American White Oak *Quercus alba*, Canadian Oak *Quercus spp.* or Euro Birch *Betula pendula* external veneer.

Beautiful, and light-weight, it is a popular choice for wall linings and joinery. (The option of using with HPL laminates is available.)

USES

- ♦ Ceiling Linings
- ♦ Tiny-house Interiors and Horse Float Interior
- ♦ Lightweight Cabinetry
- ♦ Feature Joinery



Left and above: Classique Ply (Canadian Oak) provides a warm look for this Christchurch vet clinic ceiling by Simplicity Construction.

SPECIFICATIONS

Sheet Size	Sheet Thickness	Weight	Grading
2440x1220 Canadian	12mm	16kg	AB Interior
2440x1220 Canadian	18mm	22kg	AB Interior
2440x1220 Birch	12mm	16kg	AB Interior

Colour	Natural timber colourings – (European Poplar Core)
Durability	Good durability/Interior
Origin	Southern Europe
Environment	Sustainable/Plantation Grown
Glue	EI - Class 3. Density – 440 – 490Kg/m ³

SPECIFICATIONS

	Code	Size	Thickness	Info	Grade
Birch	V2112-B	2440 x 1220	12mm	Euro Poplar Core	AB Interior
Canadian Oak	V2112-C	2441 x 1220	12mm	Euro Poplar Core	AB Interior
Canadian Oak	V2118-C	2442 x 1220	18mm	Poplar Multiply Core	AB Interior
White Oak	V2118-W	2443 x 1220	18mm	Poplar Multiply Core	AB Interior

HANDLING & APPLICATION INFORMATION

Classique ply is a lighter weight timber than other plywoods, the highly visual surface will harden once a good quality lacquer is applied. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.