

Sanicom®2

Sanicom® 2 is a high performance commercial grey water lifting station featuring 2 powerfull motors, ensuring continuity of service for your business. The easy access service design makes it ideal for busy commercial kitchens & cafe's.

WHY CHOOSE THIS PRODUCT?

Ideal for heavy commercial applications

Safe, reliable twin motor pump for continuity of service

Unit operates automatically

1/65 mm rear and two 80 mm side entries and air vent connection for external venting

Working temperature of 35°C

Will handle up to 90°C for short periods (5 minutes)

External hard-wired alarm


Alternates duty cycle

2 x pre mounted non return valves (supplied)

2 m pre wired cable

VERTICAL/HORIZONTAL PERFORMANCE


Increase size of horizontal run by one pipe size after 5m. All horizontal pipework requires a minimum of 1:100 fall.



20 30 40 50 60 70 80 90 100 110 metres

TECHNICAL CHARACTERISTICS


|) | | | |
|---|-------------------------|----|---------------------------------|
| | Discharge Pipework | | 40/50 mm |
| | Motor Power | | 1500 Watts x 2 |
| | Voltages | | 220-240 V/50 Hz |
| | Tank Volume | | 34.5 L |
| | Working Waste Water Tem | пр | 35°C/Max 90°C (intermittent) |
| | Product Weight | | 26 kg |
| | Overall Measurements | | 582 x 486 x 529 mm |
| | Inlet Pipework | | 50/65/80 mm |
| | IP Rating | | IP44 |
| | | 8 | 80 |





FLOW RATE PERFORMANCE CHART

Discharge height (m)



P1 - Output flow rate with one motor engaged P1 + P2 - Output flow rate with two motors engaged (litres/min) **APPLICATIONS**





HAND **BATH BASIN**





SHOWER WASHING **MACHINE**





WASHER



Brand: Saniflo

PRODUCT REFERENCE: SA108



Wired alarm panel (optional)



External mounted control box



Shaking up water

Made in France to the highest standards, needs to be installed by a licensed plumber