



Standard Fastening MS w/ Lining

Application

Soundproof Standard Fastening in combination with Sikla channels, also satisfying soundproof demands according to DIN 4109.

Scope of delivery

Pipe clamp Ratio S 2000 with pre-assembled clamp adaption M10, suitable for sizes 40 up to 160.

Pipe clamp Stabil D-3G with lining with pre-assembled clamp adaption M16, suitable for sizes 200 up to 315.

Installation

The entire module is pushed into the channel opening and locks automatically. While positioning the distances, the module is securely guided in the channel opening. Then hexagon bolt is tightened.

Type	W [kg]	Quantity [pack]	Part number
SB 40 MS m.E.	0.19	1	602205
SB 50 MS m.E.	0.20	1	602215
SB 56 MS m.E.	0.20	1	602225
SB 63 MS m.E.	0.22	1	602235
SB 75 MS m.E.	0.24	1	602245
SB 90 MS m.E.	0.33	1	602255
SB 110 MS m.E.	0.44	1	602265
SB 125 MS m.E.	0.46	1	602275
SB 160 MS m.E.	0.56	1	602285
SB 200 MS m.E.	1.49	1	602295
SB 250 MS m.E.	1.72	1	602305
SB 315 MS m.E.	2.03	1	602315