



POWERED BY GREEN

Futura HPL – Matt is manufactured using electricity produced from 100% renewable energy sources with official guarantees of origin.

Treun Project Management

Futura HPL – Matt

European Birch plywood finished on both faces with a smooth matt anti-fingerprint laminate produced by Egger in Germany. Available in six colours. Recommended for vertical surfaces only.

KEY FEATURES

- Anti-fingerprint
- Smooth and velvety to the touch
- European Birch
- Attractive edge detail

DIMENSIONS

2440 x 1220mm, 18mm/13ply – White, Graphite

2440 x 1220mm, 24mm/17ply – White

OPTIONS

Available uncoated or pre-finished with a uv-cured polyurethane lacquer in a low sheen (5% gloss) matt finish.

SCOPE OF USE

High-end joinery and furniture. Office and shop fittings.

PERFORMANCE

Environment Protection Standard:
ISO 14001:2005

Quality Management Standard:
ISO 9001:2009

ULEF: No harmful emissions

FSC Certified

PEFC Certified.

TECHNICAL SPECIFICATIONS

Standard – EN 636-2

Finish – High Pressure Laminate 0.6mm

Wood Raw Material – European Birch

Density – average 700kg/m³

Class – Hardwood, non-durable

Glue Bond – EN 314-3: Class 2 Exterior

Glue Formaldehyde Emissions – ULEF:

Ultra-Low Emitting Formaldehyde.

LIMITATIONS ON USE

For interior use only. Vertical surfaces only.

EDGING

Because the core is free of voids and is birch throughout, the exposed edges give a unique edge detail. No need to spend time and effort on applying edge tape or solid edge banding unless you want to. Simply sand and finish the edges.

FINISHING

We recommend that both faces and all edges of the uncoated plywood are coated. For pre-finished plywood we advise to sand and aris all end grain (edges) before coating to help prevent moisture ingress and increase longevity.

HANDLING AND STORAGE

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat.

Avoid leaning sheets against walls. Store sheets where construction activity will not damage sheets. Keep the surface free of contaminants such as dust, oil and adhesives that will affect the surface finishes.

Storage areas should be protected from sun, rain and wind to minimise changes in humidity. Treat sheets as a finished product and avoid dragging sheets across other surfaces.



White



Graphite



PLYTECH SHOWROOM

26 Business Parade North, PO Box 204-070, Highbrook, Auckland 2161, New Zealand. Phone: 09 573 5016, Fax: 09 573 5035

sales@plytech.co.nz

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade.

The 'plytech' logo in a bold, orange, lowercase sans-serif font.