



ULTRABRIGHT SOLAR SENSOR LIGHT

LHT1184

- Solar Powered Outstanding Light Output
 Just bright as 230V powered options
- Backup Power for Guaranteed Performance
 Two rechargeable 18650 Li-ion batteries are included,
 with optional battery backup of 4x 'D' cell Alkaline batteries
- No Wiring Required
 Cost effective and can be installed in just a few minutes
- Ceiling or Wall Mountable
 Perfect for exterior use where safety/security lighting is needed

1250 m NEUTRAL WHITE



















Visit our website for more information

ULTRABRIGHT SENSOR LIGHT RANGE





General Technical Data

Detection	Range	LED Colour	Luminous Flux	PIR Aiming Adjustment	Dusk Control	Colour	Product Code
180°	up to 10m	5000K	1250 lm	Left or right 90°	0~20 lux (Default)	Black	LHT1184

Dimensions	ons Hausing Color Bonel Mounting Pan/ Cofety IP	IP	IP Battery		Warranty				
H x W x D (mm)	Housing	Solar Panel	Mounting	Tilt	Safety	Rating	Included	Required	- Warranty
210 x 125 x 80	UV-stabilised polycarbonate	9V 2W with 5 metre cable	Ceiling / Wall	Yes	Class III	IP44	2 x Li-ion 18650 Rechargeable 3.7V 2200mAh	4 x 'D' Cell Alkaline	3 years

Operating Modes

Mode	Normal power supply Light on time (Li-ion battery)	Back up power supply Light on time (Alkaline battery)			
0	Off and charging only	Off			
1M	100% Brightness for 1 minute	50% Brightness for 30 seconds			
5M	100% Brightness for 5 minutes	50% Brightness for 3 minutes			
XTEN	100% Brightness for 1 minute & 20% brightness for 4 minutes	50% Brightness for 30 seconds & 10% brightness for 2 minutes			
EC0	70% Brightness for 1 minute	35% Brightness for 15 seconds			

