

Safety Data Sheet MAPEPRIM SP comp.A

Safety Data Sheet dated 16/5/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: MAPEPRIM SP comp.A

1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended use:

Water-borne synthetic resin based primer.

1.3. Details of the supplier of the safety data sheet

Supplier:

Mapei New Zealand Ltd
30 Fisher Crescent
Mt Wellington
Auckland
New Zealand

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

New Zealand
Ph: +64 9 921 1994
Fax: +64 9 921 1993
New Zealand Poisons Centre:
Ph: 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Safety Data Sheet

MAPEPRIM SP comp.A

Warning

Hazard Statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contents:

- reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\hat{a}\%_{\text{m}} 700$)
- bisphenol F - epoxy resin: May produce an allergic reaction.
- 2-ethylhexylglycidylether: May produce an allergic reaction.
- reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1): May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:
>= 5% - < 10% reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\hat{a}\%_{\text{m}} 700$)

REACH No.: 01-2119456619-26-XXXX, Index number: 603-074-00-8, CAS: 25068-38-6, EC: 500-033-5

- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
- ⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 2.5% - < 4.99% bisphenol F - epoxy resin

CAS: 28064-14-4

- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
- ⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 1% - < 2.5% 2-ethylhexylglycidylether

CAS: 2461-15-6, EC: 219-553-6

- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

Safety Data Sheet

MAPEPRIM SP comp.A

>= 0.25% - < 0.49% alkylphenol polyethyleneglycolether

CAS: 9016-45-9

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.25% - < 0.49% dodecan-1-ol

REACH No.: 01-2119485976-15-xxxx, CAS: 112-53-8, EC: 203-982-0

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 4.1/C2 Aquatic Chronic 2 H411 M=1.

⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.

225 ppm 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

3 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Index number: 613-167-00-5, CAS: 55965-84-9

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C1 Aquatic Chronic 1 H410

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

A suspension of activated charcoal in water, or petroleum jelly may be administered.

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the eyes, the product causes irritation that may last for over 24 hours, and if brought into contact with the skin it causes significant inflammation with erythema, scabs,

Safety Data Sheet

MAPEPRIM SP comp.A

and oedema.

If brought into contact with the skin, the product may cause sensitisation of the skin.

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

None in particular.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

Do not inhale explosion and combustion gases.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Limit leakages with earth or sand.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Safety Data Sheet

MAPEPRIM SP comp.A

- Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.
Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
Store above 5°C.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

SUVA - LTE mg/m³: 49 mg/m³, 10 ppm - STE mg/m³: 98 mg/m³, 20 ppm

NDS - LTE mg/m³: 98 mg/m³

NDSch - LTE mg/m³: 200 mg/m³

EU - LTE mg/m³(8h): 98 mg/m³, 20 ppm - STE mg/m³: 246 mg/m³, 50 ppm - Notes:

Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - LTE mg/m³(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700) - CAS: 25068-38-6

Worker Industry: 8.3 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 12.3 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 8.3 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 12.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 0.75 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 3.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-ethylhexylglycidylether - CAS: 2461-15-6

Worker Industry: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 220 mg/m³ - Consumer: 65 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 125 mg/kg - Consumer: 75 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 220 mg/m³ - Consumer: 65 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 75 - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 75 - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Safety Data Sheet MAPEPRIM SP comp.A

Worker Industry: 135 ppm - Consumer: 426 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 89 mg/kg - Consumer: 44.5 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 13.4 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Worker Industry: 50 ppm - Consumer: 123 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 75 mg/kg - Consumer: 38 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 20 ppm - Consumer: 49 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \bar{M}_n 700) - CAS: 25068-38-6

Target: Fresh Water - Value: 0.003 mg/l

Target: Marine water - Value: 0.0003 mg/l

Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Freshwater sediments - Value: 0.5 mg/kg

Target: Marine water sediments - Value: 0.5 mg/kg

Target: MAP2 - Value: 0.013 mg/l

bisphenol F - epoxy resin - CAS: 28064-14-4

Target: Fresh Water - Value: 0.003 mg/l

Target: Marine water - Value: 0.0003 mg/l

Target: Marine water sediments - Value: 0.0294 mg/kg

Target: Freshwater sediments - Value: 0.294 mg/kg

Target: Soil (agricultural) - Value: 0.237 mg/kg

2-ethylhexylglycidylether - CAS: 2461-15-6

Target: Fresh Water - Value: 0.002 mg/l

Target: Marine water - Value: 0.000166 mg/l

Target: Freshwater sediments - Value: 0.177 mg/kg

Target: Marine water sediments - Value: 0.018 mg/kg

Target: Soil (agricultural) - Value: 0.084 mg/kg

dodecan-1-ol - CAS: 112-53-8

Target: Fresh Water - Value: 0.0028 mg/l

Target: Marine water - Value: 0.00028 mg/l

Target: Freshwater sediments - Value: 1.1 mg/kg

Target: Marine water sediments - Value: 0.11 mg/kg

Target: Soil (agricultural) - Value: 0.888 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

In case of insufficient ventilation use mask with B type filters (EN 14387).

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Safety Data Sheet

MAPEPRIM SP comp.A

Environmental exposure controls:
None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	paste
Colour:	blue
Odour:	typical
Odour threshold:	N.A.
pH:	6-7
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	100 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.20 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	dispersible
Solubility in oil:	insoluble
Viscosity:	20000 mPa.s (23°C)
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

It may catch fire on contact with powerful oxidising agents.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion:	Yes
Inhalation:	Yes
Contact:	Yes

Safety Data Sheet

MAPEPRIM SP comp.A

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≈ 700) - CAS: 25068-38-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 11.400 mg/kg

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 2.2 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 615 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 405 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 53 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat 330 mg/m³ - Duration: 4h

Test: LC50 - Route: Inhalation - Species: Rat 2.36 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 660 mg/kg

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause irritation by contact

Sensitizing Properties:

Frequent contact may cause sensitization.

Cancerogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Liquid epoxy resin contained in this material causes only minor skin irritation. However, all epoxy resins are capable of causing sensitizing of the skin.

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

a) acute toxicity

b) skin corrosion/irritation

c) serious eye damage/irritation

d) respiratory or skin sensitisation

e) germ cell mutagenicity

f) carcinogenicity

g) reproductive toxicity

h) STOT-single exposure

Safety Data Sheet

MAPEPRIM SP comp.A

- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Biodegradability: not readily biodegradable

Biodegradability: no data available on the preparation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \bar{M}_n 700) - CAS: 25068-38-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 1.3 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 2.1 mg/l - Duration h: 48

Endpoint: NOEC - Species: Daphnia 0.3 mg/l

Endpoint: LC50 - Species: Algae 11 mg/l - Duration h: 72

dodecan-1-ol - CAS: 112-53-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.62 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 0.1855 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 320 mg/l - Duration h: 48

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 0.16 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.19 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

List of substances dangerous for the environment and corresponding classification:

$\geq 5\%$ - $< 10\%$ reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \bar{M}_n 700)

CAS: 25068-38-6

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

$\geq 2.5\%$ - $< 4.99\%$ bisphenol F - epoxy resin

CAS: 28064-14-4

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

$\geq 0.25\%$ - $< 0.49\%$ alkylphenol polyethyleneglycolether

CAS: 9016-45-9

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

$\geq 0.25\%$ - $< 0.49\%$ dodecan-1-ol

CAS: 112-53-8

R50 Very toxic to aquatic organisms.

16 ppm 1,2-benzisothiazol-3(2H)-one

CAS: 2634-33-5

Safety Data Sheet

MAPEPRIM SP comp.A

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 3.7 mg/l (48 hr)

EC50 (Algae): 0.37 mg/l (72 hr)

3 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

CAS: 55965-84-9

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.16 mg/l (48 hr)

LC50 (Fish): 0.19 mg/l (96 hr)

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Dispose of this material and its container to hazardous or special waste collection point.

Avoid release to the environment. Refer to special instructions/Safety data sheets.

91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 08 04 10

Disposal of not hardened product (EC waste code) : 08 04 09

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

14.1. UN number

UN Number: ==

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

ADR-Upper number: NA

Air (ICAO/IATA): no dangerous good

Sea (IMO/IMDG): no dangerous good

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

Marine pollutant: No

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Safety Data Sheet

MAPEPRIM SP comp.A

Regulation (EU) n. 453/2010 (Annex I)
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

No restriction.

REACH Regulation (1907/2006) – All. XVII: N.A.

Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement – IMDG Code – IATA Regulation

VOC (2004/42/EC) : 5,6 (A+B) g/l

SVHC Substances:

Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):

alkylphenol polyethyleneglycolether

SVHC

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H410 Very toxic to aquatic life with long lasting effects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

Safety Data Sheet

MAPEPRIM SP comp.A

NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List