



**Juralco Aluminium Building Products Ltd designs and distributes specialist aluminium joinery systems through a national network of franchised fabricators and agents. For more than 25 years we have been at the forefront of specialist aluminium door and window products suitable for New Zealand joinery and building methods. Our comprehensive product range includes security and insect screens, balustrades and gates, shutters and awnings, shower screens, wardrobe doors and organisers and internal doors. The Juralco EDGE® Balustrading Systems is an architectural balustrade system designed to provide a wide range of design options in both contemporary glass and in more conventional aluminium metal balusters.**

The Juralco EDGE® Balustrade system is an architectural balustrade system designed to provide a range of modern design options in both glass and aluminium. Mounting to a deck can be done a variety of ways to timber, concrete, steel, and to waterproof membranes. Toughened Glass infills can be 6mm or 10mm, either fully framed (6mm) or semi frameless (10mm) with handrails either top or side mounted. Toughened 13.2mm Laminated glass can be used for semi frameless applications. For a more traditional look Vertical metal infills are available in 17mm sq and 49mm, 60mm and 123mm slats, all in powder coated colour of your choice. All designs are available with a variety of handrails. Tables are shown for various baluster spacings, heights and wind zones. All mountings and installation recommendations conform to the latest AS/NZS1170 and NZS 4223.3.2016 regulations. Our installers are all very experienced and can recommend a balustrading system to fit your design requirements and budget.



Top left illustration - Top Mount EDGE® Balustrade with Metal Balusters  
 Bottom left illustration - Top Mount EDGE® Balustrade with Metal Balusters  
 Illustration above - Face Fixed EDGE Balustrade with Laminated glass,  
 to Concrete  
 Cover illustration - Face Fixed EDGE® Semi Frameless Balustrades



**Complies With AS/NZS 1170:2002, NZS 4223.3.2016, NZ Building Code B1, B2, F2, F4 and F9  
Complies with French Standard NF P01-013 (1988-08)**

**EDGE® Balustrade is for Domestic and Residential Occupancy types A, A Other and C3 only  
Occupancy Types as per AS/NZ 1170.1.2002. Not suitable for Commercial C3 applications**

Code	Type of Occupancy for part of the building or structure	Specific Uses	Glass
A	Domestic and Residential activities	All areas within or serving exclusively one dwelling including stairs, landings etc, but excluding external balconies and edges of roofs.	6mm, 10mm Toughened Glass and 13.2mm Toughened Laminated Glass
A Other, C3	Areas without obstacles for moving people and not susceptible to over crowding	Stairs, landings, external balconies, edges of roofs etc.	


**Note 1 Glass 6mm, 10mm Toughened Safety Glass and 13.2mm Toughened Laminated Glass must have a minimum strength of 100MPa. All edges polished.**

**Note 2 Juralco Balustrade Systems building code compliance documentation requires all balustrade installations are to be completed in accordance with the requirements of our authorised installer certification.**

**Note 3 All Semi Frameless glass Balustrades must have an Top or Side mounted Handrail to conform to NZS 4223.3.2016, except for 13.2mm Toughened Laminated Glass applications as per this manual. Handrails not necessary for Swimming Pools.**

**masterspec partner**  
Section 4852JB

## Index

Heading	Pages	Description <a href="#">Use the Bookmarks</a>  <a href="#">List to jump to selected pages</a>
Specifications	4	Juralco standard Specification sheet and Powder coating recommendations
Layouts incl Stair	5 - 9	Shows Glass and Metal Baluster style Balustrade layouts. Top Fix, Face fix and Gutterbracket Face Fix
Materials	10 - 16	All Extrusions and Components
Interlinking and Handrails	17 - 19	Shows various Interlinking and Handrails attached to Posts, Glass Panels and Walls
Post Mount Types	20	Shows the Four Post mount types
Mountings	21 - 38	Shows Mounting details - For Timber (p21-25), Steel (p26-31) and Concrete (p32-38)
	39 - 44	Shows Mounting details. Older Timber structures pre NZS3604:2011
Connection Details	45 - 49	Shows General Connection details. Handrails, Bottom Rail and Base Plates
Details, Set outs for all Glass and Metal Baluster Designs	50 - 58	All 6mm Toughened Glass. Fully Framed and Full height. All with Handrails
	59 - 67	All 10mm Toughened Glass. Semi Frameless with Handrails + Pool Fencing
	68 - 70	All 13.2 Toughened Laminated Glass. Semi Frameless
	71 - 76	All 17mm Baluster. Full Height and Split Rail. All with Handrails
	77 - 82	All 60mm Slat Baluster. Full Height and Split Rail. All with Handrails
	83 - 88	All 60mm (p83-85) and 123mm (p86-88) Horizontal Slats. All with Handrails
Design Details, Corners	89 - 90	Shows recommended Corner layouts for Solid balusters and Glass
<b>Special Section Starts after this. Special applications of the EDGE Balustrading System</b>		
LED Lighting	91	Shows LED strip light for various Handrails
Floating Deck - Edge	92	Shows details of Floating Deck edge treatment to hide edge of deck
STECCA System	93 - 95	Shows the STECCA Balustrade System
Apartment Deck Dividers	96 - 97	Shows Slat and Glass Dividers
LAMERRA System	98 - 103	Shows LAMERRA Balustrade System
X Balustrade	104	Shows Special X Balustrade
Surface Care	105 - 106	Instructions for the care of Powder coated and Glass surfaces

**1.Scope-** This specification details the documents the Juralco EDGE® Balustrade System refers to in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System, requirements in relation to fixing and surface finishings.

### 2. NZBC Compliance

- The Juralco EDGE® Balustrade System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and AS/NZS 1170 : 2002 occupancy A, A Other and C3, NZS 3604 Low, Medium, High, Very High and Extra High Wind Zones.
- The Structural Engineering design includes the requirements of B1 Structure, B2 Durability, F2 Hazardous material and F4 Safety from falling, all from the Building Code.
- Verification Method B1 / VM1, B2/AS1, F4 / AS1.
- All glass used in the Juralco EDGE® Balustrade System must conform to AS/NZS 2208.
- Complies with NZS 4223.3.2016

### 3. Manufacturer's Documents

- The Juralco EDGE® Balustrade System manual details all extrusions and components used for the fabrication and installation/fixing of the system.
- A Producer Statement 1(Design) is available.  
Copies of the above documents are available from:  
Juralco Aluminium Building Products Ltd  
48 Bruce McLaren Rd, Henderson, Auckland  
Phone 09 478 8018 Fax 09 478 7883 Email [specify@juralco.co.nz](mailto:specify@juralco.co.nz)
- Any deviation from the standard fabrication or installation/fixing must be accompanied by a site specific PS1 with site specific calculations and drawings

### 4. Products

- Only extrusions, components and hardware supplied by or specified by JABP may be used in the Juralco EDGE® System
- Aluminium extrusions, components and hardware – unless specified are manufactured to 6060 T5 specifications
- Stainless Steel components, hardware, fixings – all components to 316 grade
- Glass - all glass used in the Juralco EDGE® Balustrade System must conform to the specifications as listed in the Juralco EDGE® manual with each panel conforming to AS/NZS 2208 as confirmed by the Safety Stamp detailing the manufacturer's description and licence number.

### 5.Surface Finishing

- Juralco Aluminium Building Products Ltd is a Dulux Registered Applicator site, registration number 2101.  
JABP uses only Dulux branded powder coating materials
- Unless specified otherwise, Dulux Duralloy® powder coating systems are used for properties greater than 100 metres from high tide level where AAMA 2603 performance is required
- Dulux Duratec® powder coating systems must be used for all properties greater than 10 metres and up to 100 metres from high tide level where AAMA 2604 performance is required
- Dulux Duralloy® has a 10 year film and colour integrity warranty, Dulux Duratec® has a 20 year film and colour integrity warranty

### 6. Installation and Fixing

- The Juralco EDGE® Balustrade System must only be installed in accordance with the Juralco EDGE® Balustrade System manual
- Any deviation from that specified in the Juralco EDGE® manual must only be in accordance with the site specific PS1 with site specific calculations and drawings listing the non standard details
- The Juralco EDGE® Balustrade System must only be fabricated/installed by a Juralco approved fabricator
- Upon completion of the installation the fabricator must supply the owner with a PS3 (Construction)

#### Important information - Powder Coating systems.

**Powdercoat Systems** The new standard Dulux powder coating system used by Juralco is Duralloy Plus®. Also Duralloy® and Duratec®. All as per specs above. Juralco Powder coated prices are for Duralloy Plus® and Duralloy® (same pricing). Duratec® prices on application.

**Attachment to structures** A PVC Tape or similar material spacer must be used to separate powder coated aluminium items from all concrete and steel structures. Failure to do so can lead to the chemicals in the structure affecting the powder coating, leading to corrosion.

**Swimming Pools** The chlorinated water in swimming pools can cause the deterioration of powder coated surfaces, leading to corrosion of the underlying surface. It is recommended that Powder coated surfaces be 1200mm min from a pool.

**Care** The Dulux powder coating warranty period is conditional upon the surface being maintained in accordance with the Dulux 'Care and Maintenance Instructions'. Download from Dulux or refer to the back page of this manual.

#### Important information - Anodised Coatings.

**Anodised Systems.** The standard Anodised thickness used by Juralco is 12 micron and is suitable for single story sites greater than 100 metres from high tide.. For any multi storey buildings use 20 micron coatings. Use 25 micron for installations less than 100 metres from high tide level and for prestigious residential and commercial developments. Standard Juralco colours are Natural and Bronze. Note - Anodising prices listed in Juralco price books are for the standard 12 micron systems. For thicker coatings, and other colours prices on application. Also, for coloured coatings there will be colour variations from batch to batch.


**Attachment to structures** An PVC layer or similar material spacer must be used to separate Anodised aluminium items from all concrete and steel structures. Failure to do so may lead to the chemicals in the structure affecting the aluminium base

**Care** Aluminium oxide is amphoteric in nature. Therefore, any cleaning products used on anodised surfaces must be ph neutral so that they do not react chemically with the coating. Cleaning products should be thoroughly rinsed from surfaces as soon as possible. Stubborn contamination can usually be removed using a non-scratch cleaning pad and water or a gentle solvent.

**For 6mm Toughened Glass**


**6mm Glass - Fully Framed. Handrail + Bottom Rail.**

Balustrade Height, 1000mm min, above FFL




**6mm Glass - Full Height. Handrail + Bottom Rail.**

Balustrade Height, 1000mm min, above FFL



**6mm Glass - Full Height. Handrail + Split Rails.**


Balustrade Height, 1000mm min, above FFL



**For 10mm Toughened Glass**

**10mm Toughened Glass - Semi Frameless - Handrail**

Balustrade Height, 1000mm min, above FFL



**Top Mount**


A Corner Post is available for Top Mount only

**Gutter Brkt Face Fix**

**Face Fix**

**10mm Toughened Glass - Semi Frameless - JEB 222 Interlinking Rail + JEC 29 Brackets, Deck side. Glass 110mm Above Posts.**

Balustrade Height, 1000mm min, above FFL




**Top Mount**

**Gutter Brkt Face Fix**

**Face Fix**

**10mm Toughened Glass - Semi Frameless - No Handrail. SWIMMING POOLS ONLY. 1200mm Min Height**

Pool Fence Height. Not for use where protecting a fall of 1m or more



**Top Mount**

**Gutter Brkt Face Fix**

**Face Fix**


**Note: A Building Consent is required when installing or replacing a Swimming Pool Fence. Refer to NZBC Clause F9**

**For 13.2mm Toughened Laminated Glass**

**13.2mm Toughened Laminated Glass - Semi Frameless**

Top Protection cap JET 212 recommended

Balustrade Height, 1000mm min, above FFL



**Top Mount**

**Gutter Brkt Face Fix**

**Face Fix**




**JURALCO**

www.juralco.co.nz ph (09) 478 8018

## For 17mm Baluster

### 17mm Baluster - Full Height. Handrail + Bottom Rail.


Balustrade Height, 1000mm min, 1275mm max above FFL.



**All 17mm Baluster - suitable for Extra High Wind Zones**

### 17mm Baluster - Split Rail. Handrail + Top and Bottom Rail.

Balustrade Height, 1000mm min, 1275mm max above FFL.




**All 17mm Baluster - suitable for Extra High Wind Zones**

## For 49mm Slat - Vertical. Stecca System


### 49mm Slat - Full Height. Top + Bottom Rails (Front mounted).

Balustrade Height, 1000mm min, above FFL



### 49mm Slat - Full Height. Top + Bottom Rails (Between Posts mounted).




Balustrade Height, 1000mm min, above FFL



### For 60mm Slat - Vertical




**60mm Slat - Full Height. Handrail + Bottom Rail.**

Balustrade Height, 1000mm min, above FFL



**60mm Slat - Split Rail. Handrail + Top and Bottom Rail.**




Balustrade Height, 1000mm min, above FFL



### For 60mm Slat - Horizontal

**60mm Slat - Horizontal + Handrail. 15mm Gaps max between Slats.**




Balustrade Height. 1000mm min height above FFL



### For 123mm Slat - Horizontal

**123mm Slat - Horizontal + Handrail. 15mm Gaps max between Slats.**

Balustrade Height. 1000mm min height above FFL






**Juralco EDGE® Balustrade System Stair Setouts, Construction**


**EDGE Balustrade  
Face Fix shown**


Typical Stair installation  
Screw fixings into Single or Double Joists/Stiffeners, Concrete or Steel




**EDGE Balustrade  
Stair Stringer Detail**

Stair structure to be designed by others to resist Balustrade actions as per NZS1170.1 Table 3.3  
Applicable to Internal Residential applications only







TOP FIX EDGE POST  
JEB/207/5




TOP FIX EDGE POST  
SEMIFRAMELESS  
JEB/212/5




FACE FIX EDGE POST  
JEB/208/5





FACE FIX EDGE POST  
SEMIFRAMELESS  
JEB/214/5










TOP FIX EDGE  
CORNER POST  
SEMIFRAMELESS  
JEB/213/5



FACE FIX EDGE POST  
STIFFENER  
JEB/205/5



**Note - Infill clips are not used with the JEB 222**



**For Posts and Handrails**

**For Posts only**




**JURALCO**

www.juralco.co.nz ph (09) 478 8018


**Juralco EDGE® Balustrade Systems**

Issue 10-24 v1  
Page 11


## Juralco EDGE® Balustrade System - Extrusions



INFILL  
17mm BALUSTER  
JVB/005/5.35




WATER DEFLECTION ANGLE  
JA118/5




INFILL  
49mm SLAT  
(Single Screw)  
JVB/030/5.35


INFILL  
49mm SLAT  
(Double Screw)  
JVB/018/5.35




INFILL  
60mm SLAT  
JVB/019/5.35




INFILL  
123mm SLAT  
JGF/222/5.8




TOP PROTECTION CAP  
for 13.2mm Laminated Glass  
JET212  
(attach with JET 330  
DS Tape)



CAP  
JVB/006/5.8




BOTTOM RAIL  
JVB/022/5.8




BOTTOM RAIL SPIGOT  
JVB/017/5

These ex  
Viking Balustrade  
System




BOTTOM RAIL  
Part No JEB/202/5.8




HEAVY DUTY BOTTOM RAIL  
SPIGOT  
JET/917/5  
(NOT Suitable Semi  
Frameless Posts)


BOTTOM RAIL  
SPIGOT  
JEB/210/5  
(Suitable all Posts)



25x3 FLAT BAR  
HANDRAIL JOINTER  
Part No JA174/5




34x3 FLAT BAR  
HANDRAIL JOINTER  
Part No JA188/5



56.5x3 FLAT BAR  
HANDRAIL JOINTER  
Part No JA189/5




Base plate  
JEC200



110mm x 100mm x 12mm - 4 x holes


Base plate  
JEC201

For Concrete and Steel only



110mm x 90mm x 12mm - 2 x holes


Base plate  
JEC221



110mm x 90mm x 12mm - 4 x holes


Base plate  
JEC232

For Concrete and Steel only




128mm x 90mm x 12mm - 2 x Holes 14mm dia

Base plate - Corner Post  
JEC222



110mm x 110mm x 12mm - 4 x holes x 14mm dia


Base plate  
JEC137/65



120mm wide x 135mm high - 4 x holes


Base plate  
JEC206

These two Plates form a pair.  
For Floating decks only on a  
concrete base




120mm x 100mm x 15mm - M10 and M12 (all blind) threaded

Base plate  
Offset Corner Post  
JEC207



110mm x 100mm x 12mm - 13Ø holes


Gutter Bracket Spacer  
JEC139



135mm x 120mm x 5mm thick

Post Bottom Cap  
JEC10/HF

Hidden Fix



45mm x 65mm - Fits under face Fix Posts  
Attach with No 6 x 12 C/S SS PK screws

Handrail Clamp Screw  
JECscrew/M8x20


Handrail  
Clamp



M8 x 20 SS Grub screw


Post/Baseplate Screw  
JVBHTSCREW/50x10

This Screw **MUST** be used when attaching  
Posts to Baseplates or Gutter Brackets




50mm SS High Tensile PK C/S sq drive screw

Square Washer  
JVB SQWSH




40mm sqx 3mm SS

Face Fix Spacer  
JVB125/30mm



38mm dia x 30mm long.

Face Fix Spacer  
JVB125/15mm



38mm dia x 15mm long.

Face Fix Spacer  
JVB125/10mm




38mm dia x 10mm long.

EPDM Spacer Washer  
JVB126




38mm dia x 3mm

**Handrail Mount  
JEC23**




Angled Hand Rail Mount - Double Pocket  
Fits over Post. 66mm x 46mm

**Handrail Mount  
JEC24**




Angled Hand Rail Mount - No Pocket  
Fits over Post. 66mm x 46mm

**Handrail Mount  
JEC25RH or LH**




Angled Hand Rail Mount - Single Pocket, LH & RH  
Fits over Post. 66mm x 46mm

**Top Cap  
JEC20**




Fits over Post. 66mm x 46mm

**Top Cap  
JEC21**




Double Pocket  
Fits over Post. 66mm x 46mm

**Top Cap  
JEC22**




Single Pocket. RH/LH symmetrical  
Fits over Post. 66mm x 46mm

**Top Cap - Corner Post  
JEC27**



Fits over Post. 66mm x 66mm


**Top Cap Notched - Corner Post  
JEC28**



Double Pocket  
Fits over Post. 66mm x 66mm


**Handrail assembly  
JEC29/Kit**

For Wall or Post mounting




Includes 2 x grub screws

**Corner Post, Handrail Mount  
JEC30**



No Pockets - Fits over Post. 66mm x 66mm


**Corner Post, Handrail Mount  
JEC31**



Pockets - Fits over Post. 66mm x 66mm


**Handrail assembly  
JET48/Kit**

For Glass Panel mounting



Includes all components

**Circular Handrail Clip  
JEC38**




Attach.  
2 x No 8 x 12 C/S,  
SS PK Screws

For Circular Handrail JEB/223

**3mm Glazing Wedge**  
**JEC10/100**


For 10mm  
Glass



100mt Roll - PVC

**5mm Glazing Wedge**  
**JECW8/75**


For 8mm  
Glass and  
13.2mm  
Laminated  
Glass



75mt Roll - PVC


**7mm Glazing Wedge**  
**JECW6/75**

For 6mm  
Glass




75mt Roll - PVC

**Glazing D Seal**  
**JECDSL/100**




8mm deep x 9.5mm wide x 100mt Roll  
Semi Rigid PVC

**50mm Glazing Block**  
**JEC15**



**Back Seal**  
**JET/BSEAL/100**



For 13.2mm  
Laminated  
Glass

**Post Handrail Screw**  
**JECSCREW/14gx2**

Attach Post  
Cap  
to Post top

Use with JEC14GWASHER to attach  
Post cap to Post top



14g x 50mm SS PK Cap screw

**EPDM Washer**  
**JEC14GWASHER**


Use with JESCREW 14g to attach  
Post cap to Post top



11mm dia x 14g

**Glass Support Bracket**  
**JEC13**


Nylon



17mm x 13mm x 32mm long. Attaches to Post  
with 2 x No 8 x 16 SS PK Screws


**Glazing Wedge. Brown Tip**  
**JVBWedge/Brown/75**

For use with  
Viking Bottom  
Rail




**Backing Seal**  
**JVBBackWedge/500**

For use with  
Viking Bottom  
Rail



**Glazing Block**  
**JVB108**


For use with  
Viking Bottom  
Rail



17mm high x 9mm x 50mm long.

**Plastic Packer - Glass**


Part No	Thickness
H/PP1.5	1.5mm
H/PP2	2mm
H/PP3	3mm
H/PP4	4mm
H/PP5	5mm



Cut down to suit. 35x13.5, 52x13.5

**SIKA Supergrip**  
**Part No JECSUPERGRIP30**

For All Coach  
screws fixings




**Rhodorsil V60 Clear Silicone**  
**Part No H/RTV419098**

Construction  
Silicone

**Bottom Rail Bracket**  
**Part No JEC 14**


Attaches  
Bottom Rail  
to Timber



50mm x 38mm x 3mm thick.

**Bottom Rail 90 deg Spigot**  
**Part No JEC 12**


Joins Bottom  
Rail at  
90 deg



76mm x 76mm.

**DS Tape 12.7mm x 0.8mm**  
**Part No JET 330**

Attach Top  
Protection  
Cap



Double sided 12.7mm wide x 33mt Roll


**Rectangular and  
75mm Aerofoil Handrails  
End Cap, Straight and 90deg corners**

All ex 3mm Aluminium




Rectangular End Cap  
JEC03  
Can be used as RH or LH

(for Rectangular  
Handrail JEB/216)




75mm Aerofoil End Cap  
JEC11  
Available as RH or LH

(for 75mm Aerofoil  
Handrail JEB/217)



Rectangular and 75mm Aerofoil Inline Joiner  
Use 56.5 x 3 flat bar JA/189/5.0



Rectangular and 75mm Aerofoil  
90deg Corner Joiner JEC01


**Round and Circular  
Handrail, End Cap,  
Straight and 90deg corners**

All ex 3mm Aluminium




Round End Cap  
JEC06  
Can be used as RH or LH

(for Round  
Handrail JEB/209)




Circular End Cap  
JEC218  
Can be used as RH or LH

(for Circular  
Handrail JEB/221)



Round Inline Joiner  
Use 34.0 x 3 flat bar JA/188/5.0





Round 90deg Corner Joiner  
JEC04

**Interlinking Rail  
End Cap, Straight  
135 deg and 90deg corners**


All ex 3mm Aluminium




Interlinking Rail End Cap  
Can be used as RH or LH




14mm  
Straight Joiner  
JEC32




14mm, 135deg  
Corner Joiner  
JEC36




14mm, 90deg  
Corner Joiner  
JEC34



17.5mm  
Straight Joiner  
JEC33



17.5mm, 135deg  
Corner Joiner  
JEC37




17.5mm, 90deg  
Corner Joiner  
JEC35


**Joiners:**

- With Joiner in place, spot drill from below for position
- Drill out joiner to 3mm dia, extrusion to 4mm dia
- Use No 6 x 1/4in SS ST Pan sq drive screw
- Insert dabs of V60 Silicone inside cavities before inserting
- Both ends to be attached.
- Joins must be within 300mm of Post
- Minimum distance between screw and end of handrail is 10mm







**INTERLINKING RAIL**  
JEB/222/5.8




**AEROFOIL HANDRAIL**  
JEB/217/5.8



**ROUND HANDRAIL**  
JEB/209/5.8





**RECTANGULAR HANDRAIL**  
JEB/216/5.8



**CIRCULAR HANDRAIL**  
JEB/221/5.8

**Suitable Interlinking and Handrails**

**Semi Frameless and Frameless - Interlinking or Handrails on Deck side**  
**JEB/222 shown , but any Handrails from above suitable.**




**Important Note: Applies to JET48 Disc Mount Bracket to Glass only.**  
**All Interlinking rails, at their ends must be attached to a Building Structure using Rail End Plates or to an Edge Post attached to the Deck structure. Applies to Handrails used as Interlinking Rails.**


## Juralco EDGE® Balustrade System

### Interlinking and Handrails End Plates for attaching to a Wall


End Caps all ex 3mm Aluminium




HANDRAIL  
JEB/222/5.8




HANDRAIL  
WALL ATTACH END PLATE  
Part No JEC215/WC




For RH and LH




AEROFOIL HANDRAIL  
JEB/217/5.8




HANDRAIL  
WALL ATTACH END PLATE  
Part No JEC217/WC




For RH and LH




RECTANGULAR  
HANDRAIL  
JEB/216/5.8




HANDRAIL  
WALL ATTACH END PLATE  
Part No JEC216/WC




For RH and LH




HALF ROUND HANDRAIL  
JEB/209/5.8




HANDRAIL  
WALL ATTACH END PLATE  
Part No JEC209/WC




For RH and LH



CIRCULAR HANDRAIL  
JEB/221/5.8



HANDRAIL  
WALL ATTACH END PLATE  
Part No JEC221/WC



For RH and LH

**General Notes:** - All fixings to be Stainless Steel. - EPDM layer between Structure and End Cap  
- ULS Point load N\* = 0.9kN, inwards, outwards or down and in tension

**Note : Fixing to Steel**

- use 2 off 8g SS TEK Screws or M6 SS Bolts
- Steel 2mm min thickness
- Steel 300MPa minimum
- 15mm min distance to any Edges

**Note : Fixing to Timber Wall**

- use 2 off 8g SS Screws, 35mm min into studs.
- use Sika Supergrip 2hr
- 30mm min distance to Horizontal Edge
- If Weatherboard use suitable predrilled Wedge
- Timber stud wall to be designed and detailed in accordance with NZS 1720.1:2022 Timber Structures Part 1 - Design methods or NZ3604



**Note : Fixing to Juralco EDGE Post**

- use 2 off 8g x 25 SS PK Screws


**Note : Fixing to Concrete Wall**

- use 2 off M6 x70 SS Screw Anchors
- Solid Concrete min 20Mpa
- Block wall Concrete filled/Reinforced
- 140mm min Wall thickness
- 70mm min distance to Horizontal Edge
- 100mm min distance to Vertical Edge
- Blockwork wall must be corefilled /reinforced and is to be designed and detailed in accordance with NZ4230 or NZ4229







**Hand rail bracket and Hand rails**




Hand rail bracket and Hand rail.  
Angle attach up to 35deg



**CIRCULAR HANDRAIL**  
JEB/223/5.8  
+ Clip JEC38



**CIRCULAR HANDRAIL**  
JEB/221/5.8




**Gutter Bracket - Face Fixed**

Suitable for Waterproofed Decks and any overhanging decks.


Allows for Guttering to run under.

Different fasteners types depending on the Building substrate



**Face Fixed**


All hidden fasteners.  
Different fasteners types depending on the Building substrate



**Top Mount**

Base Plates in a variety of sizes. Different fasteners types depending on the Building substrate.

Includes a 90deg Semi Frameless Corner Post



**Base Fix - Concrete only.**

Post cemented permanently in place



**Typical TOP Fix to Timber - JEC 221, 110mm x 90mm, 4 hole Base Plate - M10 SS Coachscrews**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1400	1350	1300	1250	1200	1150	1100


Post Spacing max, mm

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrew engagement into joists 150mm. All coachscrews predrill 6mm holes
- 4 - Bond all coachscrews with SIKA Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical FACE Fix Post to Timber - M10 SS Coachscrews**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1400	1350	1300	1250	1200	1150	1100

Post Spacing max, mm



**Up to and including Extra High Wind Zone**

General Balustrades

Coachscrews as shown  
**NOT SUITABLE.**  
Must use Bolts


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 90mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKa Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical FACE Fix Post to Timber - M10 SS Bolts or Threaded Rod**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1400	1350	1300	1250	1200	1150	1100

Post Spacing max, mm



**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**


- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011

**Floating Decks**



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - All Fixings must be Stainless steel



**Typical FACE Fix to Timber - JEC 137/65, Gutter Bracket - M10 SS Coachscrews**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200

Post Spacing max, mm


**Up to and including Extra High Wind Zone**

General Balustrades


Coachscrews as shown  
**NOT SUITABLE.**  
Must use Bolts

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Floating Decks**



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 90mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKa Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical FACE Fix to Timber - JEC 137/65, Gutter Bracket - M10 SS Bolts or Threaded Rod**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200


Post Spacing max, mm

**Up to and including Extra High Wind Zone**


General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Floating Decks**



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - All Fixings must be Stainless steel



**Typical TOP Fix to Steel with Timber Deck - JEC 221, 110mm x 90mm, 4 hole Base Plate - M10 SS Bolts**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200


Post Spacing max, mm

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**


- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - All Fixings must be Stainless steel

4 x M10 SS Bolts  
+ 21dia x 2mm SS Washers





**Typical TOP Fix to Steel - JEC 201, 110mm x 90mm, 2 hole Base Plate - M12 SS Bolts**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200


Post Spacing max, mm

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - The Baseplate can be cut down to 75mm wide
- 4 - Both Base plate and PFC must be aligned, with Bolt at C/L
- 5 - A PVC tape layer must be placed between the Baseplate and Steel
- 6 - All fixings must be Stainless steel



### Typical FACE Fix Post to Steel - M10 SS Bolts

### Balustrade Dimensions by Wind Zone.

## Up to and including Very High Wind Zone


Balustrade Height above FFL, mm						
1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200
Post Spacing max, mm						

**Up to and including Extra High Wind Zone**


General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

General Notes:

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured  
above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




## Floating Decks



### Important Installation notes:

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - A PVC tape layer must be placed between the Post and Steel
- 4 - All fixings must be Stainless steel



**Typical FACE Fix Post to Steel + Wooden Packers - M10 SS Bolts**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200



Post Spacing max, mm

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - A PVC Tape layer must be installed between the Post and the Top Steel Flange
- 4 - All Fixings must be Stainless steel



**Typical FACE Fix Post to Steel + Wooden Packers - M10 SS Bolts**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200

Post Spacing max, mm



**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**


- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011

**Floating Decks**



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - A PVC Tape layer must be installed between the Post and Steel
- 4 - All Fixings must be Stainless steel



**Typical FACE Fix to Steel - JEC 137/65, Gutter Bracket - M10 SS Bolts**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above FFL, mm

1000	1050	1100	1150	1200	1250	1300 max
1500	1450	1400	1350	1300	1250	1200

Post Spacing max, mm



**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
<b>1200 max</b>	<b>1000 min - 1275 max</b>
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**


- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011

**Floating Decks**



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - A PVC Tape layer must be installed between the Gutter Bracket and Steel
- 4 - All Fixings must be Stainless steel



**Typical TOP Fix to Concrete - JEC 200, 110mm x 100mm, 4 hole Base Plate - M10 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1300	1250	1200	1150	1100
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M10
Drill hole diameter	= 12 mm
Drill hole depth	= 100 mm
Anchorage depth	= 90 mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation Notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - Fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Baseplate and Concrete
- 5 - Use Threadlok on Nuts
- 6 - All fixings must be Stainless Steel





**Typical TOP Fix to Concrete - JEC 201, 110mm x 90mm, 2 hole Base Plate - M12 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1070	1020	970	920	870
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
740	960
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M12
Drill hole diameter	= 14 mm
Drill hole depth	= 120mm
Anchorage depth	= 110mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation Notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - Fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Baseplate and Concrete
- 5 - Use Threadlok on Nuts
- 6 - All fixings must be Stainless Steel



**Typical TOP Fix to Concrete - JEC 232, 128mm x 90mm, 2 hole Base Plate - M12 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1300	1250	1200	1150	1100
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M12
Drill hole diameter	= 14 mm
Drill hole depth	= 100 mm
Anchorage depth	= 90 mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation Notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - Fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Baseplate and Concrete
- 5 - Use Threadlok on Nuts
- 6 - All fixings must be Stainless Steel



**Typical TOP Fix to Concrete - JEC 205 +207, 120mm x 100mm, 2 hole Base Plate - M12 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
970	920	870	820	770
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M12
Drill hole diameter	= 14 mm
Drill hole depth	= 90 mm
Anchorage depth	= 80 mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - All fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Base plate and Concrete
- 5 - Waterproofing membrane final details and certification by others
- 6 - All fixings must be Stainless steel



**Typical TOP Fix to Concrete - Embed Post in Concrete Slab**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1300	1250	1200	1150	1100
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
1000	1480
Post Spacing max, mm	Post Spacing max, mm


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011
- 5 - Only suitable for Ground Level sites.  
NOT elevated



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - A PVC Tape layer must completely surround the Post
- 4 - Mortar pocket 70mm sq or 85mm dia.  
Avoid mortar splashes on exposed aluminium. Wash off immediately.



**Typical FACE Fix Post to Concrete - M10 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1300	1250	1200	1150	1100
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M10
Drill hole diameter	= 12 mm
Drill hole depth	= 160 mm
Anchorage depth	= 150 mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation Notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - Fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Post and Concrete
- 5 - Use Threadlok on Nuts
- 6 - All fixings must be Stainless Steel



**Typical FACE Fix to Concrete - JEC 137/65, Gutter Bracket - M10 SS Studs**

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**

Balustrade Height above Deck, mm				
1000	1050	1100	1150	1200 max
1300	1250	1200	1150	1100
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

General Balustrades	17mm Balusters only
Balustrade Height, mm	Balustrade Height, mm
1200 max	1000 min - 1275 max
1000	1480
Post Spacing max, mm	Post Spacing max, mm

**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011




**Installation details Fischer FIS V 300T**

Thread diameter	M10
Drill hole diameter	= 12 mm
Drill hole depth	= 150 mm
Anchorage depth	= 140 mm


Drilling method	Hammer drilling
Drill hole cleaning	4 times blowing, 4 times brushing, 4 times blowing

No borehole cleaning required in case of using a hollow drill bit, e.g. fischer FHD.



**Important Installation Notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only
- 3 - Fixings must engage into the structural slab
- 4 - A PVC Tape layer must be installed between the Gutter Bracket and Concrete
- 5 - Use Threadlok on Nuts
- 6 - All fixings must be Stainless Steel





**Typical TOP Fix to Timber - JEC 221, 110mm x 90mm, 4 hole Base Plate - M10 SS Coachscrews or Bolts**

The pre NZS3604:2011 mounting details are included for older, existing buildings. New buildings must comply with NZS3604:2011- Double Boundary Joists

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above FFL, mm				
1000	1050	1100	1150	1200
1400	1350	1300	1250	1200
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 130mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKA Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical TOP Fix to Timber - JEC 200, 110mm x 100mm, 4 hole Base Plate - M10 SS Coachscrews or Bolts**

The pre NZS3604:2011 mounting details are included for older, existing buildings. New buildings must comply with NZS3604:2011- Double Boundary Joists

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above FFL, mm				
1000	1050	1100	1150	1200
1400	1350	1300	1250	1200
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 130mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKa Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical FACE Fix Post to Timber - M10 SS Coachscrews**

The pre NZS3604:2011 mounting details are included for older, existing buildings.  
New buildings must comply with NZS3604:2011- Double Boundary Joists

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above FFL, mm					
1000	1050	1100	1150	1200	
1400	1350	1300	1250	1200	
Post Spacing max, mm					

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 90mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKA Supergrip to full depth
- 5 - All Fixings must be Stainless steel



## Juralco EDGE® Balustrade System - Typical Post Fixings Pre NZS3604:2011 Connection. Single Boundary Joists

### Typical FACE Fix Post to Timber - M10 SS Bolts or Threaded Rod

The pre NZS3604:2011 mounting details are included for older, existing buildings. New buildings must comply with NZS3604:2011- Double Boundary Joists

#### Balustrade Dimensions by Wind Zone.

##### Up to and including Very High Wind Zone


Balustrade Height above FFL, mm				
1000	1050	1100	1150	1200
1400	1350	1300	1250	1200
Post Spacing max, mm				

##### Up to and including Extra High Wind Zone

**NOT SUITABLE.**


#### General Notes:

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



#### Important Installation notes:

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. New Timber SG8 minimum strength
- 3 - All Fixings must be Stainless steel



**Typical FACE Fix to Timber - JEC 137/65, Gutter Bracket - M10 SS Coachscrews**

The pre NZS3604:2011 mounting details are included for older, existing buildings. New buildings must comply with NZS3604:2011- Double Boundary Joists

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above FFL, mm					
1000	1050	1100	1150	1200	
1400	1350	1300	1250	1200	
Post Spacing max, mm					

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. Timber SG8 minimum strength
- 3 - Coachscrews 90mm min engagement into joists, predrill 6mm holes.
- 4 - Bond all coachscrews with SIKa Supergrip to full depth
- 5 - All Fixings must be Stainless steel



**Typical FACE Fix to Timber - JEC 137/65, Gutter Bracket - M10 SS Bolts or Threaded Rod**

The pre NZS3604:2011 mounting details are included for older, existing buildings. New buildings must comply with NZS3604:2011- Double Boundary Joists

**Balustrade Dimensions by Wind Zone.**

**Up to and including Very High Wind Zone**


Balustrade Height above FFL, mm				
1000	1050	1100	1150	1200
1400	1350	1300	1250	1200
Post Spacing max, mm				

**Up to and including Extra High Wind Zone**

**NOT SUITABLE.**


**General Notes:**

- 1 - All measurements mm
- 2 - Domestic Occupancy only A, A other and C3.
- 3 - Balustrade Height measured above Deck/FFL. 1000mm min
- 4 - Wind Zones as per NZS 3604:2011



**Important Installation notes:**

- 1 - The Project Engineer must ensure the structure can support the appropriate loads
- 2 - Substructure shown indicatively only. New Timber SG8 minimum strength
- 3 - All Fixings must be Stainless steel






**Post Caps - no swivel/clamp**

Use for 10mm Toughened Glass with Handrail,  
or 13.2mm Laminated Glass with no Handrail.  
Top Protection Cap recommended



All tap fit

**Post Caps - with swivel/clamp - to Handrail**








Attach from top with special  
14g dia x 50mm SS PK Capscrew


Showing 35deg max inclination - for all handrails

**Handrail Attach**

All handrails fixings identical - clamp attach with M8 grubscrew




**Baseplate to Post Attach**



JVBHT SCREW/ 50 x 10  
C/S PK SQ drive high tensile screws


**Glass Support Attach**



Drill 2 x 4dia  
holes at 12mm C/L

Glass Support  
Bracket (Nylon)

2 x No 8 x 16  
SS PK Screws




Glass Edge

Use appropriate  
Plastic Packer


10  
12

Standard Infill  
below Glass  
Support Bracket



Showing Glass and seals  
above the Glass Support Bracket



**Important Note:**  
All Glass  
engagement  
10mm min



Showing Standard Infill  
below Glass Support Bracket



**Handrail Attach  
at Corner Post**

All handrails fixings identical - clamp attach with M8 grubscrew








Plan view above, looking down through  
1 - Hand rail  
2 - Top Cap/Handrail Corner Mount  
3 - Corner Post

**Important Note:**  
**All Glass Engagements**  
**10mm min**






**Bottom Rail to Post Attach**

**Bottom Rail Spigot JEB/210  
(Suitable all Posts)**







**Bottom Rail to Post Attach**

**Heavy Duty Bottom Rail Spigot JET/917/5**  
(NOT Suitable Semi Frameless Posts)




**Bottom Rail to Post Attach  
(Viking Components)**

Viking Bottom Rail Spigot JVB017  
(NOT Suitable Semi Frameless Posts)




**This Setout for Baluster Installations**

**This Setout for Glass Installations**




Attaching Bottom or Top Rail  
TOP Fix Edge Post. PN JEB/207/5  
or FACE Fix Edge Post. PN JEB/208/5  
Not suitable for Semiframeless Posts




Drill Bottom Rail, Top rail if needed

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




**4 - Glass, Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - Bottom Rail, Cut to  
=  $PCL - 2 \times 22.5 = PCL - 45$
- d - 6mm Glass height  
=  $HH - 2 \times 22 - 99 = HH - 143$
- e - 6mm Glass width  
=  $PCL - 2 \times 12 = PCL - 24$   
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm


G Gap = 20mm, D = 92mm

G Gap = 30mm, D = 88mm

G Gap = 40mm, D = 82mm

G Gap = 50mm max, D = 75mm

**4 - Glass, Width Offsets**



**5 - Cutting, nominal**

a - Hand Rail = Use maximum lengths

b - Post, Cut to

= HH-73+OL

c - Bottom Rail, Cut to

= PCL-2x22.5 = PCL - 45

d - 6mm Glass height

= HH-2x22-99 = HH - 143


e - 6mm Glass width

= PCL- 2x12 = PCL - 24


or tight distance between posts  
at deck level + 24mm



**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm


G Gap = 20mm, D = 92mm

G Gap = 30mm, D = 88mm

G Gap = 40mm, D = 82mm

G Gap = 50mm max, D = 75mm

**4 - Glass, Width Offsets**



**5 - Cutting, nominal**

a - Hand Rail = Use maximum lengths

b - Post, Cut to

= HH-73+OL

c - Bottom Rail, Cut to

= PCL-2x22.5 = PCL - 45

d - 6mm Glass height


= HH-2x22-D = HH - 44 - D

e - 6mm Glass width


= PCL- 2x12 = PCL - 24

or tight distance between posts at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




**4 - Glass, Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - Bottom Rail, Cut to  
=  $PCL - 2 \times 22.5 = PCL - 45$
- d - 6mm Glass height  
=  $HH - 2 \times 22 - 99 = HH - 143$
- e - 6mm Glass width  
=  $PCL - 2 \times 22.5 - 2 \times 50 = PCL - 145$

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**

G Gap = 10mm, D = 96mm
G Gap = 20mm, D = 92mm
G Gap = 30mm, D = 88mm
G Gap = 40mm, D = 82mm
G Gap = 50mm max, D = 75mm

**4 - Glass, Width Offsets**




Top fix EDGE post JEB/207  
Semiframeless  
6mm Toughened Glass


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 6mm Glass height  
= HH-2x22-D = HH - 44 - D
- e - 6mm Glass width  
= PCL-2x22.5-2x50 = PCL - 145

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm
G Gap = 20mm, D = 92mm
G Gap = 30mm, D = 88mm
G Gap = 40mm, D = 82mm
G Gap = 50mm max, D = 75mm

**4 - Glass, Width Offsets**




Face fix EDGE post JEB/208  
Semiframeless  
6mm Toughened Glass

**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 6mm Glass height  
= HH-22-D = HH - 44 - D
- e - 6mm Glass width  
= PCL-2x22.5-2x50 = PCL - 145

**6mm Toughened Glass - Full Height. Handrail + Split Rails. Top Fix**

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**4 - Glass, Width Offsets**




Top fix EDGE post JEB/207  
Semiframeless  
6mm Toughened Glass


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - Bottom Rail (x2), Cut to  
=  $PCL - 2 \times 22.5 = PCL - 45$
- d - 6mm Glass height  
=  $HH - 27 - 22 - 2 \times 99 - 48 = HH - 295$
- e - 6mm Glass width  
=  $PCL - 2 \times 22.5 - 2 \times 50 = PCL - 145$


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



**Important Note:**  
All Glass Engagements  
10mm min

**4 - Glass, Width Offsets**



Top fix EDGE post JEB/207  
Semiframeless  
6mm Toughened Glass

**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail (x2), Cut to  
= PCL-2x22.5 = PCL - 45
- d - 6mm Glass height  
= HH-48-27-22-99-D = HH - 196 - D
- e - 6mm Glass width  
= PCL-2x22.5-2x50 = PCL - 145


Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**


**Opening to the deck**

- G Gap = 10mm, D = 96mm
- G Gap = 20mm, D = 92mm
- G Gap = 30mm, D = 88mm
- G Gap = 40mm, D = 82mm
- G Gap = 50mm max, D = 75mm


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



**Important Note:**  
**All Glass Engagements**  
**10mm min**

**4 - Glass, Width Offsets**



Face fix EDGE post JEB/208  
Semiframeless  
6mm Toughened Glass

**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail (x2), Cut to  
= PCL-2x22.5 = PCL - 45
- d - 6mm Glass height  
= HH-48-27-22-99-D = HH - 196 - D
- e - 6mm Glass width  
= PCL-2x22.5-2x50 = PCL - 145


Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**

G Gap = 10mm, D = 96mm
G Gap = 20mm, D = 92mm
G Gap = 30mm, D = 88mm
G Gap = 40mm, D = 82mm
G Gap = 50mm max, D = 75mm




**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




A Corner Post is available for 10mm Glass,  
Inline - Semi Frameless. Top Mount only  
with 110mm sq JEC 222 Baseplate

**2 - Handrail - Offsets**




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-54-12
- c - 10mm Glass height  
= HH - 104
- d - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**

G Gap = 10mm, D = 91mm
G Gap = 20mm, D = 86mm
G Gap = 30mm, D = 80mm
G Gap = 40mm, D = 72mm
G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass

**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-54+ OL
- c - 10mm Glass height  
= HH-5-D
- d - 10mm Glass width  
= PCL- 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**10mm Toughened Glass - Semi Frameless + Handrail. Face Fix**

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**

G Gap = 10mm, D = 91mm  
G Gap = 20mm, D = 86mm  
G Gap = 30mm, D = 80mm  
G Gap = 40mm, D = 72mm  
G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**




Face fix EDGE post JEB/214  
Semiframeless  
10mm Toughened Glass

**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-54+OL
- c - 10mm Glass height  
= HH-5-D
- d - 10mm Glass width  
= PCL- 2x12 = PCL- 24  
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




A Corner Post is not suitable available for this configuration

**2 -Glass Top - Offsets**




Other suitable Handrails




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= 840 min
- c - 10mm Glass height  
= GH - 99
- d - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 -Glass Top - Offsets**




**Other  
suitable  
Handrails**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm  
Opening to the deck**

G Gap = 10mm, D = 91mm  
G Gap = 20mm, D = 86mm  
G Gap = 30mm, D = 80mm  
G Gap = 40mm, D = 72mm  
G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to = 850 + OL
- c - 10mm Glass height = GH-D
- d - 10mm Glass width = PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 -Glass Top - Offsets**




**Other suitable Handrails**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 91mm


G Gap = 20mm, D = 86mm

G Gap = 30mm, D = 80mm

G Gap = 40mm, D = 72mm

G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**



Face fix EDGE post JEB/214  
Semi frameless  
10mm Toughened Glass

**5 - Cutting, nominal**

a - Hand Rail = Use maximum lengths


b - Post, Cut to  
= 850 + OL

c - 10mm Glass height  
= GH-D

d - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**

Top Protection Cap JET 212 between Posts highly recommended





A Corner Post is available  
Inline - Semi Frameless. Top Mount only  
with 110mm sq JEC 222 Baseplate

**2 -Glass Top - Offsets**





**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**4 - Glass, Width Offsets**



Top fix EDGE post JEB/212  
Semiframeless  
13.2mm Laminated Toughened Glass


**5 - Cutting, nominal**

- a - Post, Cut to  
= GEH - 12
- b - 13.2mm Glass height  
= GEH - 99
- c - 13.2mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm




**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**

Top Protection Cap JET 212 between Posts highly recommended




**2 -Glass Top - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm,	D = 91mm
G Gap = 20mm,	D = 86mm
G Gap = 30mm,	D = 80mm
G Gap = 40mm,	D = 72mm
G Gap = 50mm max,	D = 61mm

**4 - Glass, Width Offsets**



Top fix EDGE post JEB/212  
Semiframeless  
13.2mm Laminated Toughened Glass


**5 - Cutting, nominal**

- a - Post, Cut to  
= GEH+ OL
- b - 13.2mm Glass height  
= GEH-D
- c - 13.2mm Glass width  
= PCL- 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm


**13.2mm Toughened Laminated Glass - Semi Frameless. Face Fix**

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**

Top Protection Cap JET 212 between Posts highly recommended




**2 - Glass Top - Offsets**



**Glass Flush to top of Post**

**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**





Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm,	D = 91mm
G Gap = 20mm,	D = 86mm
G Gap = 30mm,	D = 80mm
G Gap = 40mm,	D = 72mm
G Gap = 50mm max,	D = 61mm

**4 - Glass, Width Offsets**




Face fix EDGE post JEB/214  
Semiframeless  
13.2mm Laminated Toughened Glass

**5 - Cutting, nominal**


- a - Post, Cut to  
= GEH + OL
- b - 13.2mm Glass height  
= GEH-D
- c - 13.2mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




Applies to Swimming Pools as of Jan 2017  
Complies with the Building Code Clause F9  
and section 162C of the Building Act.  
Applies to Pool Fences not protecting  
a fall of 1.0m or more

**2 -Glass Top**




**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**



**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass

**5 - Cutting, nominal**


- a - Post, Cut to  
= 1200-12
- b - 10mm Glass height  
= 1100
- c - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




Applies to Swimming Pools as of Jan 2017  
Complies with the Building Code Clause F9  
and section 162C of the Building Act.  
Applies to Pool Fences not protecting  
a fall of 1.0m or more

**2 -Glass Top - Offsets**



**Important Note: All Glass Engagements 10mm min**


**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**  
G Gap = 10mm, D = 91mm  
G Gap = 20mm, D = 86mm  
G Gap = 30mm, D = 80mm  
G Gap = 40mm, D = 72mm  
G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**




Top fix EDGE post JEB/212  
Semiframeless  
10mm Toughened Glass

**5 - Cutting, nominal**


- a - Post, Cut to  
= 1200 + OL
- b - 10mm Glass height  
= 1200 - D
- c - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




Applies to Swimming Pools as of Jan 2017  
Complies with the Building Code Clause F9  
and section 162C of the Building Act.  
Applies to Pool Fences not protecting  
a fall of 1.0m or more

**2 -Glass Top - Offsets**



**Important Note: All Glass Engagements 10mm min**

**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 91mm  
G Gap = 20mm, D = 86mm  
G Gap = 30mm, D = 80mm  
G Gap = 40mm, D = 72mm  
G Gap = 50mm max, D = 61mm

**4 - Glass, Width Offsets**




Face fix EDGE post JEB/214  
Semiframeless  
10mm Toughened Glass

**5 - Cutting, nominal**


a - Post, Cut to  
= 1200 + OL  
b - 10mm Glass height  
= 1200 - D  
c - 10mm Glass width  
= PCL - 2x12 = PCL - 24  
or tight distance between posts  
at deck level + 24mm

**17mm Baluster - Full Height. Handrail + Bottom Rail. Top Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**



**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - Bottom Rail, Cut to  
=  $PCL - 2 \times 22.5 = PCL - 45$
- d - 17mm sq Baluster, Cut to  
=  $HH - 34.5 - 31.5 - 99 = HH - 165$

**17mm Baluster - Full Height. Handrail + Bottom Rail. Gutter Brkt Face Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**

G Gap = 10mm, D = 96mm  
G Gap = 20mm, D = 92mm  
G Gap = 30mm, D = 88mm  
G Gap = 40mm, D = 82mm  
G Gap = 50mm max, D = 75mm

**4 - Width Offsets**



Top fix Edge post  
JEB/207


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 17mm sq Baluster, Cut to  
= HH-34.5-31.5-D = HH - 66 - D




**17mm Baluster - Full Height. Handrail + Bottom Rail. Face Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm


G Gap = 20mm, D = 92mm

G Gap = 30mm, D = 88mm

G Gap = 40mm, D = 82mm

G Gap = 50mm max, D = 75mm

**4 - Width Offsets**



Face fix Edge post  
JEB/208

**5 - Cutting, nominal**

a - Hand Rail = Use maximum lengths

b - Post, Cut to

= HH-73+OL

c - Bottom Rail, Cut to


= PCL-2x22.5 = PCL - 45

d - 17mm sq Baluster, Cut to


= HH-34.5-31.5-D = HH - 66 - D

**17mm Baluster - Split Rail. Handrail + Top and Bottom Rail. Top Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**




**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73-12 = HH - 85
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 17mm sq Baluster, Cut to  
= HH-48-99x2-31.5x2 = HH - 309


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm,	D = 96mm
G Gap = 20mm,	D = 92mm
G Gap = 30mm,	D = 88mm
G Gap = 40mm,	D = 82mm
G Gap = 50mm max,	D = 75mm

**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 17mm sq Baluster, Cut to  
= HH-48-99-31.5x2-D = HH - 210 - D

**17mm Baluster - Split Rail. Handrail + Top and Bottom Rail. Face Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm


G Gap = 20mm, D = 92mm

G Gap = 30mm, D = 88mm

G Gap = 40mm, D = 82mm

G Gap = 50mm max, D = 75mm

**4 - Width Offsets**



**5 - Cutting, nominal**


a - Hand Rail = Use maximum lengths

b - Post, Cut to  
= HH-73+OL


c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45

d - 17mm sq Baluster, Cut to  
= HH-48-99-31.5x2 - D = HH - 210 - D


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**




**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73-12 = HH - 85
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 60mm Slat Baluster, Cut to  
= HH-34.5-31.5-99 = HH - 165


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**  
G Gap = 10mm, D = 96mm  
G Gap = 20mm, D = 92mm  
G Gap = 30mm, D = 88mm  
G Gap = 40mm, D = 82mm  
G Gap = 50mm max, D = 75mm


**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 60mm Slat Baluster, Cut to  
= HH-34.5-31.5-D-OL = HH-66-D-OL


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the  $D$  Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**  
**G Gap = 10mm, D = 96mm**  
**G Gap = 20mm, D = 92mm**  
**G Gap = 30mm, D = 88mm**  
**G Gap = 40mm, D = 82mm**  
**G Gap = 50mm max, D = 75mm**

**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 + OL$
- c - Bottom Rail, Cut to  
=  $PCL - 2 \times 22.5 = PCL - 45$
- d - 60mm Slat Baluster, Cut to  
=  $HH - 34.5 - 31.5 - D = HH - 66 - D$




**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**



**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73-12 = HH - 85
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 60mm Slat Baluster, Cut to  
= HH-48-99x2-31.5x2 = HH - 309

**60mm Slat - Split Rail. Handrail + Top and Bottom Rail. Gutter Brkt Face Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm
G Gap = 20mm, D = 92mm
G Gap = 30mm, D = 88mm
G Gap = 40mm, D = 82mm
G Gap = 50mm, max D = 75mm

**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - Bottom Rail, Cut to  
= PCL-2x22.5 = PCL - 45
- d - 60mm Slat Baluster, Cut to  
= HH-48-99-31.5x2-D = HH - 210 - D

**60mm Slat - Split Rail. Handrail + Top and Bottom Rail. Face Fix**


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**  
G Gap = 10mm, D = 96mm  
G Gap = 20mm, D = 92mm  
G Gap = 30mm, D = 88mm  
G Gap = 40mm, D = 82mm  
G Gap = 50mm max, D = 75mm


**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to =  $HH - 73 + OL$
- c - Bottom Rail, Cut to =  $PCL - 2 \times 22.5 = PCL - 45$
- d - 60mm Slat Baluster, Cut to =  $HH - 48 - 99 - 31.5 \times 2 - D = HH - 210 - D$


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**




**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - 60mm Slat Cut to  
=  $PCL - 45$


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**



**4 - Width Offsets**



**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - 60mm Slat Cut to  
= PCL - 45


Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**


**Opening to the deck**

- G Gap = 10mm, D = 96mm
- G Gap = 20mm, D = 92mm
- G Gap = 30mm, D = 88mm
- G Gap = 40mm, D = 82mm
- G Gap = 50mm max, D = 75mm


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**




**3 - Height offsets**



Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm Opening to the deck**  
G Gap = 10mm, D = 96mm  
G Gap = 20mm, D = 92mm  
G Gap = 30mm, D = 88mm  
G Gap = 40mm, D = 82mm  
G Gap = 50mm max, D = 75mm

**4 - Width Offsets**




Face fix Edge post  
Semiframeless JEB/214


**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - 60mm Slat Cut to  
= PCL - 45


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**



**4 - Width Offsets**




**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
=  $HH - 73 - 12 = HH - 85$
- c - 123mm Slat Cut to  
=  $PCL - 45$




**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**



**2 - Handrail - Offsets**



**3 - Height offsets**




Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.

**D max values for a 99mm**

**Opening to the deck**

G Gap = 10mm, D = 96mm
G Gap = 20mm, D = 92mm
G Gap = 30mm, D = 88mm
G Gap = 40mm, D = 82mm
G Gap = 50mm max, D = 75mm


**4 - Width Offsets**




**5 - Cutting, nominal**

- a - Hand Rail = Use maximum lengths
- b - Post, Cut to = HH-73+OL
- c - 60mm Slat Cut to = PCL - 45


**1 - Refer Post Mounting type and installation Wind zone. Then choose Balustrade Height and max Post spacing.**




**2 - Handrail - Offsets**



**3 - Height offsets**



**4 - Width Offsets**



**5 - Cutting, nominal**


- a - Hand Rail = Use maximum lengths
- b - Post, Cut to  
= HH-73+OL
- c - 60mm Slat Cut to  
= PCL - 45

Note - Because the Bottom Rail is mounted forward of the Deck Edge the D Dimension is no longer 99mm.


**D max values for a 99mm Opening to the deck**

G Gap = 10mm,	D = 96mm
G Gap = 20mm,	D = 92mm
G Gap = 30mm,	D = 88mm
G Gap = 40mm,	D = 82mm
G Gap = 50mm max,	D = 75mm


**These Set out constraints apply to all 17mm sq Balusters, 49mm and 60mm Slats**



17mm sq Balusters  
215mm C/L max






49mm Slats  
247mm C/L max






60mm Slats  
258mm C/L max




**17mm Baluster - Full Height. Handrail + Bottom Rail. Top Mount, Gutter Brkt Face Fix or Face Fix**






**17mm Baluster - Split Rail. Handrail + Top and Bottom Rail. Top Mount, Gutter Brkt Face Fix or Face Fix**





**49mm or 60mm Slat - Full Height. Handrail + Bottom Rail. Top Mount, Gutter Brkt Face Fix or Face Fix**



**49mm or 60mm Slat - Split Rail. Handrail + Top and Bottom Rail. Top Mount, Gutter Brkt Face Fix or Face Fix**





**10mm Glass, Inline - Semi Frameless. Hand Rail  
(Corner Post available for Top Mount)**



**Note: All Glass Engagements 10mm min**

Apply bead of RTV silicon the the inside face of Post Pocket for full height of glass panel

**10mm Glass, Inline - Semi Frameless. Hand Rail + JEC 29 Bracket  
(Corner Post not applicable to Top Mount, this configuration)**





**Note: All Glass Engagements 10mm min**

Apply bead of RTV silicon the the inside face of Post Pocket for full height of glass panel

**13.2mm Laminated Glass, Inline - Semi Frameless.**


Top Protection Cap, between Posts recommended




**Note: All Glass Engagements 10mm min**

**10mm Glass, Inline - Semi Frameless. Corner Post - Handrail or Interlinking Rail Top Mount only**

A Corner Post is available for 10mm Glass, Inline - Semi Frameless. Top Mount only with 110mm sq JEC222 Baseplate






**EDGE LED OPAL DIFFUSER**  
Part No JEC44/3/Opal



**LED STRIP**  
C/w DS tape  
(Size to suit)




**INFILL DIMENSIONS**


All these Handrails have the same Infill dimensions

**LED Opal Diffuser**  
(Discontinuous, between Posts)


**LED Light strip (Continuous)**



**Typical Handrail with LED Installed**



**RECTANGULAR HANDRAIL**  
Part No JEB/216/5.8




**ROUND HANDRAIL**  
Part No JEB/209/5.8


**Other Suitable Handrails**

**EDGE Balustrade LED Lighting Options**


**6mm Toughened Glass - Full Height. Handrail + Split Rails.**




**Baluster - Split Rail. Handrail + Top and Bottom Rail.**



**13.2mm Laminated Toughened Glass - Semi Frameless.**



**10mm Toughened Glass - Semi Frameless + JEC 29 Bracket mounted on Post + Handrail.**



Slats  
JGF/2227  
123mm x 17mm  
Custom Corner,  
Screwed

Face Fixed  
Gutter Brackets



Slats  
JGF/2227  
123mm x 17mm

Floating Deck

Face Fixed  
EDGE posts




**IMPORTANT NOTE: The Balustrade Height is measured from the Top of the Structural Deck, not the Top of the Floating Deck**




**Basic Floating EDGE Cover Layout  
+ Glass Panel Above**

**Basic Floating EDGE Cover Layout**




**Basic Floating Deck Layout  
Applies to Face fix or Gutter Bracket**

**Stecca Balustrade System - Components**




**Lamerra™ Balustrade System - Components**


**For ALL, Panel Insert System**



**For Panel Face Fix  
Screwed Panel System**






FRAME  
Part No JCG7811








**STECCA**  
**Bottom Rails - In Line Mount**




**STECCA**  
**Bottom Rails - Front Mount**







**Juralco EDGE® Balustrade System**  
**Vertical Louvre/Slat/Glass Configurations**  
**For Fixing between Walls or Structural Posts**




Louvre 120mm JGF/2231 Overlapped





Infill Slat 123mm JGF/2227. Gaps 99mm max



Infill Slat 60mm JVB/019 Gaps 99mm max



Infill Slat 49mm JVB/018 Gaps 99mm max



Louvre 120mm JGF/2231  
Overlapped  
Width 2000mm max.  
Height 2400mm max


**Max Widths for different  
Wind Zones**

Up to and including Medium WZ	2000mm
Up to and including High WZ	1700mm
Up to and including Very High WZ	1500mm
Up to and including Extra High WZ	1400mm

10mm Toughened Glass  
Width 2000mm max.  
Height 2400mm max  
Refer Wind Zone limitations

**Note: Glass Engagements 10mm min**

**Juralco EDGE® Vertical Louvre/Slat/Glass Configurations**  
**Fixing between Walls or Structural Posts.**  
**Special Endplate JEC420**



**Important Installation Notes:**

- 1 - Attaching to Timber.** 4 total (ie 2 x ea ends) M10 x 100 SS C/s Socket drive Coachscrews central in a 90mm stud  
Sika Supergrip to full depth. + 2 x 12g x 50mm SS Woodscrews
- 2 - Attaching to Steel.** 2 x M10 x 40 C/s SS Socket drive Machine Screws and Nut+ 2 x M6 SS Bolts
- 3 - Attaching to Concrete.** 2 x M10 Fischer FIS V Fasteners + M10 x 40 C/s SS Socket drive Machine Screw  
+ 2 x M6 Fischer FIS V Fasteners + M6 x 30 SS Socket drive Machine Screws

**Note: Fixing Options assume End Plates fixed directly to supporting structure**


**NZBC Compliance**

- The Juralco Edge Vertical Louvre, Slat and Glass System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and AS/NZS 1170 : 2002. Occupancy A, B, E, C3,
- NZS 3604 Up to and including Low, Medium, High, Very High Wind Zones. Up to a max Design Wind Speed of 50m/sec but not exceeding a Design Wind Pressure of 1.5kPa
- The Structural Engineering design includes the requirements of B1 Structure, B2 Durability and F4 Safety from falling of the Building Code
- Verification Method B1 / VM1, B2/AS1, F4 / As1, F2 Hazardous Building Materials
- Gaps all less than 100mm.

**Alternative Fixings, if required**


- The Specific Engineering Design should be able to resist  $G = 0.5\text{kN}$  Vertical Load. and  $W_u = 2.44\text{kN}$  Face load

**Juralco EDGE® Balustrade System**  
**LAMERRA™ Balustrade**  
Height, Width, Wind Zones all as per EDGE® Balustrade




**Option 1**

- **Metal Panel Inset**, fully recessed into all 4 x sides
- Posts. Edge Framless
- Bottom Rail at base, Handrail at Top
- Bottom Rail, normal C/L mount
- Note the Smaller bottom gap for Face fix



**Option 2**


- **Metal Panel Inset**, fully recessed into all 4 x sides
- Posts. Edge (hidden fixing)
- Bottom Rail at Top and Base
- Bottom and Top Rail, normal C/L mount
- Note the Smaller bottom gap for Face fix
- Can use Round Handrail+Mini clip



**Option 3**

- **Metal Panel, Screw Face Fixed** all 4 x sides
- Posts. Edge (Face fix- exposed Fixings)
- Bottom Rail at Top and Base, Front mounted
- Note the Smaller bottom gap for Face fix
- Can use Round Handrail+Mini clip
- Clip assembly to hide Screw heads

**Clearguard**  
**Perforated Panel Specs**




Specifications:  
Combined Security and Insect Screen.  
Rigid perforated sheet 2.0mm, Hardened  
Open area 32%. Sizes 2000, 2400mm  
x 750, 900, 1200mm Wide  
Finish, Black Powdercoat, SCC

**Sheet perforations, Full size**

**Aluminium Sheet Ordering Codes**

JCG/ALA/2.0/BLK	750mm x 2000mm
JCG/ALA/2.4/BLK	750mm x 2400mm
JCG/ALC/2.0/BLK	900mm x 2000mm
JCG/ALC/2.40/BLK	900mm x 2400mm
JCG/ALD/2.0/BLK	1200mm x 2000mm
JCG/ALD/2.40/BLK	1200mm x 2400mm
JCG/ALD/2.4	2400mm x 1200mm

**Plain Panel Specs**  
**Rigid Sheet**



**Aluminium Sheet Ordering Codes**


JAS/101440	1200 x 2400 x 2.5mm
Can be BLK or SCC	5052 H34

Specifications:  
Combined Security and Insect Screen.  
Rigid perforated sheet 2.0mm, Hardened  
Open area 32%  
**Size 2400mm x 1200 Only**  
Finish, Black or any Powdercoat Colour

**ALL for Metal Panel Inset**  
**All for Face Hidden mounting**

Typical FACE Fix Post JEB/214  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.


(see individual EDGE pages for  
full mounting details)



**ALL for Metal Panel Face Fix**  
**All for Face Exposed mounting**

Typical FACE Fix Post JEB/207  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.


(see individual EDGE pages for  
full mounting details)



**ALL for Metal Panel Inset**  
**For Top mounting**

Typical Top Fix Post JEB/212  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.


(see individual EDGE pages for  
full mounting details)



**ALL for Metal Panel Face Fix**  
**For Top mounting**

Typical Top Fix Post JEB/207  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.


(see individual EDGE pages for  
full mounting details)



**ALL for Metal Panel Inset**  
**For Gutter Bracket mounting**

Typical Gutter Bracket Fix Post JEB/212  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.


(see individual EDGE pages for  
full mounting details)



**ALL for Metal Panel Face Fix**  
**For Gutter Bracket mounting**

Typical Gutter Bracket Fix Post JEB/207  
to Timber with Coachscrews or Bolts  
or to Steel with Bolts  
or to Concrete with Studs.

(see individual EDGE pages for  
full mounting details)



**Juralco EDGE® LAMERRA™ Balustrade System**  
**Metal Panel Inset - Assembly. Options 1&2**


①

**Cutting the Metal Sheet**

After measuring Post C/L spacings and Height, then making appropriate deductions

**Cutting**


- 1- Cut Frame to measurements at exact 45 deg miters.
- 2 - Cut PVC plugs to length, straight cuts.
- 3 - Cut mid rails (optional), straight cuts.
- 4 - Cut metal sheet, square on all four sides.
- 5 - After cutting the offsets should be as drawn.



**Note: IT IS VERY IMPORTANT THAT THE SHEET IS CUT EXACTLY SQUARE AND STRAIGHT**

②

**Assemble Frame around Metal Panel**







**Juralco EDGE® LAMERRA™ Balustrade System**  
**Metal Panel Inset - Assembly. Options 1&2**

**Option 1**  
**Panel + Frame, Heights**

For Top fix, Face Fix  
or Gutter Bracket.  
Hidden Fixings





Available Handrails, for Panel Inset into Handrail




**Option 2**  
**Panel + Frame, Heights**

For Top fix, Face Fix  
or Gutter Bracket.  
Hidden Fixings




All Handrail types available for this configuration




**Options 1 & 2**  
**Panel + Frame, Widths**

For Top fix, Face Fix  
or Gutter Bracket.  
Hidden Fixings




**Rail Attach to Post**

This Panel Fixing style  
allows for Hidden Fixings




EDGE POST. 45mm x 65mm JEB/212  
**To be used for Panel Inset**  
**as mounted Top Fix only**




EDGE POST 45mm x 65mm JEB/214  
**To be used for Panel Inset**  
**as mounted Face Fix only**

**Option 3**  
**Panel + Clips, Dimensions**

Only For Face Fix, Exposed Fixings  
All Handrail types available for this configuration




Top Rail  
Front faces flush




Bottom Rail  
Front faces flush


EDGE POST 45mm x 65mm JEB/207  
**To be used for Panel Face Fixed either**  
**Top or Face Fix (exposed Fastenings)**



Bottom/Top Rail + Post  
Front faces flush



Verticals Clips shown,  
Horizontals not shown.  
Miter Corners




Base  
Clip on Cover  
2 Part Clip.  
Black PVC


### **Juralco EDGE® LAMERRA™ Balustrade System**

#### **Metal Panel Face Fixed - Screw Fixing Details**


Only For Face Fix, Exposed Fixings  
All Handrail types available for this configuration





Only For Face Fix, Exposed Fixings  
All Handrail types available for this configuration



## VERTICAL EDGES




EDGE POST 45mm x 65mm JEB/207/5  
To be used for Panel Face Fixed either  
Top or Face Fix (exposed Fastenings)

Perforated Panel setback  
from Top Edge




**Juralco EDGE® Balustrade System**  
**X Balustrade - Layout**

17mm Baluster - Split Rail. Handrail + Top and Bottom Rail. Top Mount



EDGE POST  
JEB/207/5

Circular Handrail JEB/223



### Powder Coating Installation Care

#### **Warning re use of solvents:**

- In some cases strong solvents are recommended for thinning various types of paints and also for cleaning up mastics and sealants.
- These can be harmful to the extended life of the powder coated surface, and must not be used for cleaning purposes.
- It is important to note that the damage will not be visible immediately and may take up to 12 months to develop.

If paint splashes or sealants and mastics need to be removed then the following may be safely used:  
Methylated Spirits, Ethyl Alcohol, Isopropanol or preferably a mild detergent in warm water.

#### **Joinery Protection during Installation:**

All the activity on a construction site means that your powder coated items may get knocked or scratched, splattered with mortar, plaster, textured coating or paint during the later stages of construction.

Please ensure that all powder coated articles are masked or covered at this time. It is far easier to prevent accidents than to try and correct them. Should your joinery receive mortar or paint splashes see that these are removed before cure and follow the instructions contained in this brochure.

Typical sticker used to warn other trades of the need to protect and mask off powder coated joinery (applies to anodised joinery also)

**"IMPORTANT ALL TRADES"**  
This valuable aluminium joinery will suffer permanent damage from: plaster, mortar and paint splashes - Protect if splashes occur - Immediately wash down joinery with water or meths - Do not allow splashes to harden! ~ Do not use solvents! - Do not remove this label until final clean completed.

This photograph display damage that has occurred on site, post installation. The photo of the masked joinery displays clear signs of damage that could have occurred were it not masked. Please ensure that your joinery is protected right through the entire construction process.



### Powder Coating Maintenance

#### **External - Maintenance Program:**

To extend the life of external powder coated articles and to comply with warranty requirements for powder coated aluminium joinery, a simple, regular maintenance program must be implemented.

The effects of ultra violet light, atmospheric pollution, dirt, grime and airborne salt deposits will all accumulate over time and must be removed or surface staining and weathering will occur, leading to an unsightly appearance.

For external coatings, cleaning should take place every six months. In areas where pollutants are more prevalent, such as beachfront houses and industrial or geothermal areas, then a cleaning program should be carried out on a more frequent basis ie. every one to three months.

Fences or Balustrades in close proximity to swimming pools must be washed down every six months, to clean off chlorine and salt deposits.

#### **Cleaning your powder coating:**

1. Carefully remove any loose surface deposits with a wet sponge.
2. Use a soft brush (non abrasive) and a mild household detergent (do not use solvents) in warm water, remove dust, salt and other deposits.
3. Rinse off with clean fresh water.

#### **Restoring weathered or scratched surfaces:**

Repair of Scuffed or Scratched surfaces

Dulux Spray Cans are available in all colour card colours.

Repair of Small Scratches or Chips.

Dulux Dabsticks are ideally suited for the repair of small scratches.

Dabsticks may not be available in all colour card colours.

Repair of Weathered areas .

Dulux Gloss Up is a light to medium cutting cream ideally suited for gloss restoration and has been specifically designed for this purpose. Gloss Up contains no waxes or silicone and is a one step system.

**Contact Dulux Powder Coatings , ph 0064 9 441 8244**



### Glass Cleaning and Maintenance

Architectural glass products must be properly cleaned during the construction period so visual and aesthetic clarity are maintained. Because glass can be permanently damaged if improperly cleaned, glass producers and fabricators recommend strict compliance with the following procedures.

First, determine whether the glass is clear, tinted or reflective. Surface damage is more noticeable on reflective glass compared with the other glass products. If the reflective coated surface is exposed, either on the exterior or interior, special care must be taken when cleaning, as scratches can result in coating removal and a visible change in light transmittance. Cleaning tinted and reflective glass in direct sunlight should be avoided. Cleaning should begin at the top of the building and continue to the lower levels.

Commence cleaning by soaking the glass surfaces with clean water and a soap solution to loosen dirt or debris. Then, using a mild, non-abrasive commercial window washing solution, uniformly apply the solution to the glass surfaces with a non-abrasive applicator and follow with a squeegee to remove all of the cleaning solution from the glass surface.

Ensure that no metal parts of the cleaning equipment touch the glass surface and that no abrasive particles are trapped between the glass and the cleaning materials. All water and cleaning solution residue should be dried from the window gaskets, sealants and frames.

### Scratches and Metal Scrapers

Scratches can occur from hard pointed objects or poor handling, but most often occurs from the careless removal of foreign matter from the glass surface.

Mortar splatter and paint are common offenders and efforts to remove after hardening almost always lead to surface damage. It is essential that the foreign materials are removed before they harden. Better still, if construction work continues after glazing, that the glazed areas are protected by adhesive plastic films or suitable tarpaulins or covers.

One of the common mistakes made by non-glass trades people, including glass cleaning contractors, is the use of razor blades or other metal scrapers on a large portion of the glass surface. Using large blades to scrape a window clean carries considerable risk of causing damage to the glass.

The glass industry, fabricators, distributors and installers neither condones nor recommends any scraping of glass surfaces with metal blades or knives. Such scraping usually permanently damages or scratches the glass surfaces. When paint or other construction materials cannot be removed with normal cleaning procedures, a new 25mm razor blade may have to be used. The razor blade should be used on small spots only. Cleaning should be done in one direction only. Never scrape in a back and forth motion as this could trap particles under the blade that could scratch the glass.

Blades or scrapers can dislodge "pickup" on toughened glass. There are fine particles of glass that are fused on to the surface during toughening. Once dislodged they can scratch the glass.

---

#### **Glass Cleaning, Do's and Don'ts**

##### **DO NOT..**

- Do Not - Use Scrapers of any type or size on a Glass surface
- Do Not - Leave building dirt or residues to remain on Glass for a period of time.
- Do Not - Begin cleaning glass until you have identified the surface type.
- Do Not - Clean Glass surfaces in direct sunlight.
- Do Not - Allow dirty water or cleaning residues to remain on the Glass.
- Do Not - Begin cleaning before rinsing off a loose residues.
- Do Not - Use abrasive cleaning solutions, materials or solvents.
- Do Not - Allow metal parts of the cleaning equipment to come in contact with the Glass.
- Do Not - Trap abrasive particles between the cleaning material and the Glass.

##### **DO...**

- Clean glass promptly when dirt or building residues appear.
- Determine glass surface type.
- Exercise special care when cleaning coated surfaces.
- Avoid cleaning glass surfaces in direct sunlight.
- Start cleaning at the top of a building, then continue to lower levels.
- Soak the glass surface in a clean soapy solution before cleaning.
- Use a mild non abrasive commercial cleaner.
- Use a squeegee to remove all cleaning solution.
- Try your procedures on a small window and check.
- Caution other trades re the care and protection of the glass surfaces.

**Residues of surface grit may be present from the toughening production process.  
These grit particles must not be dragged across the surface.  
NEVER use Metal Scrapers**

All above reprinted with permission from Metro Glass Tech

All pages © Copyright Juralco Aluminium Building Products Ltd, 2022