

**Resene Paints Limited**

32-50 Vogel Street  
Naenae  
Wellington  
P O Box 38242  
Wellington Mail Centre  
NEW ZEALAND

Telephone: (64) (4) 577 0500  
Fax: (64) (4) 577 0600  
e-mail: advice@resene.co.nz  
Emergency Phone: NZ 0800 737363  
Emergency Phone: Aust. 1800 738383

**MATERIAL SAFETY DATA SHEET**

Version Number: 7  
Date Issued: 30/09/2005

**IDENTIFICATION**

Product Name: LUMBERSIDER  
Other Names: Wintergrade Lumbersider  
Proper Shipping Name Waterbased paint  
Uses: General purpose waterborne acrylic semigloss paint  
U N Number: Not Specified  
Dangerous Goods Class: Not Restricted  
Hazchem Code: Not Specified  
Toxic Substances Schedule: Not Restricted  
Packing Code: N.O.S.  
Classification of Hazardous Nature:  
Non Hazardous according to NZ Dangerous Goods and Toxic  
Substance Regulations.

**Physical Description/Properties**

Appearance-Viscosity-Odour-pH: Viscous liquid, white/coloured. Mild ammoniacal odour. pH 7 to 10  
Melting or Freezing Point: 0°C  
Boiling Point: 100°C (Variable)  
Vapour Pressure (mm Hg @ 25 C): Greater than 17 at 20°C  
Vapour Density (Air=1): Greater than 1  
Solubility in Water (g/L @20 C): Dilutable  
Percent Volatile (by weight): 42  
Specific Gravity (Water=1): 1.4  
Evaporation Rate (Butyl Acetate=1): Less than 1

**INGREDIENTS**

	<b>CAS Reg. No.</b>	<b>Approx. Proportion</b>	<b>WES - TWA</b>
Polymer	Not known	Med 10-60%	None Established +
Titanium Dioxide*	13463-67-7	Med 10-60%	10 mg/m <sup>3</sup> +
Water	7732-18-5	Med 10-60%	None Established +
Alcohol Solvents	Mixture	Low 0-10%	None Established +
Inorganic/Organic Pigments*	Mixture	Low 0-10%	None Established +
Ammonia	7664-41-7	Trace	25 ppm +

\* Proportions/Type vary with colour  
+ NZ OSH (WES) 2002

**HEALTH HAZARD INFORMATION**

**Health Effects:-**

**Skin:** Irritating to skin upon repeated or prolonged contact.

**Eyes:** Moderately irritating to eyes.

**Inhaled:** Vapour or mist is irritating to mucous membranes and respiratory system. Excessive inhalation can cause headache, nausea, dizziness, or asphyxiation.

**Swallowed:** Can be harmful if swallowed.

**Long Term Hazard:** None anticipated with this product.

**First Aid:-**

**Skin:** Wash affected area thoroughly with soap and water.

**Eyes:** Flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

**Inhaled:** Provide fresh air; give oxygen or artificial respiration if breathing laboured.

**Swallowed:** If swallowed dilute by giving two glasses of water to drink. DO NOT induce vomiting. Consult Physician or New Zealand National Poisons Centre (Ph 0800 764 766) Australian National Poisons Centre (Ph 1800 131 126) IMMEDIATELY. Never give anything by mouth to an unconscious person.

**Advice to Doctor:** Treat symptomatically.

---

### PRECAUTIONS FOR USE

**Personal Protection:-**

**Skin:** Protective clothing. Gloves of neoprene, nitrile rubber or PVC -Industrial weight lined gauntlet recommended

**Eyes:** Safety eyewear with splash guards or side shields to prevent eye contact

**Breathing:** SPRAY: Half facepiece, class P1 particulate filter.

**Other:**

**Ventilation:** Sufficient ventilation, in volume and pattern, should be provided to keep air contaminant concentrations below WES - TWA limits.

---

### SAFE HANDLING INFORMATION

**Storage and Transport:-**

Storage Maximum: 40°C. Store cool at constant temperature.

Temperature: Minimum: 1°C

**Container Type and Material:** Lacquer lined steel tins or polypropylene pails.

**Incompatible Substances:** Strong oxidizers, acids, alkalis.

**Conditions to Avoid:** Freezing, excessive heat and changes in temperature.

**Hazardous Polymerisation:** Will not occur.

**Usual Decomposition Products** Oxides of Carbon and Nitrogen.

**Spills:** Keep spectators away and avoid breathing vapours or dust. Floor may be slippery: use care to avoid falling. Dike and contain spill with inert materials (eg sand). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

**Disposal:** Incinerate the liquid and contaminated diking material at a permitted facility, or otherwise dispose of in accordance with all applicable regulations.

**Fire/Explosion Hazard:** Flash Point: >100°C

Auto Ignition Temperature: Not known

Upper Explosion Limit %: Not known

Lower Explosion Limit %: Not known

**Extinguishing Media:** Foam, Carbon Dioxide, Dry Chemical, Water.

**Special Fire Fighting Procedures:**

NOTE: Material can splatter above 100°C. Polymer film can burn.

**Other Information:**

Note: Titanium Dioxide, pigments and fillers when formulated as above, do not pose dust hazards unless sanding or grinding of the dry coating takes place. The WES (TWA) values are those for nuisance dusts. N.O.S. - NOT OTHERWISE SPECIFIED

**Contact Point: New Zealand Telephone 0800 737363 Australia Telephone 1800 738383 (24 hour)**

It is Company Policy to maintain the most accurate and up to date information possible, and Resene Paints Limited aims to review these Data regularly. The information contained herein is based on data considered accurate and reliable to the best of our knowledge as of the date issued and subsequently made available from Resene Paints Limited. However, no warranty is expressed or implied regarding the accuracy of these Data or the results to be obtained from the use hereof. Persons using these Data are urged by Resene Paints Limited to satisfy themselves that these Data are the latest available from Resene Paints Limited and remain current and suitable for particular applications after intervening periods of time. Resene Paints Limited assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such users or vendees assume all risks associated with the use of the material.