

# SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** WOODSMAN WOOD OIL STAIN  
**Other Names:** previous name Woodsman  
**Recommended Use:** Oil based sealer  
**Company Name:** Resene Paints Limited New Zealand **Address:** 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND  
 P O Box 38242, Wellington Mail Centre  
**Phone:** (04) 577 0500 Fax: (04) 577 0600  
 Resene Paints Limited Australia **Address:** 7 Production Avenue, Molendinar, Queensland 4214  
 P O Box 785, Ashmore City, Queensland 4214  
**Phone:** 1800 738 383 AUSTRALIA

### Emergency Telephone:

**New Zealand** 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

**New Zealand Poisons Centre: 0800 764 766**

**Australia** 1800 738 383

**Australian Poisons Centre: 131 126**

## SECTION 2. HAZARDS IDENTIFICATION

**Hazard Classification** HAZARDOUS according to NZ HSNO Regulations  
 Not Regulated under NZS5433 for land transportation

**Risk Phrases** Not assigned

**Safety Phrases** Not assigned

**Substance Classification** 3.1C 6.1E 6.3B 6.4A 6.5B 6.8B 6.9B 9.1B

**Hazard Statements** Flammable liquid and vapour  
 May be harmful if swallowed  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 Suspected of damaging fertility or the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.  
 Toxic to aquatic life with long lasting effects

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredients                                    | %       | CAS No     | TWA                        |                   |
|------------------------------------------------|---------|------------|----------------------------|-------------------|
| Aromatic Hydrocarbon                           | 30 - 60 | 64742-95-6 | not known                  |                   |
| Dimethyl Glutarate                             | 10 - 30 | 1119-40-0  | 262 mg/m <sup>3</sup> as x | NZ OSH (WES) 2002 |
| 2-Butoxyethanol                                | 1 - 10  | 111-76-2   | 121 mg/m <sup>3</sup>      | NZ OSH (WES) 2002 |
| 2,2,4-trimethyl-1,3-pentanediol monoisobutyr   | 1 - 10  | 25265-77-4 | None Establish             |                   |
| Mineral Turpentine                             | 1 - 10  | Mixture    | 217 mg/m <sup>3</sup> as x | NZ OSH (WES) 2002 |
| Methyl benzene                                 | 1 - 10  | 108-88-3   | 188 mg/m <sup>3</sup>      | NZ OSH (WES) 2002 |
| Methylene bis(thiocyanate)                     | < 1     | 6317-18-6  | None Establish             |                   |
| 2-(thiocyanatomethylthio)benzothiazole         | < 1     | 21564-17-0 | None Establish             |                   |
| 3-iodo-2-propynyl butyl carbamate              | < 1     | 55406-53-6 | None Establish             |                   |
| (2-Benzothiazolylthio)butanedioic acid         | < 1     | 95154-01-1 | None Establish             |                   |
| Ingredients not contributing to classification | 10 - 30 |            |                            |                   |

## SECTION 4. FIRST AID MEASURES

**Eyes** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

**Swallowed:** Immediately call a POISON CENTRE (ph 0800 764766) or Australia (131 126) or a doctor/physician.

**Skin** Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and plenty of soap. If skin irritation occurs get medical advice/attention.

**Inhaled** IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

## Aggravated medical conditions caused by exposure

**Chronic Health Effects** Not Identified

**Advice to Doctor** Treat symptomatically

### SECTION 5. FIRE FIGHTING MEASURES

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

**Hazards from combustion products**

**Special protective precautions and equipment for firefighters**

| Fire/Explosion Hazard       | Auto Ignition Temperature           | Lower Explosion Limit | Upper Explosion Limit |
|-----------------------------|-------------------------------------|-----------------------|-----------------------|
| <b>Hazchem Code</b><br>3[Y] | <b>Flash Point</b><br>250°C<br>31°C | 0.4%                  | 6.0%                  |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

#### Methods and materials for containment and clean up

**Minor Spills** Ventilate area, avoid breathing of vapours.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Remove all ignition sources.

Clean up spills immediately.

**Major Spills** Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

### SECTION 7. HANDLING AND STORAGE

**Precautions for safe handling** Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities

**Storage Temperatures** Min 1°C Max 40°C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**National exposure standards for mixture** None assigned. Refer to individual constituents.

| Component | Breathing Zone ppm | Breathing Zone mg/m <sup>3</sup> |
|-----------|--------------------|----------------------------------|
|-----------|--------------------|----------------------------------|

#### Personal Protection

**Eye:** Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.

**Hands/Feet** Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.

**Other** Use in well ventilated area with explosion proof equipment. When added to other product mixture contains hazards from both components.

Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of heated materials. Wash hands thoroughly before handling food.

**Respirator** Class AUS-1 half face respirator with type A organic filter

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** Clear amber liquid

|                 |    |                 |                |               |             |            |                   |
|-----------------|----|-----------------|----------------|---------------|-------------|------------|-------------------|
| Odour           | pH | Vapour Pressure | Vapour Density | Boiling Point | Melt Freeze | Solubility | Volatile by Weigh |
| Hydrocarbon n/a |    | 3.3kPa          | 4.3            | 145°C         | -40°C       | Insoluble  | 82                |

## SECTION 10. STABILITY AND ACTIVITY

**Chemical Stability** Product is considered stable under normal storage and handling conditions.

**Conditions to Avoid** Avoid freezing, excessive heat and changes in temperature

**Incompatible Materials** Avoid storing with strong oxidizers, acids, alkalis

**Hazardous decomposition product** Oxides of carbon and nitrogen

**Hazardous reactions** Hazardous polymerisation will not occur.

**SECTION 11. TOXICOLOGICAL INFORMATION**

No data available for this product

|           |                |                  |                |
|-----------|----------------|------------------|----------------|
| Component | Oral:LD50 mg/k | Dermal:LD50 mg/k | Inhale:LC50 pp |
|-----------|----------------|------------------|----------------|

**SECTION 12. HAZARDS IDENTIFICATION**

Do not allow the product to enter the environment

No data available for this product

|           |                 |              |
|-----------|-----------------|--------------|
| Component | Fish:LC50 mg/Lt | BCF:<100 Kow |
|-----------|-----------------|--------------|

**SECTION 13. DISPOSAL CONSIDERATIONS**

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

**SECTION 14. TRANSPORT INFORMATION**

Transport only in accordance with the following regulations

|                      |                       |
|----------------------|-----------------------|
| UN Number            | 1263                  |
| Proper Shipping Name | Paint related product |
| Subsidiary Risk      |                       |
| Poison Schedule      |                       |
| Packing Group:       | III                   |
| Class                | 3 Flammable liquid    |
| HAZCHEM Code         | 3[Y]                  |

**Special precautions for user****SECTION 15. REGULATORY INFORMATION**

Group Standard HSR002662 Surface Coatings &amp; Colourants (Flammable)

Approved Handler Not required

**SECTION 16. OTHER INFORMATION**

|                       |                                    |
|-----------------------|------------------------------------|
| Date of Preparation   | 31/10/2011                         |
| Literature references | MSDS's for individual raw material |

**Abbreviations:**

|                  |                                                    |
|------------------|----------------------------------------------------|
| NOHSC            | National Occupational Health and Safety Commission |
| TWA              | Time weighted average                              |
| STEL             | Short term exposure limit                          |
| CAS Number       | Chemical Abstract Service registry number          |
| TLV              | Threshold limit value                              |
| Marine Pollutant | Marine Pollutant <input type="checkbox"/>          |

**Safety data sheets are updated frequently. Please ensure that you have a current copy**

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.