

Hydro™

Bituminous Flashing Tape

CodeMark

CMNZ70075



Hydro Roll



Corner Guards



A bituminous flashing tape to seal around windows, doors and other joinery openings as a secondary defence against water penetration.

APPLICATIONS

- Suitable for timber and steel framed buildings
- Simple to instal saving time and reducing costs
- Reliable and dependable weather tightness
- Works in temperatures from 5°C
- An optional Masons Corner Guard is easy to install and increases protection to framing

NB: Masons Hydro Flashing Tape (and Corner Guards) must be installed in accordance with the instructions outlined on our website.

NEW ZEALAND BUILDING CODE STANDARD (NZBC)

The following tests have been carried out in accordance with NZBC Acceptable Solution E2/AS1 Table 23:

Codemark. Check mpb.co.nz or the MBIE Codemark Certificate for valid Certification	Pass
A risk score between 0-20 in accordance with NZBC Acceptable Solution E2/AS1	Pass
NZS3604 Building Wind Zones up to and including 'Extra High'	Pass

PHYSICAL PROPERTIES

Hydro Flashing Tape is compatible with most building wraps.

Warning: Don't apply any solvent based glues or adhesives/sealants to the tape as it will react with the bitumen.

Note: 150mm wide tape is used for 90mm wide window or door framing. 200mm wide tape is used for 140mm-150mm wide revels.

Description	Roll Size	Masons Code
Hydro flashing tape 75mm	H 75mm x L 25m	HYDRO75x25
Hydro flashing tape 100mm	H 100mm x L 25m	HYDRO100x25
Hydro flashing tape 150mm	H 150mm x L 25m	HYDRO150x25
Hydro flashing tape 150mm	H 150mm x L 10m	HYDRO150x10
Hydro flashing tape 200mm	H 200mm x L 25m	HYDRO200x25
Masons corner guards	pack of 10	HYDRO10CNRGUARD
Masons corner guards	pack of 50	HYDROCG50