

Dulux Professional Tintable Ceiling Flat

NZDD0863

Part A	615-84179
Approvals	APAS-0260/5, Environmental Choice Certified.






Description
Previously known as DULUX PROFESSIONAL UltraHide Tintable Ceiling Pnt DULUX PROFESSIONAL Ultrahide tintable ceiling paint is a water based 100% acrylic interior flat designed especially for ceilings

Features
<ul style="list-style-type: none"> Water based Very flat finish 100% acrylic

Benefits
<ul style="list-style-type: none"> Same day recoat, easy clean up and low odour. Hides surface imperfections, smooth, even finish Tough washable finish, can be used on walls.

Uses
Use DULUX PROFESSIONAL UltraHide tintable ceiling paint on all ceilings where a very flat finish is required.

Performance Guide			
Weather	Not suitable for exterior use.	Heat Resistance	Up to 70C.
Water	Resists light washing and water splash.	Solvent	Sensitive to alcohols, aromatic hydrocarbons and ketones.
Abrasion	Moderate resistance to abrasion.		

Typical Properties																											
Gloss Level	0-3 at 60 degrees.	Thinner	Water																								
Colour	Can be machine tinted to a comprehensive pastel and medium dark colour range.	Components	1																								
Number Of Coats	2	Toxicity	Lead free. Dry film is non-toxic.																								
V.O.C. Level	33 g/L	Touch Dry	20 Minutes																								
Clean Up	 Water																										
Clean Up Description	Clean all equipment with water.																										
Application Method	    Air Spray Airless Spray Brush Roller																										
Application Conditions	<table border="0"> <tr> <td>Solids By Volume</td> <td>32</td> <td></td> <td></td> </tr> <tr> <td></td> <td>Min</td> <td>Max</td> <td>Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td>63</td> <td>63</td> <td>78</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>20</td> <td>20</td> <td>25</td> </tr> <tr> <td>Recoat Time (min)</td> <td>2 Hours</td> <td>Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td>16</td> <td>16</td> <td>12.8</td> </tr> </table>			Solids By Volume	32				Min	Max	Recommended	Wet Film Per Coat (microns)	63	63	78	Dry Film Per Coat (microns)	20	20	25	Recoat Time (min)	2 Hours	Indefinite		Theoretical Spread Rate (m²/L)	16	16	12.8
Solids By Volume	32																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	63	63	78																								
Dry Film Per Coat (microns)	20	20	25																								
Recoat Time (min)	2 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	16	16	12.8																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply primer, sealer or undercoat as required.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, roller, conventional or airless spray. Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. <p>Brush/Roller: Rinse brush or roller in water before starting and use while still slightly damp. Apply full even coats direct from the container. Under hot conditions or on very absorbent surfaces, up to 100ml clean water may be added per litre to assist application.</p> <p>Airless/Conventional Spray: Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.</p>

Health And Safety			
MSDS Number	14550927, 0	Using Safety Precautions	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Sales and Customer Service offices.
Health Effects	Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.	Protective Equipment	Wear eye protection and when spraying wear a suitable mask.
Disposal	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
Do not paint at temperatures below 10C or when the temperature of surface may fall below 10C during the drying period.

Transport And Storage			
Pack A	615-84179	Shipment Name	Not dangerous goods.; No special transport requirements.
Size	4 Litre 10 Litre	Weight	5.9 Kg 14.6 Kg
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118