

XRV™

Insulated Panel System

XRV™ Insulated Panel has a crack resistant exterior plaster cladding system that provides a fully drained and ventilated weatherproof barrier for residential and commercial construction.











40 mm or 60 mm XRV™ Insulated panel



Masons 150 gsm Fibreglass Mesh

embedded in 3 mm Masons Meshing Render



Masons skimming render coat (optional)



Masons selected finishing coat



Masons Limestop Sealer



2 coats Masons Premium Build Highbuild Exterior Acrylic Paint





Developed specifically to meet the harsh requirements of New Zealand's coastal environment, the cavity behind XRV™ Insulated Panel provides an additional safeguard to ensure any moisture that may penetrate the exterior envelope is able to escape unimpeded.

Lightweight Advantages

The XRV™ Insulated Panel System is extremely lightweight (approximately 7 kg per m²) it is well suited to pole structures or areas with poor quality soils and foundations. This characteristic can also reduce the cost of supporting structural elements such as beams and columns. It also does not require a base footing of concrete in order to support its own weight, which can save money on foundation work.

To ensure there is a well-defined chain of accountability, the installation of the XRV™ Insulated Panel system, including the construction of the 20 mm cavity, can only be undertaken by licensed Masons installer.







For total security, use our non-crack plaster, Masons FLX^{TM} to ensure that your building is kept absolutely watertight.







WATER PROOF







XRV™ with render

XRV™ with FLX render