



METALCRAFT FASCIA

PURPOSE

Metalcraft Roofing supplies Metalcraft Fascia for use on eave and gable lines in conjunction with guttering as part of a roof drainage system.

EXPLANATION

Metalcraft Fascia are fabricated from pre-coated steel supplied by NZ Steel. The protective coatings are designed to withstand NZ's exposure zones. Design and installation information is supplied by Metalcraft Roofing. Metalcraft Fascia are available in the 135 mm, 155 mm and 185 mm. They are manufactured from the following NZ Steel branded products:

- > Zincalume®
- > Colorsteel® Endura®
- > Colorsteel® Maxx®.





SCOPE AND LIMITATIONS OF USE

Scope	Limitations
Location	
In any wind zone or calculated design load.	
In all exposure zones defined in NZS 3604:2011.	➤ In exposure Zone D only Colorsteel® Endura® or Colorsteel® Maxx® may be used.
	➤ For use in microclimatic considerations (as defined in paragraph 4.2.4) refer to Metalcraft Rooting for technical advice.
On buildings any proximity to a relevant boundary.	➤ Eaves within 650mm of the relevant boundary must be fully fire rated.
Building	
In conjunction with a primary structure and roof cladding system that complies with the NZ Building Code or where the designer has established that the existing structure is suitable for the intended building work.	

NZ STEEL ASSURANCE

As the manufacturer of the steel, from which Metalcraft Fascia are fabricated, NZ Steel provides assurance that the steel:

- has been manufactured in accordance with AS 1397:2001
- ➤ is coated in accordance with AS/NZS 2728:2013 or galvanised in accordance with AS/NZS 2312.2:2014.

NZ Steel has established an Environmental Management System certified to ISO 14001. For more information on the specific exposure zones and environmental impacts of the product refer to www.colorsteel.co.nz.



VERSION:



PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all Metalcraft Roofing requirements, the Metalcraft Fascia will comply with or contribute to compliance with the following performance claims:

NZ Building	BASIS OF COMPLIANCE ¹	
Code clauses	Compliance statement	Demonstrated by
B1 Structure B1.3.1 B1.3.2 B1.3.3 (a, b, c, j)	ACCEPTABLE SOLUTION B1/AS1	➤ Manufactured in accordance with AS/NZS 1397:2011.
B2 Durability B2.3.1 (a)	ACCEPTABLE SOLUTION B2/AS1	➤ Coated in accordance with AS/NZS 2728:2013 (cited in E2/AS1).
C3 Fire Affecting Areas Beyond the Fire Source	ACCEPTABLE SOLUTION C/AS1	➤ Steel is non-combustible (refer paragraph 5.8 C/AS2 1st edition June 2019).
C3.4 (a) C/AS2 1 st edition June 2019 C3.7 (a)	C/AS2 1 st edition June 2019	➤ Tested to ISO 5660 BRANZ (FH 6102-TT, dated 3/1/2017) (Material Group 1-S).
	➤ BRANZ is accredited to perform ISO5660 test.	
E2 External Moisture E2.3.1 E2.3.2 E2.3.7 (a, b, c)	ACCEPTABLE SOLUTION E2/AS1	➤ In accordance with NZ Metal Roof Manufacturer's (NZMRM): Code of Practice (v3.0).
F2 Hazardous Building Materials F2.3.1	ALTERNATIVE SOLUTION	 Coating systems are inert once dry. Colorsteel® safety data sheets.

^{1.} The Compliance Statement is the pass holder's statement that they have met their obligations under s14G(2) of the Building Act 2004.

SOURCES OF INFORMATION

- > AS/NZS 3604:2011. Timber framed buildings.
- ➤ AS/NZS 1397:2001. Steel sheet and strip Hot-dip zinc coated or aluminium/zinc coated.
- ➤ BRANZ http://www.level.org.nz/water/water-supply/mains-or-rainwater/harvesting-rainwater/
- > NZ Metal Roof Manufacturer's (NZMRM): Code of Practice (v3.0).
- ➤ NZ Steel Technical Bulletin (August 2016). Fire Testing of Coated Steel Product.



VERSION: DATE:

Note: Uncontrolled in printed format.

NAME: Frances Charles

POSITION: National Sales & Marketing Mgr

Signed on behalf of Metalcraft Roofing:

By signing this pass™ the signatory confirms that, in respect of the subject of this pass™, the company has met their s14G obligations under the Building Act 2004.

