MAINTENANCE RECOMMENDATIONS



MAINTENANCE

All roofing and cladding products are subject to the cumulative effects of weather, dust and other deposits. Normal rain washing will remove most accumulated atmospheric contaminants from roofs. For wall cladding, manual washing every 3 to 12 months, depending on the paint system, is recommended in moderate to very severe environments to prevent accumulation of dirt, debris or other material not removed by rain washing. For areas that do not receive any or adequate rain washing (called unwashed areas) such as soffits, wall cladding under eaves, underside of gutters, fascias, sheltered areas of garage doors and unwashed roof areas, more extensive manual washing is required. Similarly, other High Risk areas, around flues, under television aerials or overhanging trees and sites prone to mould, lichen, bird droppings or debris, need to have regular manual washing.

Regular washing of COLORSTEEL® prepainted steel products increases the durability by reducing attack from airborne salts and pollutants. GALVSTEEL™ products and ZINCALUME® steel products will also benefit from routine washing.

Roofing and cladding products should be manually washed with water and a sponge or a soft nylon-bristled brush. For large areas it may be more appropriate to use water blasting at pressures up to 20Mpa.

If New Zealand Steel Limited products are maintained according to the following recommendations, the requirements of the New Zealand Building Code B2 for 15 year durability for roofs and exterior walls will be met or exceeded.

Note:

- 1. The New Zealand Building Code durability requirement does not include aesthetic appearance.
- 2. The New Zealand Building Code requires a durability of 15 years minimum (with maintenance) for non structural roofing, including valleys, and wall cladding products. This means no moisture penetration due to product failure.
- 3. New Zealand Steel Limited products are designed to exceed the New Zealand Building Code B2: durability requirements. Continued maintenance and overpainting will greatly extend the ultimate life of all products.
- 4. Where a 50 year durability is required **OR** where a product is to be used in aggressive internal environments, New Zealand Steel Limited should be consulted.
- 5. In Industrial Environments, the type of pollution generated may alter the above recommendations. If in doubt, consult New Zealand Steel Limited. The Maintenance Table, on the reverse, is for guidance only. Each proprietary building product should carry its own manufacturers' recommendations for usage.
- 6. New Zealand Steel Limited will not accept responsibility for proprietary roofing and cladding products which do not conform to our recommendations for manufacturing, environmental use or maintenance.







MINIMUM MAINTENANCE RECOMMENDATIONS FOR NEW ZEALAND STEEL PRODUCTS USED FOR ROOFING AND WALL CLADDING.

		Moderate	Severe	Very Severe
COLOUR FOR THE EXTREME	Roof Wall Cladding	Rain washing Rain washing plus manual washing every year	Rain washing Rain washing plus manual washing every 6 months	Rain washing Rain washing plus manua washing every 3 months
	Unwashed and High Risk Areas	Manual washing every 6 months	Manual washing every 3 months	Manual washing every month
COLOUR FOR THE FUTURE	Roof Wall Cladding	Rain washing Rain washing plus manual washing every year	Rain washing Rain washing plus manual washing every 6 months	Not recommended Not recommended
	Unwashed and High Risk Areas	Manual washing every 6 months	Manual washing every 3 months	Not recommended
Zincalume®	Roof Wall Cladding	Rain washing	Not recommended Not recommended	Not recommended Not recommended
	wan Cladding	Rain washing plus manual washing every 6 months	Not recommended	Not recommended
	Unwashed and High Risk Areas	Manual washing every 3 months	Not recommended	Not recommended
<i>GALVSTEEL</i> ™	Roof	Rain washing	Not recommended	Not recommended
	Wall Cladding	Rain washing plus manual washing every 6 months. Painting may be advisable depending on the specific location	Not recommended	Not recommended
	Unwashed and High Risk Areas	Manual washing every 3 months. Painting may be advisable depending on the specific location	Not recommended	Not recommended

Note: Recommendations provided in this table apply to the standard provisions of the New Zealand Building Code, Section B2 Durability.

FURTHER INFORMATION

For additional information, literature or technical assistance, please contact:

Roofing and Cladding Sector New Zealand Steel Limited Private Bag 92 121, Auckland Telephone: 0-9-375 8999

Facsimile: 0-9-375 8213 Free Phone: 0800 100 523

Email Address: info@colorsteel.co.nz

http://www.colorsteel.co.nz



ZINCALUME® is a registered trademark.



GALVSTEEL™ is a trademark of New Zealand Steel Limited.



COLOUR FOR THE EXTREME

MAXX™ is a trademark of New Zealand Steel Limited.



COLOUR FOR THE FUTURE

ENDURA™ is a trademark of New Zealand Steel Limited.



COLORSTEEL® is a registered trademark of New Zealand Steel Limited.

THE ROOF OF NEW ZEALAND®

is a registered trademark of New Zealand Steel Limited.

NOTE: With New Zealand Steel Limited's commitment to continuous improvement, information provided in this publication may be subject to modification. At the time of publication we believe the information contained in this document is the best available. Nonetheless, we reserve the right to modify any product, technique, equipment or statement to reflect improvements in the manufacture and application of coil coated products.

The information is supplied without prejudice to New Zealand Steel Limited's standard terms and conditions of sale. In the event of any conflict between this information and the standard terms and conditions, the standard terms and conditions shall prevail.

Copyright@ 2003 New Zealand Steel Limited.





