

# COMFLEX PREMIUM

## FLEXIBLE DUCTING

Diameter (mm)	Length (m)	NUDE	INSULATED R.06
		Order Code	Order Code
100	3	DCT0215	DCT0452
	6	DCT0104	
125	3	DCT0216	
	6	DCT0160	
150	3	DCT0217	DCT0427
	6	DCT0107	DCT0428
200	3	DCT0218	DCT0429
	6	DCT0109	DCT0430
250	3	DCT0219	DCT0431
	6	DCT0421	DCT0432
300	3	DCT0111	DCT0433
	6	DCT0422	DCT0434
350	3	DCT0112	DCT0435
	6	DCT0423	DCT0436
400	3	DCT0113	DCT0437
	6	DCT0424	DCT0438



Nude



Insulated R0.6 (40mm)

- **Complies to AS1530 PT3 and relevant clauses of the NZ building code.**
- Material Group Number of 1 or 1S as per NZBC.
- **DUCT CORE:** Polyester film core with aluminium foil laminated onto both sides.
- This composite film is then permanently bonded onto a corrosion resistant coated, spring steel wire helix.
- **DUCT SLEEVE:** Fire retardant 75µm black low density polyethylene and UV stabilised.
- **DUCT INSULATION:** Polyester R0.6 nominal.
- **TEMPERATURE RANGE:** Nude Core - Maximum: +150°C, Minimum: -30°C.
- **COLOUR:** Silver with black sleeve.

### Note

1. No glued/adhesive duct should be installed in a compressed or ovalised state for fear of long term failure.