

# Resene Emulsifiable Solvent Cleaner

oil and grease  
remover

Resene Emulsifiable Solvent Cleaner is a blend of solvents specifically designed to dissolve oil and greasy residues on surfaces prior to painting. May be rinsed with clean water to produce a totally grease-free surface. Used prior to steam cleaning it is the best pre-treatment of smoke damaged surfaces.

## exterior/interior

### Typical uses

- All grease or smoke contaminated surfaces

### Physical properties

<b>Type</b>	Hydrocarbon solvent
<b>Form</b>	Water thin liquid
<b>Colour</b>	Colourless
<b>Toxicity</b>	Poison
<b>Mixing ratio</b>	Do not dilute
<b>Theoretical coverage</b>	Dependent on surface porosity and degree of contamination
<b>VOC</b>	725 grams per litre (see <a href="#">Resene VOC Summary</a> )

### Performance and limitations

- Performance**
1. Excellent solvent for removing grease and oils.
  2. Rinses clean with water.

**Limitations** -

# Emulsifiable Solvent Cleaner oil/grease remover

## Surface preparation

No special preparation necessary.

## Application

Apply by stiff bristle scrubbing brush or broom. Rinse with steamcleaning or waterblasting equipment. Wear safety glasses with sideshields, protective clothing and gloves (neoprene or butyl rubber).

1. Apply heavily to the area to be degreased.
2. Allow a contact time of 5-15 minutes. Cleaning is aided by scrubbing the surface, especially if the surface is pitted.
3. Rinse by steamcleaning, waterblasting or by hose and scrubbing.
4. If oil and grease deposits remain, repeat the above procedure.
5. Allow degreased surface to dry thoroughly if painting.

## Precautions

1. This material may be harmful if swallowed, inhaled or absorbed through the skin, and may cause skin or eye irritation.
2. Avoid breathing vapour - use with adequate ventilation.
3. If swallowed give water to dilute. Do not induce vomiting.
4. If eyes become contaminated, flood with running water for at least 15 minutes. SEEK MEDICAL AID.
5. If any skin contact occurs, wash skin thoroughly with soap and water. Do not scrub the skin.
6. FLAMMABLE - Keep away from heat and open flame. Keep closed when not in use.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.  
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

**In Australia**  
PO Box 785, Ashmore City, Queensland 4214  
Call 1800 738 383, visit [www.resene.com.au](http://www.resene.com.au)  
or email [advice@resene.com.au](mailto:advice@resene.com.au)

**Resene**  
the paint the professionals use

**In New Zealand**  
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Call 0800 RESENE (737 363), visit [www.resene.co.nz](http://www.resene.co.nz)  
or email [advice@resene.co.nz](mailto:advice@resene.co.nz)