



## 15MM HERRINGBONE SPECIFICATION SHEET

Atelier Collection Engineered T&G herringbone by Forté. 15mm thick, 120mm wide, 600mm length. Glue down installation method onto substrate. Pre-finished with UV Cured Matte Lacquer.

### PRODUCT DETAILS


|                 |  |
|-----------------|--|
| Collection      | Atelier  |
| Product Type    | Engineered Herringbone   |
| Availability    | Stocked  |
| Total Thickness | 15mm   |
| Width           | 120mm  |
| Length          | 600mm  |
| Wear Layer      | 4mm Solid European Oak   |
| Core            | Birch Plywood  |
| Construction    | 2-layer Engineered   |
| Re-sands        | Up to 2 (approx. 1mm removed per re-sand)                            |
| Surface Texture | Brushed  |
| Surface Sheen   | Matte  |
| Bevel           | Bevel 4-sides  |
| Status          | Pre-finished<br>(no additional coats required)                       |
| Finish          | Ageing Stain with UV Cured Matte<br>Lacquer                          |
| Species         | European Oak   |
| Wood Grade      | Rustic (refer page 2 for details)                                    |
| Filler Colour   | Dependant on colour, visit<br>forte.co.nz for accurate filler colour |

The Atelier Collection is also available in planks and stair nosings.


### STRUCTURAL WARRANTY

|                     |  |
|---------------------|--|
| 5 Year Commercial   | For terms and conditions see   |
| 25 Year Residential | <a href="http://www.forte.co.nz/warranties">www.forte.co.nz/warranties</a> |


Images are colour representation only




Dolomite



Siltstone



Classic



Marl



Granite

### SUSTAINABILITY

#### Sustainably Sourced

### INSTALLATION

|                       |  |
|-----------------------|--|
| Installation Method   | Glue down<br>(Double Stick for Multi-level)  |
| Suitable Substrates   | Plywood, Particle Board, Concrete,<br>existing timber - enquire for others   |
| Joint Profile         | Tongue and Groove (4 sides)  |
| Suitable Applications | Flooring, Walls, Ceilings  |
| Suitable Uses         | Residential homes, hospitality, retail<br>stores, restaurants, apartments  |
| Underfloor Heating    | • Hydronic Systems<br>• Electric Systems set in screed<br>(Ensure screed is suitable for UFH)<br>• Enquire for other systems |
| Wet Area Suitability  | Contact the Forté team for information<br>0508 35 66 77  |

### TECHNICAL SPECIFICATIONS

|                                       |  |
|---------------------------------------|--|
| Reaction to Fire (Floors)             | Critical Flux 2.2kw/m <sup>2</sup>   |
| Reaction to Fire (Walls and Ceilings) | Group 3 / Class Dfl-s1 (Group 1 can<br>be achieved with intumescent coating) |
| <u>Formaldehyde Emission</u>          |  |
| AS/NZS 2098.11                        | E0 (0.13 mg/L)<br>Low VOC, No added Formaldehyde                             |
| Wear Layer Density                    | 650kg/m <sup>3</sup>   |
| <u>Slip Ratings</u>                   |  |
| AS/NZS 4586 Wet Test                  | Classification F, Mean COF 0.85  |
| AS/NZS 4586 Dry Test                  | Classification X, Pendulum Mean 42<br>BPN                                    |

### PACK INFORMATION

|                 |                           |
|-----------------|---------------------------|
| Pack Size       | 0.864m <sup>2</sup>       |
| Pack Weight     | 9kg                       |
| Pieces per pack | 12 (6 x right + 6 x left) |

# Plank Profile

## ATELIER HERRINGBONE

---

Image Coming Soon

## ATELIER – RUSTIC GRADE

---



Grade Representation only

An Atelier rustic grade plank will typically contain unlimited natural colour variation. This grade allows for more frequent, larger knots and more sapwood should be expected throughout the planks. Cracks and checks will be present and are finished with filler.

# Care and Maintenance

## RESIDENTIAL AND COMMERCIAL CARE AND MAINTENANCE

---

Forté's Product Specialists have collated our care and maintenance recommendations to ensure your flooring looks like new for years to come. Residential and Commercial projects require different levels of care and maintenance. Visit [www.forte.co.nz/careandmaintenance](http://www.forte.co.nz/careandmaintenance)

# Structural Warranty

## ATELIER 25 YEAR RESIDENTIAL STRUCTURAL WARRANTY

---

The Atelier Collection comes with a full 25 year Residential Structural Warranty. For full warranty terms and conditions, please visit [www.forte.co.nz/warranties](http://www.forte.co.nz/warranties)

## ATELIER 5 YEAR COMMERCIAL STRUCTURAL WARRANTY

---

The Atelier Collection comes with a full 5 year Commercial Structural Warranty. For full warranty terms and conditions, please visit [www.forte.co.nz/warranties](http://www.forte.co.nz/warranties)

# Installation

## THE ATELIER COLLECTION MUST BE INSTALLED BY A TRAINED PROFESSIONAL

---

Please ensure that you have read and understood the installation guidelines before proceeding to install Atelier timber flooring. If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty.

For full installation guidelines, please visit [www.forte.co.nz/installation](http://www.forte.co.nz/installation)