

ACOUSTIFOAM

- Closed cell foam backing sheet with impact sound reduction properties

SPECIFICATION



TOTAL THICKNESS
2.0mm



ROLL SIZE
2m x 20m = 40m²



TOTAL WEIGHT
680g/m²



REACTION TO FIRE
Classic Mystique PUR + Acoustifoam,
Mystique PUR + Acoustifoam,
XL PU + Acoustifoam:
ASTM E648 Class 1
EN 13501-1 Class Bfl-S1
EN ISO 9239-1 >8kw/m²
EN ISO 11925-2 Pass



ACOUSTICAL IMPACT NOISE REDUCTION
EN ISO 140-8
ISO 717/2 2mm Polyflor Vinyl + Acoustifoam: 18dB



APPLICATIONS
Acoustifoam may be combined with 2mm sheet vinyl to achieve impact sound reduction of 18dB. This combination is suitable for use in hospitals, schools, offices, retirement and nursing homes, high rise buildings and other locations where noise reduction is required. Acoustifoam is also suitable for use with SaarFloor 2mm sheet rubber.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



2006

POLYFLOR
ACOUSTIFOAM

PERFORMANCE AND
PROPERTIES

POLYFLOR
COVERING THE WORLD