

## IBS HIGH-DENSITY HARDBOARD

### PURPOSE

IBS supplies four variations of IBS high-density hardboard for internal use as follows:

*Standard:*

- where a flat, paintable surface is required
- as a wall substrate for vinyl and flexible surface finishes
- in general DIY projects
- in applications such as partitioning, internal doors, and wall panelling and cupboards
- in furniture making.

*Pegboard:*

- in general DIY projects
- in workshops or garages to store tools.

*Tempered:*

- as a wall substrate to accept a waterproof membrane
- for door and partition surfaces.
- for building uses such as furniture making, automotive industry, pallet making.

*Flooring underlay:*

- as a flooring underlay where a flat, uniform floor finish is required and the existing flooring substrate is damaged or has surface imperfections or, where a water-resistant slip layer is required.



For further assistance please contact:

- ☎ 0800 367 759
- ✉ info@ibs.co.nz
- 🌐 www.ibs.co.nz



### EXPLANATION

IBS high-density hardboard is an impact resistant, high-density hardboard manufactured from FSC certified Eucalyptus. Wood fibres are mixed with water and subjected to heat and pressure to create a hardboard that meets the performance characteristics of AS 2458. It is available in standard, tempered, pegboard and flooring underlay variations.

The tempering process involves applying a thin film of linseed oil and then baking the panel to improve the moisture resistance, rigidity and tensile strength characteristics of the panel.

The general and tempered variations are available in the following sizes (H x W x D, mm):

Standard	Pegboard	Tempered	Flooring underlay
2400 x 1200 x 3.2 2400 x 1200 x 4.8 2440 x 1220 x 6.4	2440 x 1220 x 4.8	2440 x 1220 x 4.8	1220 x 915 x 5

### SCOPE AND LIMITATIONS OF USE

Scope	Limitations
<b>Building</b>	
In conjunction with a substrate that complies with the NZ Building Code or for an existing building, where it is suitable for the intended building work.	➤ The substrate must allow fixing in accordance with the current IBS High-Density Installation and Maintenance Guide.
For internal use in protected areas.	➤ IBS high-density hardboard must not be subject to sustained wetting or high humidity conditions.
For all uses where a high quality, paintable face finish is required.	➤ IBS high-density hardboard must not be used as a structural element, although the product is designed to be self-supporting.
As a flooring underlay.	➤ Only the flooring variation of IBS high-density hardboard may be used.

### OTHER CERTIFICATIONS AND APPROVALS HELD BY BETANZOS HB, S.L.

- BMC. [15/11/2020] ISO 9001:2015 Quality Management Systems. Certificate no. 0171.
- EXOVA BMTRADA [01/2020] FSC STD-40-004 (v3.0) EN, FSC-STD-40-005 (v3.1) EN, FSC-STD-50-001 (v2.0) EN. Certificate nos. TT-COC-004546, TT-CW-004546.
- BMC [17/11/2020] ISO 14001:2015. Environmental Management Systems. Certificate no. 0073.
- EXOVA BMTRADA [08/04/2018] PEFC Certification. Certificate no. PEFC/14-35-00014.

### USEFUL INFORMATION

For information on the use and maintenance of IBS high-density hardboard and for our warranty refer to [www.ibs.co.nz](http://www.ibs.co.nz).

## PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all IBS requirements, the IBS high-density hardboard will comply with or contribute to compliance with the following performance claims:

NZ Building Code clauses	COMPLIANCE STATEMENT	BASIS OF COMPLIANCE <sup>1</sup>
	Compliance statement	Demonstrated by
<b>B1 Structure</b>	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> <li>➤ Manufacturer's technical information confirms the general specifications and physical properties. Product meets EN 324-1/ EN 324-2 (dimensions) EN 323/EN 316 (density), EN 322/EN 622-1 (moisture content), EN 319/EN 622-2 ( internal bond), EN 317/ EN 622-2 (swelling), EN 310/EN 622-2 (bending strength) [Betanzos HB, n.d.a; Betanzos HB, n.d.b].</li> <li>➤ Hydro-tempered variation of the hardboard is CE certified in accordance with EN 13986:2004 [Betanzos HB, n.d.a].</li> <li>➤ Declaration of performance for standard variation of the hardboard by Betanzos HB [Betanzos HB, 25/10/2018].</li> </ul>
<b>B2 Durability</b> B2.3.1(c)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> <li>➤ Manufacturer's technical information confirms the general specifications and physical properties [Betanzos HB, n.d.a; Betanzos HB, n.d.b].</li> <li>➤ Hydro-tempered variation of the hardboard is CE certified in accordance with EN 13986:2004 [Betanzos HB, n.d.a].</li> <li>➤ Declaration of performance for standard variation of the hardboard by Betanzos HB [Betanzos HB, 25/10/2018].</li> </ul>
<b>C3 Fire Affecting Areas Beyond the Source</b> C3.4 (a)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> <li>➤ Achieves material group number 3</li> <li>➤ CE certified in accordance with EN 13986:2004, declaration of performance by Betanzos HB [Betanzos HB, 25/10/2018].</li> </ul>
<b>F2 Hazardous Building Materials</b> F2.3.1	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> <li>➤ CE certified in accordance with EN 13986:2004, declaration of performance by Betanzos HB [Betanzos HB, 25/10/2018].</li> </ul>

1. The Compliance Statement is the pass holder's statement that they have met their obligations under s14G(2) of the Building Act 2004.


## SOURCES OF INFORMATION<sup>2</sup>

- Betanzos HB. [25/10/2018] Declaration of Performance DOP no BHB.01.01. Retrieved from [https://www.betanzoshb.es/wp-content/uploads/2019/01/DoP\\_BHB.pdf](https://www.betanzoshb.es/wp-content/uploads/2019/01/DoP_BHB.pdf). [Accessed 09/03/2021].
- Betanzos HB. [n.d.a] *Technical Data Sheet (Tablex H1 Hydro-tempered)*. Retrieved from <https://www.tablex.eu/wp-content/uploads/2020/10/Technical-data-sheet-Tablex-H1.pdf>. [Accessed 09/03/2021].
- Betanzos HB. [n.d.b] *General Specifications (Tablex Standard ST-A2)*. Retrieved from <https://www.tablex.eu/en/technical-characteristics/>. [Accessed 09/03/2021].
- BMC. [15/11/2020] *ISO 9001:2015 Quality Management Systems*. Certificate no. 0171. Refer <https://www.betanzoshb.es/wp-content/uploads/2020/11/Betanzos-HB-S.L.-QMS-2020-02.pdf>. [Accessed 18/03/2021].
- BMC [17/11/2020] *SIO 14001:2015. Environmental Management Systems*. Certificate no. 0073. Refer <https://www.betanzoshb.es/wp-content/uploads/2020/11/Betanzos-HB-S.L.-EMS-2020-02.pdf>. [Accessed 18/03/2021].
- EXOVA BMTRADA [08/04/2018] *PEFC Certification*. Certificate no. PEFC/14-35-00014. Refer <https://www.betanzoshb.es/wp-content/uploads/2018/06/Betanzos-HB-PEFC-ES.pdf>. [Accessed 18/03/2021].

2. Sources of information also include the Building Act 2004 and its regulations, including the Building Code (Schedule 1 of the Building Regulations 1992), Acceptable Solutions and Verification Methods, and relevant cited standards.

**Scan or click this QR code for a full download of Compliance Documentation for this pass™.**

[www.ibs.co.nz](http://www.ibs.co.nz)



<p><b>NAME:</b> Jason Bardell</p> <hr/> <p><b>POSITION:</b> Managing Director</p> <hr/> <p><b>DATE OF FIRST ISSUE:</b></p> <hr/> <p><b>DATE OF NEXT ASSURANCE:</b></p> <hr/>	<p>Signed on behalf of IBS Building Products:</p>  <p>By signing this pass™ the signatory confirms that, in respect of the subject of this pass™, the company has met their s14G obligations under the Building Act 2004.</p>
--	---



**IBS Building Products, 1/7 Fraser Road, Panmure, Auckland > [info@ibs.co.nz](mailto:info@ibs.co.nz) > 0800 367 759 > [www.ibs.co.nz](http://www.ibs.co.nz)**

This Product Assurance Supplier Statement (pass™) has been prepared by TBB in accordance with MBIE PTS guidelines and the recommendations of s9.2, Determination No. 2019-011 (issued 12 April 2019). TBB is ISO9001:2016 certified. Copyright © 2017, The Building Business Limited (TBB). All rights reserved.