# Safety Data Sheet KERAPOXY comp.A

Safety Data Sheet dated: 09/06/2021 - version 2



# Section 1. Identification of the substance and supplier

#### **Product identifier**

Mixture identification:

Trade name: KERAPOXY comp.A

Trade code: 90459990

#### Recommended use of the chemical and restrictions on use

Recommended use: Acid-resistant epoxy grout and adhesive for ceramic tiles

Uses advised against: Data not available

Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road - Mount Wellington - 1060 - Auckland - New Zealand

enquiries@MBPLtd.co.nz - www.MBPLtd.co.nz

**Emergency phone number** 

New Zealand Poisons Centre: Ph: 0800 764 766

#### **Section 2. Hazards identification**

#### **HSNO** hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

#### **HSNO** classification:

6.3A H315 - Causes skin irritation.

6.4A H319 - Causes serious eye irritation.

6.5B H317 - May cause an allergic skin reaction.

9.1C H412 - Harmful to aquatic life with long lasting effects.

#### **Hazard information**

# **Pictograms and Signal Words**



Warning

#### **Hazard statements:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

# **Precautionary statements:**

P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P321 Specific treatment (see supplementary instructions on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

# Other hazards which do not result in a classification

#### No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 1 of 9

# Section 3. Composition/information on ingredients

# Substances

N.A.

#### **Mixtures**

Mixture identification: KERAPOXY comp.A

# Hazardous components within the meaning of HSNO Act and related classification

Concentration (% w/w)	Name	Ident. Numb.	Classification
≥10 - <20 %		CAS:25068-38-6 EC:500-033-5 Index:603-074- 00-8	6.4A, H319; 6.3A, H315; 6.5B, H317; 9.1B, H411
≥2.5 - <5 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103- 00-4	6.3A, H315; 6.5B, H317
≥1 - <2.5 %	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS:9003-36-5 EC:500-006-8	6.3A, H315; 6.5B, H317; 9.1B, H411
≥0.49 - <1 %	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	5	6.5B, H317; 9.1A, H400; 9.1A, H410

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

# Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

# Section 5. Fire-fighting measures

# Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 2 of 9

Explosive properties: == Oxidizing properties: N.A.

#### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

# **Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

#### Methods and materials for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

# Section 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

# Section 8. Exposure controls/personal protection

# **Workplace Exposure Standards**

# **Predicted No Effect Concentration (PNEC) values**

Component	CAS-No.	PNEC Limit	<b>Exposure Route</b>	<b>Exposure Frequency Remark</b>
	25068-38-6	0,006 mg/l	Fresh Water	
		0,0006 mg/l	Marine water	
		0,0627 mg/kg	Freshwater sediments	
		0,00627 mg/kg	Marine water sediments	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	0,00072 mg/l	Marine water	
		0,0072 mg/l	Fresh Water	
		66,77 mg/kg	Freshwater sediments	
		6,677 mg/kg	Marine water sediments	
		80,12 mg/kg	Soil	
		10 mg/l	Microorganisms in sewage treatments	

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 3 of 9

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	10 mg/l	Microorganisms in sewage treatments
		0,003 mg/l	Fresh Water
		0,294 mg/kg	Freshwater sediments
		0,0003 mg/l	Marine water
		0,0294 mg/kg	Marine water sediments
		0,237 mg/kg	Soil
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5	0,0022 mg/l	Fresh Water
		0,00022 mg/l	Marine water
		0,009 mg/l	Intermittent release
		1,05 mg/kg	Freshwater sediments
		0,11 mg/kg	Marine water sediments

# **Derived No Effect Level. (DNEL)**

Derived No Effect Leve					
Component	CAS-No.	Worker Worke Industr Profes y ional		Exposure Route	Exposure Frequency Remark
	25068-38-6	8,3 mg/kg		Human Dermal	Short Term, systemic effects
		12,25 mg/m3		Human Inhalation	Short Term, systemic effects
		8,3 mg/kg		Human Dermal	Long Term, systemic effects
		12,25 mg/m3		Human Inhalation	Long Term, systemic effects
			3,571 mg/kg	Human Dermal	Short Term, systemic effects
			0,75 mg/kg	Human Oral	Short Term, systemic effects
			3,571 mg/kg	Human Dermal	Long Term, systemic effects
			0,75 mg/kg	Human Oral	Long Term, systemic effects
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5	2,5 mg/kg	1,25 mg/kg	Human Dermal	Short Term, systemic effects
		2,35 mg/m3	0,58 mg/m3	Human Inhalation	Short Term, systemic effects

0,21 mg/kg Soil

1 mg/l

Microorganisms in sewage treatments

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 4 of 9

2,35 mg/m3	0,58 mg/m3	Human Inhalation	Long Term, systemic effects
2,5 mg/kg	1,25 mg/kg	Human Dermal	Long Term, systemic effects
	1,25 mg/kg	Human Oral	Short Term, systemic effects
	1,25 mg/kg	Human Oral	Long Term, systemic effects

### **Engineering Controls**

N.A.

# Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0.4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Thermal Hazards:

N.A.

# Section 9. Physical and chemical properties

Physical state: Liquid

Appearance and colour: paste various

Odour: Characteristic Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: N.A.

Flammability (Solid, Gas): N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: 0.01 Vapour density: N.A.

Relative density: 1.65 g/cm3 Solubility in water: Insoluble Solubility in oil: soluble

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity: 2,000,000.00 cPs Kinematic viscosity: N.A.

Particle characteristics: No data available

# Section 10. Stability and reactivity

#### Reactivity

Stable under normal conditions

# **Chemical stability**

Data not available.

#### Possibility of hazardous reactions

None.

# **Conditions to avoid**

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 5 of 9

Stable under normal conditions.

#### **Incompatible materials**

None in particular.

#### Hazardous decomposition products

# Section 11. Toxicological information

# Information on toxicological effects

# Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

# Toxicological information on main components of the mixture:

a) acute toxicity LD50 Oral Rat > 15000 mg/kg

LD50 Skin Rabbit > 23000 mg/kg

LD50 Oral Rat = 11400 mg/kg

i) STOT-repeated exposure NOAEL Oral Rat = 50 mg/kg

NOAEL Skin Rat = 100 mg/kg

oxirane, mono[(C12-14- a) acute toxicity

alkyloxy)methyl] derivs.

LD50 Oral Rat = 19200 mg/kg

LD50 Skin Rabbit = 4000,00000 mg/kg

Formaldehyde, oligomeric a) acute toxicity

reaction products with 1-chloro-2,3-epoxypropane and phenol

LD50 Oral Rat > 5000,00000 mg/kg

LD50 Skin Rat > 2000 mg/kg

i) STOT-repeated

a) acute toxicity

exposure

NOAEL Oral = 250 mg/kg

Reaction mass of

Bis(1,2,2,6,6pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4piperidyl sebacate LD50 Oral Rat = 3230 mg/kg

# If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

# Section 12. Ecological information

# **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

# List of components with eco-toxicological properties

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 6 of 9

Component Ident. Numb. **Ecotox Infos** 

> CAS: 25068-38-6 a) Aquatic acute toxicity: LC50 Fish > 2 mg/L 96

EINECS: 500-033-5 - INDEX: 603-074-

00-8

a) Aquatic acute toxicity: EC50 Daphnia > 1,8 mg/L 48

a) Aquatic acute toxicity: LC50 Algae > 11 mg/L 72

a) Aquatic acute toxicity: LC50 Daphnia = 1,3 mg/L 96

b) Aquatic chronic toxicity: NOEC Daphnia = 0,3 mg/L

oxirane, mono[(C12-14alkyloxy)methyl] derivs. CAS: 68609-97-2 -EINECS: 271-846-8

- INDEX: 603-103-

00 - 4

a) Aquatic acute toxicity: LC50 Fish > 100,00000 mg/L 96h

a) Aquatic acute toxicity: EL50 Daphnia = 7,20000 mg/L 48h a) Aquatic acute toxicity: EC50 Algae = 843,00000 mg/L 72h

b) Aquatic chronic toxicity: NOEC Algae = 500 mg/L 72h

Formaldehyde, oligomeric reaction CAS: 9003-36-5 -

products with 1-chloro-2,3epoxypropane and phenol

4-piperidyl sebacate

EINECS: 500-006-8

a) Aquatic acute toxicity: LC50 Fish = 5,70000 mg/L 96h

a) Aquatic acute toxicity: EC50 Daphnia = 2,55 mg/L 48h a) Aquatic acute toxicity: EC50 Algae = 1,80000 mg/L 72h

Reaction mass of Bis(1,2,2,6,6pentamethyl-4-piperidyl) sebacate - EINECS: 915-687and Methyl 1,2,2,6,6-pentamethyl- 0

CAS: 1065336-91-5 a) Aquatic acute toxicity: EC50 Daphnia = 20 mg/L 24

a) Aquatic acute toxicity: EC50 Algae = 0,22 mg/L 72 a) Aquatic acute toxicity: LC50 Fish = 0,97 mg/L 96 a) Aquatic acute toxicity: LC50 Fish = 7,9 mg/L 96 a) Aquatic acute toxicity: LC50 Fish = 0,9 mg/L 96

b) Aquatic chronic toxicity: NOEC Daphnia = 6,3 mg/L - 21 d

# Persistence and degradability

#### Persitence/Degradabili Component

ty:

oxirane, mono[(C12-14alkyloxy)methyl] derivs. Readily biodegradable

# **Bioaccumulative potential**

#### Component **Bioaccumulation**

oxirane, mono[(C12-14alkyloxy)methyl] derivs. Not bioaccumulative

# Mobility in soil

NΔ

#### Other adverse effects

N.A.

# Section 13. Disposal considerations

# **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

# Special precautions to be taken during disposal

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information,

24/07/2021 KERAPOXY comp.A Page n. 7 of Date Production Name

contact your local waste authority.

# Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

# **Section 14. Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### **UN** number

N.A.

# **UN proper shipping name**

N.A.

#### Transport hazard class(es)

N.A.

# Packing group, if applicable

NΔ

#### **Environmental hazards**

N.A.

# Special precautions for user

NZS-Subsidiary risks: N.A.

NZS-Special Dispositions:

N.A.

# Road and Rail ( ADR-RID ):

N.A.

ADR-Hazard identification number: NA

Air ( IATA ): N.A.

Sea ( IMDG ):

N.A.

# Section 15. Regulatory information

# **HSNO Approval**

HSNO approval number and group standard title:

HSR002544 - Construction Products (Subsidiary Hazard) Group Standard 2006

# **HSNO** Controls

#### **Approved Handler**

No data available

#### New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

# **Regulatory references**

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Hazardous Substances (Classification) Regulations 2001.

Labelling of Hazardous Substances: Hazard and Precautionary Information (January 2012 EPA0094).

Assigning a Product to a HSNO Approval (May 2013/Revised June 2014).

# Section 16. Other information

Safety Data Sheet dated: 09/06/2021 - version 2

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# Description of the HSNO Classification codes used in section 2 or 3:

6.3A Substances that are irritating to the skin.

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 8 of 9

6.5B	Substances that are contact sensitisers.
9.1A	Substances that are very ecotoxic in the aquatic environment. $ \\$
9.1B	Substances that are ecotoxic in the aquatic environment.

Substances that are irritating to the eye.

9.1C Substances that are harmful in the aquatic environment.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

6.4A

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

HSNO: Hazardous Substances and New Organisms Act 1996.

# Paragraphs modified from the previous revision:

- Safety Data Sheet
- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 5. FIRE-FIGHTING MEASURES
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Date 24/07/2021 Production Name KERAPOXY comp.A Page n. 9 of 9